



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 1, January 2024

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.423



9940 572 462



6381 907 438



ijirset@gmail.com



www.ijirset.com

A Methodology for Quality Evaluation of user Experience in Virtual Reality: Metrics, Tools, and Validation

Komal Jasani

QA Engineering Lead, USA

ABSTRACT: Because VR is used in education, healthcare, architecture, and entertainment, strong evaluation techniques to measure users' feelings are very important. Because of immersion, presence, embodiment, and sensory feedback, the main issues in VR make UX evaluation different from conventional approaches. Here, we cover a complete approach to assessing the quality of UX in VR, which uses all three metrics. It looks at modern and old data collection tools such as sensors, eye-tracking systems, and software, explaining how they help designers gather user information. A detailed sequence of steps is presented so researchers and developers can perform scenario design, create participants' profiles, synchronize the data, and conduct multimodal analysis.

Additionally, the paper explores the main concerns in the reliability and verification of UX evaluation techniques, including test-retest reliability, internal consistency, and cross-modal correlation. The framework works to provide both researchers and industry professionals with methods and software that make VR experiences easier to use, more responsive, and more engaging for everyone. The paper discusses possible developments, including AI for predicting user experience and adaptive systems that update in real-time while constantly promoting ethical treatment and uniformity in VR systems.

KEYWORDS: Virtual Reality, User Experience Evaluation, Immersion, Presence, Biometric Data, UX Metrics, VR Usability

I. FOUNDATIONS OF UX IN VIRTUAL REALITY

Other systems' usability and design features do not fully describe User Experience (UX) in Virtual Reality (VR). Traditional 2D screens lack the same full three-dimensional experience as VR, which immerses users, acts on several senses, and creates a real sense of presence. Since the way people interact has changed so much, we must change our understanding of experience and how we measure it.

UX in VR relies on how someone uses their senses, feels, thinks, and interacts with virtual surroundings. How people respond depends on the interface, how realistic the virtual scene is, how user actions are interpreted, how closely feedback reflects what the user does, and how complete their expectations are.

Table 1: Core Dimensions of UX in VR and Their Definitions

UX Dimension	Description
Presence	The subjective feeling of "being there" in the virtual environment
Immersion	The objective level of sensory fidelity and system realism
Usability	Ease with which users can interact and achieve goals in the VR system
Engagement	Emotional and cognitive involvement in the VR experience
Embodiment	The sense of ownership and control over a virtual body
Motion Comfort	The absence of simulator sickness or discomfort during movement

Being present is the main concept in VR UX, meaning you feel like you are in that environment. The sense of being in the VR world is often considered the main feature of good design. It depends on good spacing, instant reactions, and junctionless experience (i.e., experiences that do not break the illusion). Immersion is closely connected to presence and describes the technical and visual depth of the virtual world. Immersive experiences are made possible by combining high-definition graphics, large field-of-view headsets, an un-fixed sound, and haptic feedback.

Embodiment refers to the extent to which someone feels that a virtual character (avatar or similar) represents them. If users think of their virtual body as a part of themselves, interactions with others in the metaverse are simpler and easier. VR applications used in therapy, remote teamwork, and social scenes through avatars all depend greatly on embodiment.

The way you interact with each other matters a lot. In VR, people reach, hold, move, and interact with objects in three dimensions. For edge computing to work well, gestures should trigger actions quickly in the virtual environment. Interaction models and jitter that aren't in sync with real movement can be annoying and quickly pull you out of the experience. As a result, making controls that are easy to use and follow naturally in VR is very challenging.

When designing for VR UX, developers must consider the burden on the user's mind, possible sickness from motion, and their feelings. When a VR application has poor performance or inconsistent visual or body movement signaling, a person might feel nauseated and dizzy. A virtual environment's emotional feel, which may be soothing or engaging, greatly influences how content users are and whether they will keep using it.

Using ISO 9241-210 as a guide, human-centered design works well in VR. Even though HCI was its original focus, this standard ensures that VR, too, is usable and useful and provides satisfaction for its users. Yet, as virtual reality is unique, additional measures must cover presence, immersion, and sensorimotor coherence.

The situation in which the software will be used matters as well. UX in a medical training VR app will have little in common with UX in games. The situation affects the difficulty of tasks, the user's hopes for feedback, and the kinds of feedback that matter the most. As a result, we need to create UX evaluation methods tailored to a particular field that are still useful for many applications.

We must remember that experience happens over time. People's reactions to VR usually develop throughout using it. Beginning a relationship can be exciting, which often fades as time passes, and continuing a relationship for weeks can tire people. Therefore, UX evaluations should occur when users react shortly and when their adoption happens with time.

Making VR accessible to all is fundamental in the field of foundational UX. Not all users are equally able regarding physical skills, how well they think, or their senses. A universal design strategy can support different kinds of VR users and guarantee that VR is fun and user-friendly for many people.

All in all, the key parts of UX in VR include visual, mental, physical, and emotional features. These elements should always be studied and evaluated in a structured way. You must use traditional UX approaches and standards while adding VR elements to design experiences that are memorable, robust, and open to all. Paying attention to these core areas allows us to create solid evaluation approaches that record everything that makes virtual user experiences distinct.

Figure 1: The Relationship Between System Components and UX in VR



II. METRICS FOR EVALUATING UX IN VR

Since VR pulls us in deeply, looking at its use should consider different aspects of what it feels like and how it behaves. Traditional devices are mainly controlled through the fingers, but VR uses full-body movements and visual, audio, and sometimes touch input. For that purpose, UX metrics for VR should consider more than usability tests, like how people react, the overall functioning of the software, and what users do. Such VR UX metrics make it easy to assess how VR experiences function.

Subjective Metrics

When people fill out subjective metrics surveys, they tell us how they truly feel and think about VR. Many survey participants use forms, participate in interviews, or interact with computer interfaces during an activity. They are used to learn about people's emotions, their ability to use a game, how much enjoyment they get, and their levels of engagement.

Applying a subjective technique, the PQ measures mood in the virtual experience for the user. Having presence means being involved in something, noticing things around you, and being able to guide what is unfolding. In addition, the Igroup Presence Questionnaire (IPQ) measures your sense of being in the environment, engagement, and lifelikeness, allowing you to evaluate and compare presence in many contexts.

At first, the System Usability Scale (SUS) was designed for 2D layouts, but it is now regularly used in VR contexts to evaluate usability. At the same time, VRUSE looks at variables like ease of movement, pressure experienced by users, and understanding of where they are.

VR activity designers, mainly working with entertainment and training, pay close attention to flow state and personal happiness. One can create FSS questions using a Likert scale to study these emotions. The Simulator Sickness Questionnaire can determine if someone feels discomfort, unease, or nausea after using VR.

Objective Metrics

Objective measurements tell us how users move and behave in certain tasks. Because these tools can be programmed, you do not need user perception, making it simple and fast to test VR across a large scale.

Performance on a task, such as time used, number of errors, the number of times a task is successful, and how smoothly it was done, is evaluated with primary objective metrics. In VR training simulations, we can determine a user's skill in using software by watching their progress as they perform a task.

The user's insights are better understood by using physiological data. Because of frequent practice, HRV, EDA, skin conductance, EEG, and EMG are commonly used to detect stress, engagement, arousal, and attention. As a result, it becomes clear if a user is experiencing anxiety, calmness, or is overwhelmed, which changes how training, therapy, or education is delivered.

In current VR headsets, tracking eye movement makes it possible to spot what a user is looking at, for how long, and their movement around the virtual space. They help you see how a website interface is built, how people react, and what they do when given options. As gaze analysis generates heatmaps, they can be added to virtual scenes to help determine the user's focus, with action taken as necessary.

Using motion tracking is an essential form of objective recording. You can tell a lot about someone's skill and energy level by the way they move the tool. A user's path, gesture accuracy, and speed in using the system indicate how simple or hard it is to use.

Table 2: Commonly Used UX Metrics in VR Evaluations

Metric Type	Specific Metrics	Measurement Tool or Scale
Subjective	Presence, satisfaction, workload	Presence Questionnaire, SUS, NASA-TLX
Objective	Task time, error rate, gaze fixation	System logs, eye-tracking software
Physiological	Heart rate variability, GSR	Biopac, Empatica, Shimmer
Behavioral	Movement smoothness, task completion flow	Motion tracking logs, Unity events

Behavioral Metrics

Between people's views and physical data lies behavioral measurement. They show what happens when users are online and can indicate problems with the site's design.

How well people navigate in virtual reality can help us see how easily they can adapt. Counting the character's movement paths, the amount of collisions, and where it spends the most time can hint that game space is difficult to

arrange. Users who follow the same sections repeatedly or skip different locations might get confused, lost, or uncomfortable.

You can observe behaviors from the way logs show people interrelating. If a piece of equipment often needs reviewing during an activity, you perform a step more than once or spend a lot of time doing tasks; this can result from poor affordances, extra information, or not understanding guidance.

In addition to studying what people say, a few scholars recommend looking at movement and gestures to understand engagement. Touching virtual items with their movement is a common sign that users are enjoying the game. A set poor posture might mean concentrating is tough or the workplace is not designed well.

Behavior often reflects someone's mood. In military virtual reality training and treating phobias, anxiety or fear can be recognized by sudden increases in body movements, quick head turning, or quick withdrawal from the scene.

Usage of Multimodal Evaluation

Considering different data areas is useful, but seeing the data from various perspectives is important for a proper VR evaluation. If the passenger's heart rate rises, they say they feel stressed, and their navigation becomes unusual, it could mean something with the environment is triggering the passenger's emotions.


Lining up data from various sources is technically tough, but current biometric, VR software, and event-logging options greatly help. By following the user's physiology over time, researchers can discover how in-space occasions influence the user's actions.

Challenges and Consideration

Even though they are pretty good, it's important to recognize that UX measurements in VR are still not flawless. While physiological readings can be confirmed, they often do not help us tell one emotion from another, such as when a person feels both excited and scared. People's accounts may be affected by their memory, mood, or desire to present things as they are seen. Even though behavioral observations reveal information about individuals, we should take this information in context.

Since people's reactions to VR are unique, any report on user experience should be statistically powerful and serve a wide range of users. That means we should use a well-structured process that adjusts to various situations.

All in all, considering UX for VR involves watching for users' feelings, how much they learn, and the actions they complete. Examining these metrics as a group allows us to build VR systems that are enjoyable, effective, and simple for users.



Graph 1: Comparative Bar Chart: Subjective vs. Objective UX Scores Across VR Systems

III. TOOLS AND TECHNOLOGIES FOR UX DATA COLLECTION IN VR

Assessing how users experience virtual reality requires utilizing many tools and technologies that record a broad range of user inputs, responses, and behaviors. Such tools should consider that VR is highly immersive, involves many senses, and involves the full body, changing how data can be collected. As the field becomes more advanced, several types of hardware and software are now available, including eye trackers, wearable biometric sensors, and loggers for telemetry. Every tool helps to understand how people notice, use, and react to what virtual environments provide.

HMDs form the core of virtual reality, and today's models include various sensors. Some devices, such as the Meta Quest Pro, HTC Vive Pro Eye, and Varjo XR series, include eye tracking, pupillometry, and the ability to track facial expressions. The exact monitoring of people's sight with eye-tracking reveals their attention patterns, pupil response, and mental workload. Collecting real-time gaze data allows researchers to determine which locations hold attention, how long users look at them, and how tuned the scene design is to their expectations.

Gaze tracking and motion tracking contribute importantly to understanding user behavior. Data from inside-out and outside-in trackers reveals how participants move their heads, hands, and whole bodies, along with their navigation, interaction, gesture use, and level of physical participation. Sub-millimeter accuracy is possible with movements captured by controllers such as the Valve Index and Oculus Rift. By relying on Vive Trackers or OptiTrack cameras, full-body tracking helps assess body movement with great detail, which greatly matters in rehabilitation, sports training, and ergonomics testing.

VR test results have become more realistic because of wearable biometric devices. EDA sensors, heart rate monitors, EEG headbands, and EMG devices can all be connected to a VR setup to check the user's condition. The Empatica E4 wristband, the Shimmer3 GSR+ unit, and the Muse EEG headsets gauge stress, how much mental work someone is doing, and emotions in real time. With this information, you can study the users' responses and show them skills in pressure situations. Feedback involving our bodies is significant in exposure therapy, military exercises, and when immersive stories are important.

Table 3: Summary of Key Tools for VR UX Evaluation

Tool/Platform	Data Captured	Integration Level	Example Devices
Eye-Tracking	Gaze, pupil dilation	Built-in (HTC, Varjo)	Tobii Pro, Vive Eye
EEG	Attention, engagement	External	Emotiv, OpenBCI
Motion Tracking	Position, posture	Built-in or external	OptiTrack, Leap Motion
Software Logging	Events, interaction logs	Custom/engine-native	Unity Analytics, Unreal Logger
Multimodal Sync	Time-aligned sensor data	High	iMotions, LabStreamingLayer

Using behavioral and interaction data best means using software-level telemetry tools. Developers and researchers can use Unity Analytics, the data logging tools in Unreal Engine, and third-party SDKs like Cognitive3D and iMotions to monitor every click, trigger, movement, and object interaction within the VR environment. Usually, these tools supply pre-built visual analytics dashboards and allow users to tag custom events. Cognitive3D is designed for this purpose, showing where users focus their attention, telling us how they use the game and where they regularly falter.

Audio data is not often used, yet it can still give valuable insights into UX. People's speech usually shows if they are comfortable, engaged, or confused during a conversation. VR sets that can communicate in natural words or play with others using voice chat are improved by including Affectiva's or Beyond Verbal's speech analysis technology.


Getting data from all the sources into one system is a major tech problem when evaluating VR UX. Eye trackers, EEG systems, and telemetry loggers could use different rates at which to sample and ways to assign time stamps. This problem can be managed by using LabStreamingLayer (LSL) and OpenSync to link the data streams from various sources. Thanks to this, VR actions can match the biometric reactions of users at very precise points during the experience.

New cloud-based analytics and machine learning models are added to help traditional tools. A few systems can process data live and react to changes in the environment due to the user's mood. The space may calm down or present useful hints if the system detects anxiety from someone's heart rate or eye movements. With data constantly streaming in and AI checking the results, these adaptive interfaces offer the best VR UX evaluation seen thus far.

Although much better tools are available, we must address important practical factors. Choosing the right tools considers the target group, what you hope to achieve, and what resources are available. EEG can be hard for regular users because it's invasive and difficult to put on, and tracking someone's eyes with glasses could give inaccurate results. The system should be simple, gentle on the user, and able to resist problems caused by movement.

Simply put, VR UX data-gathering tools and technologies are both advanced and always progressing. We can use an HMD with eye tracking, motion capture, wearable biosensors, telemetry analytics tools, and synchronization systems to manage and assess every detail of the user experience. To improve design, increase user involvement, and ensure VR applications are accessible, it will become very important to determine UX accurately.


Figure 2: Multimodal UX Data Collection Pipeline in VR



IV. A METHODOLOGY FOR COMPREHENSIVE UX EVALUATION IN VR

A good approach to assessing user experience in virtual reality combines different disciplines to equally evaluate individual feelings and objective facts about how people use technology. Unlike in the past, in VR, users are involved in a full, sensorimotor experience that makes it important for evaluation to focus on physiology, behavior, and cognition. In other words, a proper way to do this requires covering four closely linked efforts: planning, carrying out experiments, getting the data, and analyzing and understanding the results.

Figure 3: End-to-End Methodology for Comprehensive UX Evaluation in VR



Every good UX evaluation is built on a clear set of goals. The objectives should state which part of the virtual reality experience will be evaluated—such as how easy it is to use, its level of presence, the emotions it creates, or how effectively users complete tasks—and which sections of the market you want to focus on. Evaluating how VR is used for emergency training requires different measurements than assessing its use in a VR therapy that treats anxiety. If research objectives are connected to the use context, the framework for evaluation stays focused and can be applied to other situations in the same field.

Once objectives are chosen, you then design the experimental protocol. Part of this process is. Volunteer participants should match what the common user will likely be by including age, gender, awareness of VR, and other abilities. It is necessary that task design represents real examples and is standardized for repeatability during various sessions. A protocol list should have guidelines for the time participants are exposed, the order of different tasks and breaks, and, most importantly, to ensure safety when you collect physiological data.

Using the right tools is very important in the evaluation of user experience. User experience is best checked by using a range of research methods together. VR equipment may be equipped with eye trackers, heart rate and skin conductance measurements, motion drivers, and logging software to capture everything simultaneously. The main challenge is ensuring all these devices happen simultaneously to pair user actions, in-game actions, and body reactions. If capturing an electrodermal reaction helps a person's stress, it should be linked to something observable in the virtual environment.

During data collection, things are carefully controlled. First, the participants learn why the study is being carried out, and only then do they consent, specifically for biometric or behavioral testing. It is necessary to calibrate devices so that your readings are correct. Once the VR session starts, researchers notice if users look uncomfortable, confused, or tired, all while letting them interact with the environment easily. As the VR system is run, gaze information, interaction time, and physical signals are logged side by side with the event logs from the program itself. Participants are given standardized questionnaires regularly or after their session to rank aspects such as presence, usefulness, satisfaction, and likelihood of motion sickness. Administrators can pick from the Simulator Sickness Questionnaire (SSQ), Presence Questionnaire (PQ), or NASA-TLX workload scale for their evaluation goals.

You can interview them or offer an open questionnaire to investigate users' feelings. Such insights usually bring to light problems, great memories, or ways of thinking that numbers alone might miss. Repeated assessments let researchers see if VR helped the subject maintain their learning, emotions, or behavior.

During the synthesis and interpretation stage, input from subjective comments, tracked activities, body monitoring, and completed tasks are all merged into one overall evaluation. Statistical tools help us see patterns, relationships between things, and unusual observations. When we see that task completion time is long, the mental effort is high, and skin conductance is up, it may mean that the VR interface is challenging to use. Another situation where this happens is when players finish activities too quickly and score low on involvement. Using multiple insights together gives us a better picture of user experience than depending on just one type of information.

Researchers often sort and study these datasets by relying on platforms that link and display different data collections. Supporting processes of interpretation and design by using gaze heatmaps, patterns of attention engagement, or time-series plots of biometric readings. Patterns in UX data are now being spotted thanks to machine learning, such as classifying user profiles or flagging possible discomfort from things like user activity. Special attention must be given to ensuring such models can be easily understood and explained, mostly in cases involving vulnerable groups or confidential uses.

The method should be designed as the final step so feedback can return to the process. Users' needs and suggestions should be described to the teams in a way that directors can take action on. Some examples are updating the game interface, making storytelling more even, setting balance for different levels of challenge, or optimizing how players receive sensory signals. The approach should change as you learn from applying it, improving data tools and tasks, or including new metrics as technology improves.

Ethics is important at every stage of the UX evaluation process. The strong involvement in VR may cause strong feelings in users, which is why safety for participants is essential. Experts must pay attention to any hints of ill effects and end the session without hesitation. Another significant concern is data privacy, which appears when working with biometric or behavioral data. For data to be handled correctly, companies must have clear and trusted data use policies.

In short, evaluating user experience in VR means using various approaches built on iteration. You need to plan well, measure accurately, and combine information from several types of tests when conducting one. Since this methodology observes how perception, action, emotion, and cognition work together, developers and researchers can design good and caring VR systems for their users.

Table 4: Sample UX Evaluation Protocol Matrix

Task Name	Objective	Metrics Captured	Devices Used	Time Allocated
VR Navigation Task	Assess spatial usability	Task time, motion logs	Vive Tracker, Unity	5 min
Emotion Induction	Evaluate engagement/arousal	GSR, HRV, self-report	Empatica, SSQ	4 min
Object Interaction	Evaluate gesture accuracy	Task errors, gaze	Leap Motion, EyeLink	6 min

V. VALIDATION AND RELIABILITY OF UX EVALUATION METHODS IN VR

Because user experience (UX) is very important to development and study in virtual reality (VR), finding accurate and dependable evaluation approaches is more important than ever. Because VR stimulates the senses, invites user interaction, and creates psychological involvement, any UX research findings must be supported by scientifically correct approaches. Here, I examine ways to prove that VR UX evaluation methods are accurate and repeatable, including the kinds of Validity involved, practical tools to check reliability, different validation tactics, and points to consider when applying the methods in real situations.

Understanding Validity in VR UX Evaluation

Validity is about how correctly a test or instrument records the concept it is designed to test. Because evaluating VR UX uses various kinds of data, such as perception, behavior, and reactions, it is important to check multiple Validity dimensions.

1. Construct Validity

The concern is whether the tool measures what it says it measures psychologically. Is the Igroup Presence Questionnaire (IPQ) measuring the presence, or are novelty and technological expertise mixed with the measurements? Experts need to link their chosen measures to properly defined concepts and confirm them by using factor analysis or comparing them with values set by similar research.

2. Content Validity

It evaluates whether the evaluation methods consider all important aspects of how users use the system. A UX study concentrating on usability but not users' feelings might not reflect the right data. Examples of frameworks that reach more topics are ISO 9241-210 or the UX Honeycomb Model.

3. Criterion Validity

The score from the measurement is related to how accurately it predicts an outcome from another source. High usability scores in a VR survey regularly lead to improved user outcomes in practice, which strongly indicates the instrument's criterion validity.

4. Ecological Validity

Since VR uses artificial worlds, the experience must be ecologically valid. An excellent and authentic VR scenario must hold users' attention and correctly represent the world's constraints and decision-making methods. Giving the tool to targeted users in their habitual environments can show its effectiveness in practice.

Establishing Reliability in VR UX Evaluation

Reliability means a measurement gives the same results when all conditions are identical. Making UX in VR reliable requires using dependable tools and evaluating the process similarly.

1. Internal Consistency

With this, Cronbach's alpha is used to determine if different questions within the same test give results that agree. An example of good design is when a presence questionnaire shows consistent results between its subscales: spatial presence, involvement, and realism.

2. Test-Retest Reliability

The purpose is to measure if the same test evaluates participants the same both times it is given. Test-retest reliability is needed for measures such as heart rate and EDA because keeping all background conditions and anxiety constant is important.

3. Inter-Rater Reliability

This measurement confirms that different people recording activities have similar understandings of what is happening. Good coding practices and learning should be followed when examining user gestures, voices, or emotions in virtual reality.

4. Temporal Stability and Sensor Calibration

Reliability of the sensors is an important issue with physiological devices. The sensors in wearables, such as EEG headsets or EDA sensors, must be regularly calibrated and tested for stable measures over time to ensure all changes are due to how people use them, not hardware issues.

Strategies for Validation and Reliability Assurance

Researchers and developers who want accurate and reliable UX evaluations in VR should use some common best practices.

Using both subjective questionnaires, tracking drivers' actions, and recording their physical signals helps to check whether the findings are consistent. The conclusion will be made stronger if a survey reports high engagement, and these outcomes are supported by reduced blinking and high interaction levels.

Running pilot tests before main studies ensures that measurement does not produce conflicting results and that the study design is correct. Determining good data collection windows and the level of user discomfort is another duty of pilots.

Fixed methods for conducting evaluations, using sensors, and setting up VR systems to minimize session differences. Scripted data capture using Unity and similar tools makes procedures more trustworthy. Researchers should run the studies again and compare their findings with known standards to make results more reliable and applicable to different users.

If a new tool is put together, official validation studies should occur. Again, it may rely on exploring and confirming factors using analysis, testing how precise and accurate the tool is, and making the test results agree with standard approaches.

A reliable assessment in VR UX depends mainly on validation and reliability. As VR experiences involve multiple modes, researchers must test their instruments skillfully to see if they record the target variables accurately each time. Using construct alignment, sensor calibration, and data triangulation allows developers and UX specialists to rely on their results when making design choices, boosting user interactions and lowering the risks associated with launch.

VI. FUTURE TRENDS AND RESEARCH DIRECTIONS


With VR developing and maturing, the techniques used to assess user experience (UX) must also improve. Better UX evaluation in VR is enabled by progress in artificial intelligence, adaptive interfaces, sensors, and ethical guidelines for immersive technology. Because of these coming trends, the field will go from capturing static data afterward to using live insights to inform dynamic virtual experiences.

One important change is bringing machine learning and AI into assessing UX. Using biometric signals, interaction reports, and eye movement patterns in big datasets, AI can spot complex behavior patterns and predict emotions, how much effort is needed to complete a task, or what a person's accomplishment levels are. Because of this, VR

experiences can instantly adapt to what individual people like or need, creating a focus on uncomfortable or uninteresting experiences.

Thanks to edge computing and wearable biosensors, UX monitoring can now be achieved over a long period. Because lightweight EEG devices, eye trackers, and GSR wearables are more available, researchers can measure physiological responses in natural situations. With the help of embedded edge AI processors in VR headsets, this capability lets VR apps run processing on the device to improve performance, maintain user privacy, and enable useful environment analysis during real-time VR use.

Graph 2: Radar Chart: Aggregated UX Scores Across Evaluation Dimensions



As the VR environment grows more scattered with different platforms, devices, and types of content, users are focusing more on making things standard and compatible. In the future, research should aim to design open UX evaluation frameworks and APIs that can be added to different VR engines, allowing data to be gathered and analyzed similarly. As a result, benchmarking, testing how well the ecosystem works across platforms, and team research becomes easier. Longitudinal research into UX is showing great potential. Today, VR UX researchers mainly focus on first impressions after one use, but future work will focus on looking at experience changes over a longer time. In healthcare, education, and enterprise training, what's most important is how well people retain their skills and continue to engage with the course rather than just their first engagement. A varied study can help us see how their skills change, how much they get tired of using the tool, and how they learn to use it, all of which can be used to design for continued and effective use.

Being fair and including all perspectives will soon be central to UX research in VR. Making immersive systems available to different groups of people requires ensuring accessibility, respect for cultures, and enough psychological safety. Research should include studies comparing how people of various ages, genders, abilities, and cultures interact with VR and suggest methods to assess those differences without favoritism.

In short, VR UX evaluation is shaped by smart, steady, inclusive, and ethical approaches. This development allows both designers and researchers to make virtual worlds that are engaging and equitable and that share human values.


VII. CONCLUSION

Unique issues and promising changes can be found when evaluating virtual reality (VR) user experience. Since immersive environments are changing how we use digital tools, we need stronger, dependable, and detailed UX evaluation techniques. This article explains the main areas of UX in VR, outlines key ways to assess it, looks at major tools and technologies, and introduces a clear process for understanding the subjective, behavioral, and physiological data gathered during user experiences. Furthermore, we considered how to ensure findings are valid and reliable and support the science. We believe fields like AI analytics, adaptive software, and design that respect all users and their values will play growing roles in HCI.

Evaluating UX in VR requires methods surpassing the typical usability testing process. It needs to be studied in a way that highlights being there, feeling part of the experience, having emotions, and making lasting changes in behavior. Researchers and practitioners can better understand how users react in virtual environments using many methods and new technological tools.

As VR moves to education, healthcare, and business, the quality of how users feel will determine how well the system performs, is accepted, and is trusted. A strong and flexible methodology will help us use VR at its best. Essentially, a full UX review does much more than measure results—it guides us in building safe and enjoyable virtual scenarios for people.

Figure 4: Feedback Loop Diagram: UX Insights to Design Improvements



REFERENCES

1. Bailenson, J. N., Yee, N., Blascovich, J., Beall, A. C., Lundblad, N., & Jin, M. (2008). The use of immersive virtual reality in the learning sciences: Digital transformations of teachers, students, and social context. *The Journal of the Learning Sciences*, 17(1), 102–141. <https://doi.org/10.1080/10508400701793141>
2. Brooke, J. (1996). SUS: A “quick and dirty” usability scale. In P. W. Jordan, B. Thomas, B. A. Weerdmeester, & A. L. McClelland (Eds.), *Usability evaluation in industry* (pp. 189–194). London: Taylor & Francis.
3. Cummings, J. J., & Bailenson, J. N. (2016). How immersive is enough? A meta-analysis of the effect of immersive technology on user presence. *Media Psychology*, 19(2), 272–309. <https://doi.org/10.1080/15213269.2015.1015740>

4. Freeman, J., Avons, S. E., Meddis, R., Pearson, D. E., & IJsselsteijn, W. A. (2000). Using behavioral realism to estimate presence: A study of the utility of postural responses to motion stimuli. *Presence: Teleoperators and Virtual Environments*, 9(2), 149–164. <https://doi.org/10.1162/105474600566691>
5. Hart, S. G., & Staveland, L. E. (1988). Development of NASA-TLX (Task Load Index): Empirical and theoretical research results. In P. A. Hancock & N. Meshkati (Eds.), *Human mental workload* (pp. 139–183). Amsterdam: North-Holland.
6. IJsselsteijn, W., de Ridder, H., Freeman, J., Avons, S. E., & Bouwhuis, D. (2001). Effects of stereoscopic presentation, image motion, and screen size on subjective and objective corroborative measures of presence. *Presence: Teleoperators and Virtual Environments*, 10(3), 298–311. <https://doi.org/10.1162/105474601300343333>
7. ISO. (2010). ISO 9241-210: Ergonomics of human-system interaction—Part 210: Human-centred design for interactive systems. Geneva: International Organization for Standardization.
8. LaViola, J. J. (2000). A discussion of cybersickness in virtual environments. *ACM SIGCHI Bulletin*, 32(1), 47–56. <https://doi.org/10.1145/333329.333344>
9. Makransky, G., Terkildsen, T. S., & Mayer, R. E. (2019). Adding immersive virtual reality to a science lab simulation causes more presence but less learning. *Learning and Instruction*, 60, 225–236. <https://doi.org/10.1016/j.learninstruc.2017.12.007>
10. Slater, M., & Wilbur, S. (1997). A framework for immersive virtual environments (FIVE): Speculations on the role of presence in virtual environments. *Presence: Teleoperators and Virtual Environments*, 6(6), 603–616. <https://doi.org/10.1162/pres.1997.6.6.603>
11. Witmer, B. G., & Singer, M. J. (1998). Measuring presence in virtual environments: A presence questionnaire. *Presence: Teleoperators and Virtual Environments*, 7(3), 225–240. <https://doi.org/10.1162/105474698565686>
12. Baños, R. M., Botella, C., Guerrero, B., García-Palacios, A., & Quero, S. (2004). Presence and emotions in virtual environments: The influence of stereoscopy. *CyberPsychology & Behavior*, 7(6), 734–741. <https://doi.org/10.1089/cpb.2004.7.734>
13. Brooke, J., Jordan, P., Thomas, B., Weerdmeester, B., & McClelland, A. (1996). SUS: A quick and dirty usability scale. *Usability Evaluation in Industry*, 189–194.
14. Cummings, J. J., & Bailenson, J. N. (2016). How immersive is enough? A meta-analysis of the effect of immersive technology on user presence. *Media Psychology*, 19(2), 272–309. <https://doi.org/10.1080/15213269.2015.1015740>
15. Gaggioli, A., Cipresso, P., Serino, S., Riva, G., & Bonanno, D. (2014). Neurophysiological correlates of presence and emotion in virtual environments: A review. *Cognitive Processing*, 15(2), 99–107. <https://doi.org/10.1007/s10339-013-0593-z>
16. Hughes, C., & Ware, C. (2019). Sensor technologies for physiological data capture in virtual reality. *Frontiers in Virtual Reality*, 1, Article 4. <https://doi.org/10.3389/frvir.2020.00004>
17. Nacke, L. E., Drachen, A., & Göbel, S. (2010). Methods for evaluating gameplay experience in a serious gaming context. *International Journal of Computer Science in Sport*, 9(2), 1–16.
18. Patel, H., & Patel, P. (2021). A review on psychophysiological measurement techniques in virtual reality environments. *Journal of Ambient Intelligence and Humanized Computing*, 12, 4443–4465. <https://doi.org/10.1007/s12652-020-02504-7>
19. Riva, G., & Mantovani, F. (2014). Extending the self through the tools and the others: A general framework for presence and social presence in mediated interactions. In M. Slater & S. J. Bailenson (Eds.), *The Oxford Handbook of Virtuality* (pp. 39–54). Oxford University Press.
20. Santos, P., Oliver, J., & Pimentel, J. (2019). Evaluating presence in virtual reality through physiological and behavioral measures. *Computers in Human Behavior*, 95, 114–121. <https://doi.org/10.1016/j.chb.2018.12.009>
21. Slater, M. (2009). Place illusion and plausibility can lead to realistic behavior in immersive virtual environments. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 364(1535), 3549–3557. <https://doi.org/10.1098/rstb.2009.0138>
22. Smith, S. P., & Du'Mont, S. A. (2019). Validation and reliability of virtual reality usability assessment tools: A systematic review. *Journal of Usability Studies*, 14(2), 55–71.
23. Witmer, B. G., Jerome, C. J., & Singer, M. J. (2005). The factor structure of the presence questionnaire. *Presence: Teleoperators and Virtual Environments*, 14(3), 298–312. <https://doi.org/10.1162/1054746053967094>
24. Zhao, B., & Azari, P. (2020). Real-time affective state recognition in virtual reality using EEG. *IEEE Transactions on Affective Computing*, 11(3), 436–446. <https://doi.org/10.1109/TAFFC.2018.2866924>



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details