



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

# IJIRSET

International Journal of Innovative Research in  
**SCIENCE | ENGINEERING | TECHNOLOGY**



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 11, November 2024

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

**Impact Factor: 8.524**



9940 572 462



6381 907 438



ijirset@gmail.com



www.ijirset.com

# Semantic Model Migration Patterns: Converting Legacy Repository (RPD) Structures for Modern Analytics Server Platforms

Baleeswara Bolleddula

Senior Oracle Applications Database Administrator, USA

**ABSTRACT:** Enterprise analytics platforms built on Oracle Business Intelligence Enterprise Edition (OBIEE) carry substantial intellectual capital embedded in their Repository (RPD) files - thousands of physical connection definitions, logical business model objects, calculated measures, multi-level hierarchies, and presentation layer subject areas. Migrating these artefacts to Oracle Analytics Server (OAS) or equivalent modern analytics platforms demands systematic pattern recognition, semantic-preserving transformation rules, and rigorous quality validation that ad-hoc manual migration cannot reliably deliver. This paper introduces a catalogue of seven primary migration patterns covering the full RPD object taxonomy, a three-phase migration framework (Classify, Transform, Validate), and empirical evaluation across 38 enterprise migration projects. Results demonstrate 88.7% automated object migration fidelity, 94.2% semantic lineage preservation, and mean project duration reduction from 18 weeks to 8 weeks when the pattern catalogue is applied systematically.

**KEYWORDS:** RPD migration, OBIEE, Oracle Analytics Server, semantic model, logical layer, dimensional modelling, metadata transformation, analytics platform migration

## I. INTRODUCTION

The Oracle Business Intelligence Enterprise Edition platform, commercially dominant in enterprise analytics deployments since its 2007 release, encodes the entire semantic layer of an organisation's analytical capability within a proprietary binary Repository file format. An RPD file may contain thousands of physical-layer connection pools, hundreds of logical-layer business model tables with complex multi-source joins, elaborate hierarchical dimension structures, session-variable-driven security filters, and thousands of presentation-layer subject areas and columns visible to end users. This accumulated configuration represents years of institutional knowledge that must be preserved - not just migrated - when organisations transition to modern analytics server platforms.

Despite the strategic importance of RPD migration, the discipline lacks a systematic pattern language. Migration projects are typically executed either through vendor-supplied upgrade utilities with limited scope, or through manual re-creation that is expensive, error-prone, and unable to scale to large repositories. Neither approach addresses the semantic fidelity challenge: whether the migrated model produces identical query results for identical user requests across all report types and dimensional navigation paths.

1. Vendor upgrade utilities typically handle direct-map objects (data sources, simple tables) but fail on complex calculated measures, multi-level hierarchies, and cross-subject-area references.
2. Manual re-creation projects average 18 weeks for mid-sized repositories (500–2,000 logical objects) and produce regression defect rates of 22–41% in initial testing cycles.
3. Semantic fidelity failures - where migrated models return different results than source RPDs for the same query - cause more business disruption than object migration failures, yet are measured less systematically.
4. The absence of a pattern catalogue means each migration team independently re-discovers the same transformation patterns, accumulating effort without cross-project learning.
5. Governance of the migration process - audit trails, lineage preservation certificates, and rollback procedures - is absent from current migration tooling and practice.

This paper addresses these gaps through three contributions: a comprehensive migration pattern catalogue (seven primary patterns, 23 sub-patterns) derived from analysis of 38 enterprise migration projects; a three-phase framework (Classify,

Transform, Validate) that operationalises the catalogue in a repeatable process; and empirical evaluation demonstrating the framework's effectiveness.




Figure 1. RPD to modern analytics server migration architecture showing the migration engine between legacy RPD three-layer structure and modern OAS semantic model.

## II. RPD ARCHITECTURE AND MODERN ANALYTICS PLATFORMS

### 2.1 The RPD Three-Layer Model

Oracle OBIEE organises semantic metadata in a strict three-layer hierarchy within the RPD. The Physical Layer defines connectivity to data sources through connection pools, physical database objects, physical tables, physical columns, and physical joins - the structural representation of the underlying relational schema as seen by the BI server. The Business Model and Mapping Layer transforms the physical representation into a business-friendly logical model: logical tables (which may draw from multiple physical tables via complex mappings), logical columns, measure aggregation rules, logical joins, level-based hierarchies, and dimension-specific aggregation content specifications. The Presentation Layer exposes a subset of the business model to end users through subject areas, presentation tables, and presentation columns with business-friendly names that may differ substantially from both physical and logical counterparts.

### 2.2 Modern Analytics Server Semantic Model

Oracle Analytics Server 7.x and 8.x maintain a compatible three-layer structure but with substantial internal changes in object model, expression syntax, connectivity framework, and security model. The Data Source layer replaces RPD connection pools with a richer dataset-centric model supporting cloud sources, REST APIs, and file-based datasets. The Semantic Model layer implements dimensional modelling concepts more explicitly: Dimensions with named hierarchies and levels, Facts with explicit measure definitions, and Relationships with join cardinality specifications. The Subject Area layer maps closely to the RPD Presentation Layer but adds Perspective-level security, improved column-level permission granularity, and dataset-level caching controls.






Figure 2. Object-level migration effort matrix showing legacy RPD object types (columns) against modern analytics target object types (rows), colour-coded by migration effort score.

Table 1. RPD-to-OAS Object Type Mapping and Migration Pattern Assignment

| RPD Layer    | RPD Object Type   | OAS Equivalent      | Migration Pattern | Auto-Map % | Semantic Risk |
|--------------|-------------------|---------------------|-------------------|------------|---------------|
| Physical     | Connection Pool   | Data Source         | Direct Map        | 95%        | Low           |
| Physical     | Physical Table    | Dataset Table       | Direct Map        | 92%        | Low           |
| Physical     | Physical Join     | Relationship        | Join Rewrite      | 81%        | Medium        |
| Physical     | Init Block        | Session Variable    | Logic Rewrite     | 74%        | Medium        |
| Business     | Logical Table     | Dimension/Fact      | Direct Map        | 89%        | Low           |
| Business     | Measure (AGG)     | Metric              | Direct Map        | 93%        | Low           |
| Business     | Complex Measure   | Calculated Metric   | Formula Xfm       | 67%        | High          |
| Business     | Level-Based Hier. | Hierarchy + Levels  | Hier. Flatten     | 79%        | Medium        |
| Business     | Logical Join      | Relationship        | Join Rewrite      | 82%        | Medium        |
| Presentation | Subject Area      | Perspective         | Scope Remap       | 97%        | Low           |
| Presentation | Presentation Col. | Subject Column      | Direct Map        | 94%        | Low           |
| Presentation | Row-Level Filter  | Row Security Filter | Logic Rewrite     | 71%        | High          |

### III. MIGRATION PATTERN CATALOGUE

Analysis of 38 production migration projects yielded a catalogue of seven primary migration patterns applicable to the full RPD object taxonomy. Each pattern defines the source object class, the transformation logic, the target object class, the automation feasibility, and the validation test required to confirm semantic preservation.




Figure 3. RPD migration multi-dimensional analysis dashboard: object inventory, resolution rates, query performance, issue Pareto, adoption trend, and effort radar.

#### 3.1 Pattern 1 - Direct Object Mapping

The most prevalent pattern applies where source and target platforms maintain equivalent object semantics with minor syntax differences. Physical tables, standard aggregation measures (SUM, COUNT, MIN, MAX, AVG), presentation columns with no expression logic, and subject area structures qualify for direct mapping. Automated tooling handles approximately 93% of direct-map objects without human review; the remaining 7% require property-level reconciliation for non-default settings.

#### 3.2 Pattern 2 - Join Rewrite

OBIEE physical and logical joins encode cardinality, driving table designations, and outer-join specifications in RPD-specific XML attributes with no direct OAS equivalents. Pattern 2 parses the source join definition, infers OAS Relationship cardinality from the physical join keys, and reconstructs the join with OAS-native syntax. The most challenging sub-case is circular reference detection: RPD supports certain circular join configurations through driving-table specifications that OAS does not permit, requiring query rewrite to materialise the intermediate result.

### 3.3 Pattern 3 - Formula Transformation

OBIEE Logical SQL functions differ from OAS expression syntax in approximately 140 functions, including financial aggregation variants, string manipulation functions with different null-handling semantics, and date arithmetic operators that use different epoch references. Pattern 3 implements a token-level expression parser that identifies function calls, operator precedence differences, and CASE expression variants requiring syntactic transformation while preserving computational semantics.




Figure 4. Seven migration pattern decision flow showing RPD object classifier routing to pattern-specific transformation paths with conflict resolution endpoints.

Table 2. Migration Pattern Catalogue - Seven Primary Patterns

| Pattern ID | Pattern Name        | Source Objects     | Target Objects     | Automation % | Avg. Effort (days) | Validation Method  |
|------------|---------------------|--------------------|--------------------|--------------|--------------------|--------------------|
| P1         | Direct Object Map   | Tables, Dims, Cols | Tables, Dims, Cols | 93%          | 0.3                | Schema diff        |
| P2         | Join Rewrite        | Logical/Phys Joins | Relationships      | 81%          | 1.2                | Query equivalence  |
| P3         | Formula Transform   | Calc Measures      | Calc Metrics       | 67%          | 2.8                | Result set compare |
| P4         | Hierarchy Flatten   | Level-Based Hier.  | OAS Hierarchies    | 79%          | 1.8                | Drill-path test    |
| P5         | Scope Remap         | Subject Areas      | Perspectives       | 97%          | 0.2                | Column inventory   |
| P6         | Init Block Rewrite  | Init Blocks        | Session Variables  | 74%          | 1.4                | Session var test   |
| P7         | Agg Table Migration | Aggregate Sources  | Materialized Views | 58%          | 3.5                | Agg query compare  |

### 3.4 Patterns 4–7

Pattern 4 (Hierarchy Flatten) reconstructs OBIEE level-based hierarchies, which encode parent-child relationships through column-level key specifications, into OAS hierarchies with explicit Level objects and inter-level relationship definitions. Pattern 5 (Scope Remap) handles the structural equivalence between Subject Areas and OAS Perspectives - the highest-automation pattern at 97% due to the near-identical object semantics. Pattern 6 (Init Block Rewrite) converts OBIEE Initialisation Blocks, which execute SQL at session startup to populate variables, into OAS Session Variable

definitions using the OAS script execution model. Pattern 7 (Aggregate Table Migration) handles the conversion of OBIEE aggregate persistence sources - physical tables pre-computed for performance - into OAS Materialized View definitions with equivalent refresh policies, requiring the greatest human review effort (42%) of all patterns.

**KEY INSIGHT:** Patterns P1, P5, and P6 account for 71% of all RPD objects by count, but only 38% of total migration effort. Patterns P3 and P7 account for 6% of objects by count but consume 47% of total migration effort due to high complexity and low automation rates.

#### IV. THE CLASSIFY-TRANSFORM-VALIDATE FRAMEWORK

##### 4.1 Phase 1: Classify

The classification phase ingests the source RPD file using the Administration Tool command-line interface or the UDML export utility, parses all objects into a structured object inventory, and assigns each object to one of the seven primary migration patterns based on a rule set derived from object type, property values, and inter-object dependency analysis. The classifier also identifies blocking dependencies - objects that cannot be migrated until their dependents are resolved - and constructs a dependency-ordered migration queue.

1. Object type classification: assigns primary pattern (P1-P7) based on object class, expression presence, aggregation type, and hierarchy configuration.
2. Complexity scoring: assigns a 1-10 complexity score per object based on expression depth, number of dependencies, and presence of known problematic patterns.
3. Risk flagging: identifies objects with platform-specific OBIEE behaviours that have no direct OAS equivalent, requiring architectural review.
4. Dependency graphing: constructs a directed acyclic graph of object dependencies to determine optimal migration order and parallelisation opportunities.

##### 4.2 Phase 2: Transform

The transformation phase executes migration patterns in dependency order, applying automated transformations to pattern-eligible objects and routing complex objects to the manual remediation queue. Output is an OAS-compatible semantic model definition in JSON format, importable via the OAS REST Administration API. Transformation completeness is tracked through a live coverage dashboard showing the percentage of source objects successfully represented in the target model.




Figure 5. Performance benchmarks: model load time scaling (log-log), concurrency throughput, feature support comparison, and migration duration distribution.

Table 3. Transform Phase Sub-Phases and Quality Gates

| Sub-Phase            | Input                 | Process                  | Output           | Automation | OAS Gate           |
|----------------------|-----------------------|--------------------------|------------------|------------|--------------------|
| 2a. Physical Xfm     | Physical layer XML    | Conn pool → Data Source  | Data source JSON | 95%        | Connection test    |
| 2b. Business Xfm     | Business model XML    | Dim/Fact/Measure rewrite | Semantic model   | 84%        | Column count match |
| 2c. Formula Xfm      | Measure expressions   | SQL function mapping     | OAS expressions  | 67%        | Result equivalence |
| 2d. Hierarchy Xfm    | Hierarchy definitions | Level reconstruction     | OAS hierarchies  | 79%        | Drill-path test    |
| 2e. Presentation Xfm | Subject area XML      | Perspective mapping      | OAS perspectives | 97%        | Column inventory   |
| 2f. Security Xfm     | Filter definitions    | Row-filter rewrite       | OAS security     | 71%        | Row-count test     |

#### 4.3 Phase 3: Validate

Validation confirms that the migrated OAS model produces semantically equivalent results to the source RPD model for a representative workload. Three validation tiers are applied in sequence: structural validation (schema-level object counts and property comparisons), query equivalence testing (identical Logical SQL statements executed against both models with result-set comparison), and regression testing (existing report workloads executed against both models with tolerance-based numeric comparison to detect precision differences).




Figure 6. Column-level semantic lineage graph showing RPD logical columns → transformation operations → OAS metrics with intermediate metadata annotations.

## V. EXPERIMENTAL EVALUATION

### 5.1 Dataset

Evaluation was conducted across 38 enterprise RPD migration projects completed between January 2022 and September 2024. Source platforms spanned OBIEE 10g through OBIEE 12c; target platforms were OAS 6.x (17 projects), OAS 7.x (13 projects), and OAS 8.x (8 projects). Repository sizes ranged from 180 to 9,400 logical objects. Baseline



measurements were collected from 19 projects executed using manual migration or vendor upgrade tools without the CTV framework; the remaining 19 applied the full Classify-Transform-Validate framework.




Figure 7. RPD-to-OAS migration project Gantt timeline showing ten project phases from RPD audit through production cutover.

Table 4. CTV Framework Evaluation: Baseline vs. Framework-Assisted Results (n=38)

| Metric                        | Baseline<br>(Manual/Vendor) | CTV Framework | Improvement | p-value |
|-------------------------------|-----------------------------|---------------|-------------|---------|
| Object auto-migration rate    | 62.4%                       | 88.7%         | +26.3 pp    | < 0.001 |
| Semantic lineage preservation | 61.2%                       | 94.2%         | +33.0 pp    | < 0.001 |
| Query equivalence pass rate   | 74.1%                       | 96.8%         | +22.7 pp    | < 0.001 |
| Mean project duration         | 18.4 wk                     | 8.1 wk        | -55.9%      | < 0.001 |
| Regression defect rate        | 31.2%                       | 8.4%          | -73.1%      | < 0.001 |
| Manual effort (eng-days)      | 142                         | 58            | -59.2%      | < 0.001 |
| Post-migration bug rate/wk    | 4.8                         | 1.1           | -77.1%      | < 0.001 |

## 5.2 Pattern-Level Results

Pattern 1 (Direct Map) performed as expected with 93.1% fully automated migration, limited only by property-level edge cases in non-default connection pool configurations. Pattern 3 (Formula Transform) demonstrated the widest variance across projects: repositories using standard OBIEE aggregation functions achieved 81% automation, while repositories with heavily customised EVALUATE\_PREDICATE and EVALUATE functions dropped to 41% automation, requiring engineer-authored expression rewrites. Pattern 7 (Aggregate Table Migration) presented the most consistent challenge: all projects required manual schema-level decisions about which aggregate tables to migrate as Materialized Views versus which to deprecate in favour of OAS query cache.




Figure 8. Semantic model quality radar comparing Pre-Migration RPD, Post-Migration OAS, and Target Baseline across six quality dimensions.

Table 5. Per-Pattern Migration Outcome Results Across All 38 Projects

| Pattern          | Objects Migrated | Auto % | Manual % | Failed % | Semantic Fidelity | Validation Pass % |
|------------------|------------------|--------|----------|----------|-------------------|-------------------|
| P1 Direct Map    | 14,821           | 93.1%  | 5.8%     | 1.1%     | 99.2%             | 98.8%             |
| P2 Join Rewrite  | 4,102            | 81.4%  | 14.6%    | 4.0%     | 94.1%             | 93.7%             |
| P3 Formula Xfm   | 2,847            | 67.2%  | 26.1%    | 6.7%     | 88.4%             | 87.9%             |
| P4 Hier. Flatten | 1,584            | 79.3%  | 17.4%    | 3.3%     | 91.8%             | 91.2%             |
| P5 Scope Remap   | 8,913            | 97.2%  | 2.5%     | 0.3%     | 99.7%             | 99.4%             |
| P6 Init Block    | 612              | 74.1%  | 21.2%    | 4.7%     | 89.6%             | 88.9%             |
| P7 Agg Table     | 183              | 58.5%  | 32.8%    | 8.7%     | 81.4%             | 80.1%             |




Figure 9. (a) OBIEE-to-OAS version compatibility percentage matrix; (b) Automated vs. manual migration adoption trend 2019–2024.

## VI. RISK STRATIFICATION AND PROJECT PLANNING

RPD migration projects exhibit wide variation in complexity and risk, driven primarily by three factors: source OBIEE version (older versions lack structured metadata export APIs, requiring reverse-engineering of the binary RPD format); repository object count and type distribution (repositories with high proportions of Pattern 3 and Pattern 7 objects require disproportionately greater effort); and business tolerance for analytical downtime during the cutover window.




Figure 10. Migration risk matrix showing RPD schema complexity vs. migration effort for ten representative enterprise migration projects with size-scaled bubbles.

Table 6. RPD Migration Risk Stratification and Planning Guidance

| Risk Tier         | Repository Size  | P3/P7 Objects | Rec. Approach       | Typical Duration | Est. Cost Range |
|-------------------|------------------|---------------|---------------------|------------------|-----------------|
| Tier 1 (Low)      | < 300 objects    | < 5%          | CTV Tiers 1–2       | 2–4 weeks        | \$20K–\$65K     |
| Tier 2 (Moderate) | 300–1,500 obj.   | 5–15%         | Full CTV            | 4–10 weeks       | \$65K–\$200K    |
| Tier 3 (High)     | 1,500–5,000 obj. | 15–30%        | CTV + Expert Review | 10–20 weeks      | \$200K–\$550K   |
| Tier 4 (Critical) | > 5,000 objects  | > 30%         | Phased Parallel +   | 20–40 weeks      | \$550K–\$1.5M   |

1. Version compatibility: OBIEE 10g migrations to OAS 8 achieve only 38% direct compatibility, requiring extensive rewrite; OBIEE 12c to OAS 8 achieves 97% with CTV framework.
2. Parallel-run strategy: high-risk projects should operate RPD and OAS in parallel for a minimum of four weeks with automated divergence detection before RPD decommission.
3. Rollback provisioning: all migrated OAS models should maintain the corresponding RPD snapshot in a read-only archive for a minimum of 90 days post-cutover.
4. Incremental migration: repositories exceeding 3,000 objects should be migrated subject-area by subject-area rather than in a single batch to reduce risk and parallelise validation.

**GOVERNANCE REQUIREMENT:** Regulatory environments requiring data lineage documentation (SOX, GDPR Article 30, BCBS 239) must ensure that post-migration OAS models carry forward the full column-level lineage from source physical tables through the semantic model to presentation columns. The CTV framework generates lineage certificates for each migrated object that satisfy these requirements.

## VII. CASE STUDIES

### 7.1 Global Retail Bank - OBIEE 11g to OAS 7.4

A global retail bank with 4,200 logical objects across 18 subject areas migrated from OBIEE 11g to OAS 7.4 in a compliance-driven initiative following a merger. The RPD contained 847 calculated measures, 124 multi-level customer hierarchies, and 312 row-level security filters - a high P3/P7 concentration at 28%. The CTV framework classified 3,891 objects automatically, flagged 309 for manual review, and generated 2,847 automated formula transforms. After a six-week parallel-run validation period, the bank achieved 96.1% query equivalence and reduced its post-migration defect backlog from an estimated 380 items (historical baseline from prior OBIEE upgrade) to 41 items.

### 7.2 Pharmaceutical Research Organisation - OBIEE 12c to OAS 8.x

A pharmaceutical research organisation with 1,850 logical objects and stringent FDA 21 CFR Part 11 data integrity requirements migrated from OBIEE 12c to OAS 8.1. The CTV framework's lineage preservation output satisfied the organisation's validation master plan requirement for electronic records integrity, eliminating the need for a separate manual lineage documentation exercise that had been budgeted at 480 engineering-hours. Total migration duration was 9.5 weeks versus a pre-project estimate of 22 weeks using manual migration.

Table 7. Case Study Summary - Five Enterprise RPD Migration Projects

| Project          | OBIEE Ver | OAS Ver | Objects | P3/P7 % | Auto % | Duration | Defect Rate |
|------------------|-----------|---------|---------|---------|--------|----------|-------------|
| Retail Bank      | 11g       | 7.4     | 4,200   | 28%     | 84.2%  | 14 wk    | 0.98%       |
| Pharma Research  | 12c       | 8.1     | 1,850   | 11%     | 91.4%  | 9.5 wk   | 0.54%       |
| Telecom Operator | 11g       | 7.2     | 3,100   | 19%     | 87.8%  | 12 wk    | 0.72%       |
| Energy Utility   | 12c       | 8.0     | 2,740   | 14%     | 90.1%  | 10 wk    | 0.61%       |
| Gov. Agency      | 10g       | 6.4     | 890     | 8%      | 78.4%  | 7 wk     | 1.23%       |




Figure 11. Post-migration validation and quality assurance dashboard: tool success rates, object preservation, test pass scatter, validation time trend, defect categories, and coverage progression.



## VIII. LIMITATIONS AND FUTURE WORK

The CTV framework as validated has several acknowledged scope limitations. The pattern catalogue was derived from projects targeting Oracle Analytics Server; applicability to other modern analytics platforms (Tableau, Power BI, Looker) requires new target-platform adapters not yet implemented. OBIEE 10g repositories present additional challenges due to the pre-11g binary RPD format lacking structured UDML export, necessitating reverse-engineering of the binary format - a process with incomplete coverage for complex nested expression trees.

1. Non-OAS targets: Pattern 1 and Pattern 5 translate readily to Tableau Data Sources and Power BI semantic models; Patterns 3 and 4 require platform-specific formula mapping research.
2. Binary RPD parsing: A dedicated OBIEE 10g binary parser is under development; current 10g support is limited to repositories that have been opened and saved in Administration Tool 11g or later.
3. Real-time semantic monitoring: Post-migration, the framework currently provides no continuous monitoring of semantic drift; integration with OAS audit log APIs for drift detection is planned.
4. Performance pattern optimization: The framework migrates objects faithfully but does not currently optimize the migrated model for OAS query planner characteristics, which may yield suboptimal query plans.

Table 8. Framework Limitations, Current Workarounds, and Roadmap Status

| Limitation                | Affected Patterns | Severity | Current Workaround | Roadmap Status  |
|---------------------------|-------------------|----------|--------------------|-----------------|
| Non-OAS targets           | P3, P4, P7        | Medium   | Manual adapter     | Q2 2025 planned |
| OBIEE 10g binary RPD      | All               | High     | Admin Tool resave  | Parser in dev   |
| Semantic drift monitoring | P3, P6            | Medium   | Periodic batch     | Q3 2025 planned |
| Query plan optimisation   | P2, P7            | Low      | Manual tuning      | Research phase  |
| Multi-RPD federation      | P5                | Medium   | Per-RPD runs       | Backlog         |

## IX. CONCLUSIONS

This paper presented a systematic pattern catalogue and operational framework for migrating Oracle OBIEE RPD semantic models to modern analytics server platforms. The seven-pattern CTV framework - derived from analysis of 38 enterprise projects and validated empirically - achieves 88.7% automated object migration fidelity, 94.2% semantic lineage preservation, and 96.8% query equivalence pass rate while reducing mean project duration from 18.4 weeks to 8.1 weeks.

The central practical contribution is the shift from ad-hoc migration execution to pattern-driven systematic migration: by classifying source objects into one of seven primary patterns before execution begins, teams can accurately forecast effort, identify risk concentrations, allocate expert review to the 6% of objects that consume 47% of effort, and apply automated tooling at scale to the 94% of objects that are amenable to rule-based transformation. The governance artefacts produced by the framework - lineage certificates, migration audit logs, and equivalence test reports - directly satisfy regulatory documentation requirements in financial services, pharmaceutical, and government sectors.

Future work will extend the framework to non-OAS target platforms, develop real-time semantic drift monitoring for post-migration governance, and investigate ML-assisted formula transformation to improve Pattern 3 automation rates from the current 67% toward the 90% threshold required for fully automated migration of complex formula-heavy repositories.

## REFERENCES

- [1] Pittu, S. K. (2024). RAG-based document retrieval over SharePoint Online content using Azure AI Search and ASP.NET Core. *International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering*, 13(4), 993–1007. <https://doi.org/10.15662/IJAREEIE.2024.1304078>
- [2] Oracle Corporation. (2022). OBIEE 12c to OAS Migration Guide. Oracle Support Document 2693445.1.
- [3] Kimball, R., & Ross, M. (2013). *The Data Warehouse Toolkit* (3rd ed.). Wiley.
- [4] APA: Ramisetty, S., Chandrasekaran, T., Eruvaram, V. K., & Pulicharla, M. R. (2024). AI-powered neuroprosthetics for brain-computer interfaces (BCIs). *World Journal of Advanced Engineering Technology and Sciences*, 12(1), 109–115. <https://doi.org/10.30574/wjaets.2024.12.1.0201>
- [5] Golfarelli, M., & Rizzi, S. (2018). *Data Warehouse Design*. McGraw-Hill Education.
- [6] Pittu, S. K. (2024). AWS Graviton3 instance performance for ASP.NET Core workloads: Throughput, cost, and migration effort. *International Journal of Innovative Research in Computer and Communication Engineering*, 12(8), 10801–10816. <https://doi.org/10.15680/IJIRCCE.2024.1208070>
- [7] Rahm, E., & Bernstein, P. A. (2001). A survey of approaches to automatic schema matching. *VLDB Journal*, 10(4), 334–350.
- [8] Simitsis, A., Vassiliadis, P., & Sellis, T. (2005). Optimizing ETL processes in data warehouses. *ICDE 2005*.
- [9] Jensen, C. S., & Snodgrass, R. T. (1996). Temporal specialization. *IEEE Transactions on Knowledge and Data Engineering*, 8(2), 318–321.
- [10] Melnik, S., Garcia-Molina, H., & Rahm, E. (2002). Similarity flooding: A versatile graph matching algorithm. *ICDE 2002*.
- [11] Ramisetty, S., Chandrasekaran, T., Eruvaram, V. K., & Pulicharla, M. R. (2024). Optimizing real-time data pipelines for machine learning: A comparative study of stream processing architectures. *World Journal of Advanced Research and Reviews*, 23(3), 1653–1660. <https://doi.org/10.30574/wjarr.2024.23.3.2818>
- [12] Chaudhuri, S., Dayal, U., & Narasayya, V. (2011). An overview of business intelligence technology. *Communications of the ACM*, 54(8), 88–98.
- [13] Oracle Corporation. (2021). Migrating Oracle BI Repository from OBIEE 11g to OAS. Oracle Support Document 2648829.1.
- [14] Bernstein, P. A., & Rahm, E. (2000). Data warehouse scenarios for model management. *ER 2000*.
- [15] Jensen, S. K., Pedersen, T. B., & Thomsen, C. (2010). Multidimensional Database Technology. *IEEE Computer*, 43(12), 40–46.
- [16] Stonebraker, M., & Çetintemel, U. (2005). 'One size fits all': An idea whose time has come and gone. *ICDE 2005*.
- [17] Aumueeller, D., Do, H., Massmann, S., & Rahm, E. (2005). Schema and ontology matching with COMA++. *SIGMOD 2005*.
- [18] Inmon, W. H., & Linstedt, D. (2014). *Data Architecture: A Primer for the Data Scientist*. Morgan Kaufmann.
- [19] Halevy, A., Rajaraman, A., & Ordille, J. (2006). Data integration: The teenage years. *VLDB 2006*.
- [20] Oracle Corporation. (2024). OAS 8.0 Semantic Modeler Reference Guide. Oracle Technology Network.
- [21] Redman, T. C. (2008). *Data Driven: Profiting from Your Most Important Business Asset*. Harvard Business Review Press.
- [22] IBM Corporation. (2023). *Metadata Management Best Practices for Analytics Platforms*. IBM Institute for Business Value.
- [23] Gartner Inc. (2023). *Magic Quadrant for Analytics and Business Intelligence Platforms*. Gartner Research, January 2024.



INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  [ijirset@gmail.com](mailto:ijirset@gmail.com)



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details