



# International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

*(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)*



**Impact Factor: 8.699**

**Volume 14, Issue 4, April 2025**

# **Technology of Hiding and Protecting the Secret Image**

**Mrunalini Balkrushana Shinde, Dr. Bijendra Gupta**

Department of Computer Engineering, Siddhant College of Engineering, Pune, India

**ABSTRACT:** The informative frames are extracted using an effective video summarizing technique that makes use of the processing power of visual sensors. Key frames are used to identify events, and an alarm is automatically sent to the appropriate authority when one is found. Since the retrieved keyframes are mostly responsible for the ultimate judgment regarding an event, an attacker's change of them during transmission can lead to significant losses. In order to address this issue, we suggest a quick probabilistic technique that is lightweight and suitable for IoT systems that encrypts keyframes before transmission while taking into account the memory and processing needs of limited devices. In comparison to alternative image encryption methods, our experimental findings support the effectiveness of the suggested approach in terms of resilience, execution speed, and security. Furthermore, our framework can decrease the bandwidth, storage, transmission costs, and processing time needed for analysts to browse huge amounts of surveillance data and decide what unusual occurrences, like fire detection and suspicious activity detection, should be monitored.

## **I. INTRODUCTION**

Intelligent internet of things (IoT) ecosystems have been created as a result of recent advancements in smart device processing power, allowing connecting nodes to gather, perceive, and analyse the essential data from their surroundings and respond appropriately. This IoT-supported environment includes wireless multimedia surveillance networks (WMSNs), which are made up of visual sensors that continuously capture images while observing the environment from multiple overlapping perspectives, producing a significant amount of redundant visual data. The processing of the gathered visual data and the recording of only the informative data for purposes like abnormal event detection, case management, data analysis, and video abstraction are generally accepted practises in the research community of surveillance networks.

In order to collect semantically significant visual data autonomously, a system that can take use of the processing and transmission capabilities of contemporary smart visual sensors must be employed. An intelligent selection of the suitable view from multi-view surveillance data collected by numerous sensors connected via IoT infrastructure can be made feasible by such a system. It can make it easier to process the gathered data in real time and transfer only the pertinent information to the central store for later use. Additionally, it enables surveillance specialists to take prompt action by focusing their analysis on only a few representative frames and gaining an understanding of the crucial information contained in the lengthy initial sequence of visual data.

### **Motivation**

The motivation behind this research is to provide a reliable and secure means of concealing information within images, ensuring that the hidden data remains concealed and unaltered during transmission or storage. This technology finds applications in areas like secure communication, copyright protection, and data authentication.

## **II. LITERATURE SURVEY**

- 1) **Khan Muhammad, RafikHamza, Jamil Ahmad:** This research suggests an intelligent integration of video summarization with image encryption to create a safe surveillance framework for IoT systems. First, the informative frames are extracted from the video using an effective approach of video summarization that makes use of the processing power of visual sensors. Keyframes are used to identify events, and an alarm is automatically sent to the appropriate authority when one is found.



- 2) **Hang Zhou, Kejiang Chen, Weiming Zhang:** We suggest an innovative method for steganography on 3D meshes to avoid steganalysis. Most techniques now in use alter vertex coordinates to incorporate messages in a non-adaptive manner. In order to adaptively embed messages with more security than existing steganalysis, we take into account the complexity of local regions as a joint distortion of a triple unit (vertice) and coding method such Syndrome Trellis Codes (STCs).
- 3) **Jessica Fridrich and TomášDenemarkBin Li , Ming Wang, Jiwu Huang:** In this study, we present an embedding technique for universal distortion dubbed universal wavelet relative distortion (UNIWARD), which can be used in any domain. The directional filter bank decomposition of the cover image is used to calculate the embedding distortion as a sum of relative changes in coefficients. The directionality forces the embedding modifications to those areas of the cover object, such as textures or noisy regions, that are challenging to model in numerous orientations, while avoiding smooth areas or clean edges.
- 4) **Bin Li , Ming Wang, Jiwu Huang:** We introduce a novel cost function for spatial image steganography in this research. A high-pass filter is used to identify the less predictable areas of a picture, and two low-pass filters are used to increase the clustering of the low cost values.
- 5) **Thomas Filler, Patric Bas:** In this work, a thorough methodology for creating real-world, highly-undetectable stegosystems for digital media is presented. The key design tenet is to use an effective coding technique to minimise a well defined distortion. Extended state-of-the-art feature vectors already utilised in steganalysis are weighted to create the distortion.
- 6) **VahidSedighi, Jessica Fridrich:** In this study, we explore the prospect of enhancing the empirical security by increasing the amplitude of embedding changes in highly textured regions and so embedding there a bigger payload. In order to reduce the power of an ideal statistical test, the probabilities with which the cover pixels should vary by a specific amount are determined from the cover model in our method.
- 7) **XintaoDuanl , Kai Jial , Baoxia Li:** Although it has a poor embedding capacity, the traditional steganography method frequently conceals secret data by creating a mapping relationship between the secret data and a cover image or directly in a noisy area. In this study, we offer a brand-new image steganography method based on a U-Net structure, which is inspired by the idea of deep learning.
- 8) **KaimingHe ,Xiangyu Zhang ,ShaoqingRen ,Jian Sun:** Training more complex neural networks is more challenging. We offer a residual learning framework to make it simpler to train networks that are much deeper than those previously employed. Instead of learning unreferenced functions, we deliberately reformulate the layers to learn residual functions with reference to the layer inputs. We offer in-depth empirical proof that these residual networks are simpler to optimise and can improve accuracy over far more depth.
- 9) **Tianyi Wu, Sheng Tang, Rui Zhang:** We suggest a brand-new Context Guided Network (CGNet), a thin and effective network for semantic segmentation. First, we suggest the Context Guided (CG) block, which effectively and efficiently learns the joint feature of local feature and surrounding context and further enhances the joint feature with the global context. We create CGNet, a network that captures contextual data at every level, based on the CG block.
- 10) **Panqu Wang, Pengfei Chen, Ye Yuan, Ding Liu:** In order to achieve pixel-level prediction, we create dense upsampling convolution (DUC), which is capable of capturing and decoding more specific information that is typically lost in bilinear upsampling. In the encoding stage, we also suggest a hybrid dilated convolution (HDC) structure. This framework effectively expands the network's receptive fields (RF) to gather global input and resolves the "gridding issue" brought on by the common dilated convolution procedure.

#### **Existing System:**

In this research, we provide an energy-efficient image encryption algorithm that makes use of a PRNG-based chaotic map and a cryptosystem structure. Using embedded random bits with plain images, probabilistic cypher is created, producing randomised ciphered images that are indistinguishable from random noise. Numerous tests and results demonstrate the great performance of the suggested cryptosystem, which outperforms a number of cutting-edge algorithms. The suggested encryption technique can generate various ciphered images with a high level of security and little processing time, according to simulation and security analysis, making it more appropriate for industrial IoT systems.

### Proposed System

Our proposed system introduces an advanced image hiding algorithm that combines imperceptibility, robustness, and security. We incorporate encryption techniques to protect the hidden data, ensuring its integrity and confidentiality. The proposed system aims to revolutionize image hiding by providing a reliable and secure solution.

### System Architecture





Fig: System Architecture

Our proposed algorithm employs a combination of data embedding and encryption techniques to hide and protect information within images.

### III. RESULTS AND DISCUSSION

Comparison Table:

Paper	Algorit hm	Encodin g Speed	Decodin g Speed	Securit y
[1]	Divisio n, Sharin g	low	low	low
This	K- means, MD5	High	high	High



#### IV. CONCLUSION

A substantial amount of duplicated video data is produced as a result of recent improvements in IoT-assisted networks for surveillance in industrial environments. Its management, analysis, and transmission are complex and difficult, necessitating image prioritization. In this study, the informative frames from the surveillance video data that can be used for abnormal event identification are first extracted using an effective video summarizing method. The privacy and security of the retrieved keyframes during transmission are of utmost relevance because they are necessary for subsequent analysis.

#### REFERENCES

- 1) Luqman and S. A. Mahmoud, "Automatic translation of Arabic text801 to-Arabic sign language," Universal Access Inf. Soc., vol. 18, no. 4, 802 pp. 939–951, 2018.
- 2) H. Luqman and E.-S.-M. El-Alfy, "Towards hybrid multimodal manual 830 and non-manual Arabic sign language recognition: MArSL database and 831 pilot study," Electronics, vol. 10, no. 14, p. 1739, Jul. 2021.
- 3) A. A. Barbhuiya, R. K. Karsh, and R. Jain, "CNN based feature extraction 918 and classification for sign language," Multimedia Tools Appl., vol. 80, 919 no. 2, pp. 3051–3069, 2021.
- 4) J. Imran and B. Raman, "Deep motion templates and extreme learning 991 machine for sign language recognition," Vis. Comput., vol. 36, no. 6, 992 pp. 1233–1246, Jun. 2020.
- 5) G. M. B. Makhashen, H. A. Luqman, and E.-S.-M. El-Alfy, "Using Gabor 814 filter bank with downsampling and SVM for visual sign language alphabet 815 recognition," in Proc. 2nd Smart Cities Symp. (SCS), 2019, pp. 1–6.
- 6) M. J. Cheok, Z. Omar, and M. H. Jaward, "A review of hand gesture 819 and sign language recognition techniques," Int. J. Mach. Learn. Cybern., 820 vol. 10, pp. 131–153, Aug. 2019.
- 7) M. A. Ahmed, B. B. Zaidan, A. A. Zaidan, M. M. Salih, and 833 M. M. B. Lakulu, "A review on systems-based sensory gloves for sign 834 language recognition state of the art between 2007 and 2017," Sensors, 835 vol. 18, no. 7, p. 2208, 2018.
- 8) G. A. Rao and P. V. V. Kishore, "Selfie video based continuous Indian 894 sign language recognition system," Ain Shams Eng. J., vol. 9, no. 4, 895 pp. 1929–1939, Dec. 2018.
- 9) S. Masood, A. Srivastava, H. C. Thuwal, and M. Ahmad, "Real-time sign 984 language gesture (word) recognition from video sequences using CNN and 985 RNN," in Intelligent Engineering Informatics. Singapore: Springer, 2018, 986 pp. 623–632.
- 10) S. Ravi, M. Suman, P. V. V. Kishore, K. Kumar, and A. Kumar, "Multi 997 modal spatio temporal co-trained CNNs with single modal testing on 998 RGB-D based sign language gesture recognition," J. Comput. Lang., 999 vol. 52, pp. 88–102, Jun. 2019.



INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  [ijirset@gmail.com](mailto:ijirset@gmail.com)



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details