



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 14, Issue 12, December 2025

A Review on Surface Texturing Techniques and Their Effect on Tribological Performance of Mechanical Components

Gourishankar H¹, Amaresh U², Syed Assad Basha³, Yasin Basha⁴, Shankar Sai⁴

Principal, Sanjay Gandhi Polytechnic Ballari, Karnataka, India¹

Dean & Hod, Department of Mechanical Engineering, Sanjay Gandhi Polytechnic Ballari, Karnataka, India²

Assistant Hod and Senior Grade Lecturer, Department of Mechanical Engineering Sanjay Gandhi Polytechnic Ballari, Karnataka, India³

Students, Department of Mechanical Engineering Sanjay Gandhi Polytechnic Ballari, Karnataka, India⁴

ABSTRACT: Surface texturing has emerged as a significant technique to enhance the tribological performance of mechanical components by improving lubrication, reducing friction, and increasing wear resistance. This paper presents a comprehensive review of surface texturing techniques, including laser texturing, mechanical grooving, chemical etching, and electrochemical machining, and their effects on friction, wear, and lubrication behavior. It further explores the influence of texturing parameters such as shape, depth, density, and pattern distribution on tribological properties. The review also examines the applications of surface textures in bearings, gears, seals, and biomedical implants. Challenges, limitations, and future directions in optimizing surface textures using computational models and artificial intelligence are discussed. Overall, the study highlights the critical role of surface texturing in enhancing mechanical efficiency and prolonging component life.

KEYWORDS: Tribology, Surface Texturing, Friction, Wear, Lubrication, Mechanical Engineering, Surface Engineering

I. INTRODUCTION

Tribology, the science of friction, wear, and lubrication, plays a critical role in mechanical engineering as it directly affects the efficiency, reliability, and lifespan of machinery. Friction leads to energy losses and heat generation, while wear results in material degradation, requiring frequent maintenance and replacement of components. Among several approaches to mitigate friction and wear, surface texturing has gained significant attention due to its effectiveness in improving lubrication and load-bearing capacity without significant changes to material composition.

Surface texturing involves creating controlled patterns, such as dimples, grooves, or pits, on a contact surface to enhance tribological performance. Textures act as reservoirs for lubricants, trap wear debris, and generate localized hydrodynamic effects that reduce direct surface contact. Over the last decade, numerous experimental and computational studies have investigated the impact of surface textures on friction reduction, wear resistance, and lubrication efficiency in various mechanical components such as bearings, gears, piston rings, and biomedical implants.

This review aims to summarize the recent advances in surface texturing, its mechanisms, techniques, influencing parameters, applications, challenges, and future research directions.

II. FUNDAMENTALS OF SURFACE TEXTURING

2.1 Mechanisms of Friction and Wear

Friction occurs when two surfaces interact, and wear is the material loss due to repeated contact. Surface roughness, load, speed, and lubrication conditions influence the friction and wear behavior of materials. Proper surface texturing

modifies the contact area and promotes the formation of micro-lubricant films, reducing metal-to-metal contact and, consequently, friction and wear.

2.2 Surface Texturing Benefits

The benefits of surface texturing include:

- Reduction in friction coefficient
- Improvement in wear resistance
- Enhanced load-carrying capacity
- Trapping of debris and wear particles
- Better lubricant distribution and retention

These benefits depend on the type, size, and distribution of surface textures, making optimization critical for each application.

III. SURFACE TEXTURING TECHNIQUES

Several techniques are used to produce surface textures, each with specific advantages and limitations:

3.1 Laser Surface Texturing (LST)

As shown in fig a Laser surface texturing involves using focused laser beams to create micro-dimples or grooves on a surface. It provides high precision, flexibility, and the ability to create complex patterns. LST is widely used for bearings, seals, and cutting tools due to its high repeatability and minimal mechanical stress.




Fig a

3.2 Mechanical Grooving

As shown in fig b Mechanical grooving uses tools to cut grooves or patterns on the surface. It is simple and cost-effective but may introduce residual stresses and limited control over fine texture dimensions.



Fig b

3.3 Chemical Etching

Chemical etching uses acid or chemical solutions to remove material and create micro-patterns. This method allows selective material removal but requires careful handling of chemicals and precise control to avoid over-etching.




Fig c

3.4 Electrochemical Machining (ECM)

As shown in fig d ECM uses an electrochemical reaction to remove metal and form patterns. It produces smooth textures without inducing thermal or mechanical stress, making it suitable for high-precision applications.

ELECTROCHEMICAL MACHINING (ECM)




Fig d

IV. INFLUENCE OF SURFACE TEXTURE ON TRIBOLOGICAL PERFORMANCE

4.1 Friction Reduction

Surface textures can significantly reduce the coefficient of friction (COF) by generating micro-hydrodynamic effects and decreasing direct contact between surfaces. Dimples and grooves act as lubricant reservoirs, allowing continuous replenishment of the lubricant film. Multiple studies have reported up to 20–40% reduction in friction for properly designed textured surfaces under boundary and mixed lubrication conditions.

4.2 Wear Resistance

Textured surfaces improve wear resistance by redistributing stresses, reducing asperity contact, and trapping debris that could otherwise cause abrasive wear. The depth, shape, and density of textures play a critical role in determining the wear rate.

4.3 Effect of Texture Parameters

Several parameters influence the effectiveness of surface textures:

- **Shape:** Dimples, grooves, and pits perform differently based on sliding direction and load conditions.
- **Size and depth:** Optimal depth ensures sufficient lubricant storage without weakening the surface.
- **Pattern density:** Higher density increases lubricant retention but may reduce the load-bearing area.
- **Orientation:** Alignment of grooves relative to sliding direction affects lubrication mechanisms.

4.4 Combined Effects

The combination of texture type, size, and pattern can be tailored for specific tribological conditions. For example, circular dimples improve micro-hydrodynamic lubrication, while longitudinal grooves are effective for directional lubricant flow.

V. APPLICATIONS OF SURFACE TEXTURING

Surface texturing has broad applications across mechanical engineering:

- **Bearings:** Reduce friction and wear, extend service life, and improve load-carrying capacity.
- **Gears:** Minimize surface fatigue, reduce noise, and improve lubrication.
- **Seals and Piston Rings:** Enhance sealing performance and reduce energy losses.
- **Biomedical Implants:** Reduce friction in joint prostheses and improve biocompatibility.
- **Micro- and Nano-scale Devices:** Enable precise control of surface interactions in MEMS/NEMS systems.

VI. CHALLENGES AND FUTURE RESEARCH DIRECTIONS

Despite its advantages, surface texturing faces challenges:

1. **Optimization:** Determining the ideal texture design for specific loads, speeds, and lubrication conditions is complex.
2. **Manufacturing Costs:** High-precision methods like laser texturing can be expensive for large-scale production.
3. **Modeling Accuracy:** Predicting tribological behavior requires advanced computational models integrating surface roughness, lubrication, and material properties.
4. **Integration with Coatings:** Combining surface textures with wear-resistant or low-friction coatings could provide superior performance but requires further study.

Future Directions:

- AI-guided optimization of texture design
- Multi-functional surfaces combining textures with coatings or surface treatments
- Experimental studies under extreme temperatures, pressures, and lubrication conditions
- Integration with Industry 4.0 for predictive maintenance and performance monitoring

VII. CONCLUSION

Surface texturing is a proven method to enhance tribological performance in mechanical systems by reducing friction, improving wear resistance, and optimizing lubrication. The choice of texturing technique, texture design, and application-specific parameters plays a vital role in achieving optimal performance. Future research integrating computational modeling, AI, and advanced materials can further expand the benefits of surface texturing in mechanical engineering.

REFERENCES

1. M. Zou, M. Afshar-Mohajer, and R. A. Fleming, "Tribology of Textured Surfaces," *Lubricants*, vol. 13, no. 8, p. 339, 2025.
2. S. G. Ansari and P. R. Jain, "The performance of textured surfaces in friction reduction: A review," *Tribology International*, vol. 177, 108010, 2023.
3. A. Kovalchenko et al., "Surface texturing of steel for tribological improvement," *Wear*, vol. 267, pp. 664–670, 2009.
4. M. B. Mainak, "Laser surface texturing for enhanced tribology of mechanical components: A review," *Materials Today: Proceedings*, vol. 63, pp. 1480–1490, 2023.



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

9940 572 462 6381 907 438 ijirset@gmail.com

www.ijirset.com



Scan to save the contact details