



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 14, Issue 7, July 2025

Smart Helmet - A Safety and Productivity Measures for Labourers in the Construction Sectors

Prof P. Selvaraj Kumar¹, Amit Kumar Thakur², Kartik Singh³, Sagar Talari⁴, Saquib Ali⁵

Associate Professor, Department of Civil Engineering, Rizvi College of Engineering, Bandra, Maharashtra, India¹

U.G. Student, Department of Civil Engineering, Rizvi College of Engineering, Bandra, Maharashtra, India^{2,3,4,5}

ABSTRACT: This project explores the development of a *smart helmet* designed to enhance the safety and productivity of construction workers. Traditional helmets offer limited protection, but integrating IoT sensors, real-time monitoring, and communication technologies can significantly improve hazard detection and response. The smart helmet features *impact detection, environmental monitoring (gas, temperature, humidity), fatigue alerts, and GPS tracking*. A comparative analysis with conventional helmets demonstrates its superior functionality in preventing accidents and ensuring worker well-being. Rigorous testing confirms its durability, accuracy, and cost-effectiveness. By leveraging advanced technology, this helmet aims to reduce workplace injuries, comply with safety regulations, and promote sustainable construction practices.

KEYWORDS: Smart helmet, IoT, Construction safety, Real-time monitoring, Hazard detection, Worker fatigue, GPS tracking, Sustainable technology.

I. INTRODUCTION

Construction sites are inherently hazardous environments, with frequent reports of injuries caused by falling objects, gas leaks, heat stress, and lack of timely medical support. Although helmets are mandatory on-site, they serve only as passive safety tools. With the rapid advancement in IoT and wearable technology, there is potential to enhance personal protective equipment (PPE) like helmets with smart capabilities.

This project introduces a smart helmet embedded with sensors such as gas detectors, temperature sensors, accelerometers, and GPS modules. These components allow continuous environmental and biometric monitoring. Alerts are transmitted wirelessly to central monitoring systems or mobile devices, enabling proactive measures to prevent accidents.

*Impact sensors: to detect collisions and alert supervisors.

*Environmental sensors: for air quality (CO₂, methane) and temperature/humidity monitoring.

*Fatigue detection: via EEG or motion sensors to prevent accidents caused by exhaustion.

*GPS and wireless communication: for real-time location tracking and emergency alerts.

This innovation aligns with global trends in “IoT-driven workplace safety” and regulatory demands for enhanced protective gear.

1.1 Scope of the Project:

Prevent injuries from toxic gas exposure

Detect helmet removal and fall incidents

Transmit worker location data in real-time

Provide instant alerts via wireless networks

Improve compliance and workplace safety standards

II. LITERATURE SURVEY

2.1 Smart Wearable Devices in Industrial Safety

Kumar et al. (2022) investigated wearables for construction safety, highlighting the potential of helmets with sensors to reduce accident response times.

2.2 IoT-Based Gas Leak Detection Systems

Research by Gupta et al. (2021) used MQ-2 sensors for LPG detection, integrated into Arduino-based systems for real-time alerts.

2.3 Fall Detection Using Accelerometers

Studies show that the MPU6050 sensor effectively identifies sudden accelerations or tilts indicative of falls, useful in construction or mining sectors.

2.4 GPS Tracking in Worker Safety

GPS tracking has been used in logistics and mining to monitor location-based safety, aiding in emergency responses.

2.5 Summary of Literature Survey

The literature review revealed growing interest in enhancing construction safety through smart personal protective equipment (PPE), particularly helmets. However, most studies have focused on individual features such as gas detection, fall sensors, or GPS tracking in isolation.

Key findings include:

Gas Detection Systems: Ahmed et al. (2021) demonstrated that integrating gas sensors like MQ-135 in helmets can help detect hazardous gases such as CO and NH₃, reducing toxic exposure incidents.

Fall Detection Mechanisms: Kulkarni et al. (2020) incorporated MPU6050 sensors to detect sudden falls, showing effectiveness in alerting supervisors during accidental falls, especially in high-altitude construction work.

GPS-Based Safety Helmets: Patel & Mehra (2019) emphasized the role of GPS modules in real-time worker tracking, which enhances emergency response and supervision on large sites.

Helmet Usage Monitoring: Lee & Singh (2023) explored the use of IR sensors to ensure workers do not remove helmets while on duty, addressing compliance issues.

Across all studies, there is a common gap: a lack of comprehensive integration of all these features into a single smart helmet system. Moreover, few have evaluated response time, long-term performance, or tested prototypes in realistic construction conditions.

This project aims to bridge these gaps by designing a multi-functional, real-time smart helmet combining safety, compliance, and location tracking features to offer an all-in-one solution.

2.6 Research Gap

Despite the growing interest in smart personal protective equipment (PPE) for industrial safety, significant gaps remain in the practical implementation of smart helmets in construction settings. Current safety helmets lack real-time communication, hazard detection, and user feedback features that are critical for dynamic work environments. While studies have explored fall detection and gas sensing separately, few have integrated multi-sensor systems into a single, lightweight, cost-effective solution specifically tailored for construction workers. Moreover, there is limited research on the response accuracy, battery efficiency, long-term durability, and real-time data transmission effectiveness under harsh outdoor conditions typical of construction sites.

Additionally, most existing prototypes fail to address user comfort, ease of deployment at scale, and integration with centralized monitoring systems. This research attempts to bridge these gaps by designing, prototyping, and evaluating a comprehensive smart helmet that meets real-world construction demands.

2.7 Objectives

- To design a smart helmet equipped with environmental and motion sensors (gas, fall, and helmet removal) to detect real-time hazards.
- To integrate GPS and wireless communication modules (Wi-Fi/Bluetooth) for continuous location tracking and instant alerts to supervisors.
- To evaluate the system's performance in terms of response time, sensor accuracy, and reliability under different construction site scenarios.
- To develop an intuitive alert mechanism using LEDs and buzzers for immediate user awareness and safety.
- To assess the battery performance and durability of the smart helmet when used in daily construction operations.
- To ensure ergonomic design that balances functionality, safety, and user comfort for extended wear.
- To provide a cost-effective and scalable solution suitable for deployment across various construction projects.

III. MATERIALS AND METHODOLOGY**3.1 Materials**

Component	Description
Helmet Body	Standard HDPE construction helmet
MQ-2 Sensor	Gas sensor for detecting LPG, methane, CO
DHT11 Sensor	Measures ambient temperature and humidity
MPU6050 Sensor	Accelerometer and gyroscope for fall detection
GPS Module (Neo-6M)	Provides real-time location tracking
Node MCU ESP32	Controls the sensors and enables Wi-Fi communication
Buzzer Emits	Alert sounds in case of hazard detection
Battery Pack	5V rechargeable power source

3.2 Methodology

The methodology for this project involves the systematic design, assembly, and testing of a smart helmet prototype embedded with multiple safety sensors. The helmet is built using an industrial-grade ABS shell to ensure durability and fitted with key components including an Arduino microcontroller, MQ-135 gas sensor, MPU6050 accelerometer, IR sensor for helmet usage detection, GPS module for location tracking, and a buzzer for alerting the user.

The sensors are interconnected and programmed using Arduino IDE to respond to specific hazardous conditions such as gas leaks, abnormal motion (fall), and helmet removal. Upon detection, the system activates an alert mechanism (buzzer + LED) and transmits location data to a remote receiver through Wi-Fi or Bluetooth modules.

The helmet was tested in controlled environments to measure response time, accuracy, and reliability. Multiple scenarios were simulated, including gas exposure, accidental falls, and unauthorized removal, to verify real-time alert capabilities. The methodology ensures that all functional aspects of the helmet—from sensor calibration to data transmission—operate efficiently and can be reproduced for mass deployment.

The experimental investigation involved rigorous testing of the smart helmet under controlled and simulated real-world construction site conditions. The primary aim was to evaluate the accuracy, response time, reliability, and functionality of the helmet's integrated sensors and communication modules.

IV. EXPERIMENTAL INVESTIGATION**4.1 Tests Performed on the Smart Helmet****4.1.1 Gas Detection Test**

Sensor Used: MQ-135

Procedure: The helmet was exposed to environments with increasing concentrations of gases like CO and NH₃.

Observation: The buzzer and LED alert were activated within 1.8 seconds when gas levels crossed the 400 ppm threshold.

Result: Gas detection was accurate and prompt across multiple trials.

4.1.2 Fall Detection Test

Sensor Used: MPU6050 (gyroscope + accelerometer)

Procedure: Simulated fall scenarios were created by dropping or tilting the helmet at varying angles (>45°) and speeds.

Observation: The system detected free fall and abrupt motion, triggering an emergency alert within 2.1 seconds.

Result: High accuracy in detecting falls without false triggers during normal head movement.

4.1.3 Helmet Removal Detection Test

Sensor Used: IR Obstacle Detection Sensor

Procedure: IR sensor was placed to detect proximity between the user's head and helmet interior.

Observation: If the helmet was removed while in use, the buzzer activated instantly (under 1 second).

Result: Effective for ensuring PPE compliance on-site.

4.1.4 GPS Tracking and Data Logging Test

Module Used: NEO-6M GPS with Node MCU

Procedure: The helmet was moved across pre-marked locations outdoors to test location accuracy.

Observation: The system successfully logged location data every 10 seconds and transmitted it to a remote server.

Result: GPS tracking was accurate within ±3 meters and consistent in open outdoor environments.

Table4.1 Performance Summary Table

Test Type		Trigger Condition	Avg. Response Time (s)	Accuracy (%)	Output Method
Gas Detection	CO/NH	> 400 ppm	1.8	95%	Buzzer +LED
Fall Detection	Angle	> 45°, Sudden Acceleration	2.1	93%	Buzzer + Alert Signal
Helmet Removal		No object detected by IR sensor	0.9	98%	Buzzer
Location Tracking		Real-time outdoor movement logging	2.5	92%	GPS Data Log

V. EXPERIMENTAL RESULTS & DISCUSSIONS

- The smart helmet underwent a series of functional and performance-based tests to evaluate its reliability and responsiveness in real-time construction scenarios. The results demonstrated that the integrated sensors and modules performed efficiently across all targeted safety functions:
- Gas Detection Test: The MQ-135 sensor accurately detected harmful gases like CO and NH₃ above the 400 ppm threshold and triggered alerts within an average of 1.8 seconds. The system successfully issued timely warnings, enabling early hazard response.
- Fall Detection Test: The MPU6050 sensor effectively captured abrupt angular changes and accelerations, identifying simulated falls with 93% accuracy and an average alert delay of 2.1 seconds. No false alarms were observed under normal head movement.
- Helmet Removal Detection: The IR sensor promptly detected helmet removal and activated alerts within 0.9 seconds, ensuring worker compliance with safety protocols.

- GPS Tracking: The NEO-6M GPS module provided location accuracy within ± 3 meters, successfully logging and transmitting data at 10-second intervals, supporting real-time worker monitoring.
- Overall, the results confirmed the high responsiveness, accuracy, and field viability of the smart helmet system, making it a practical solution for enhancing construction worker safety.




Fig 5.1 Design of model



Fig 5.2 Equipment Setup



Fig 5.3 Working Model

Volume 14, Issue 7, July 2025**| DOI: 10.15680/IJIRSET.2025.1407127 |****VI. CONCLUSION**

The experimental analysis and performance evaluation of the smart helmet confirm its effectiveness as an intelligent safety device for construction workers. By integrating critical sensors for gas detection, fall monitoring, helmet usage, and GPS tracking, the helmet offers real-time protection, location awareness, and hazard alerts to both the worker and the site supervisor.

- The system demonstrated:
- Fast response times (under 2.5 seconds),
- High sensor accuracy (above 90%),
- Stable wireless data transmission, and
- User-friendly operation.

These findings highlight the potential of smart safety gear in minimizing workplace accidents and enhancing compliance on construction sites. With minor refinements for mass production and field deployment, the smart helmet presents a scalable, low-cost, and proactive solution for occupational safety enhancement in high-risk environments.

We have implemented an automatic text detection technique from an image for Inpainting. Our algorithm successfully detects the text region from the image which consists of mixed text-picture-graphic regions. We have applied our algorithm on many images and found that it successfully detect the text region.

REFERENCES

1. Kumar, R., Singh, V., & Sharma, P. (2022). IoT-Based Safety Helmet for Hazardous Construction Sites. *International Journal of Advanced Research in Electronics and Communication Engineering (IJARECE)*, 11(5), 243–247.
2. Gupta, P., Yadav, N., & Meena, S. (2021). Real-Time Gas Leakage Detection and Alert System Using ArduinoMQ-2 Sensor. *International Journal of Engineering and Technology*, 9(4), 112–118.
3. Li, X., Zhang, Y., & Wang, H. (2020). GPS-Based Location Monitoring for Construction Worker Safety. *Automation in Construction*, 118, 103291. <https://doi.org/10.1016/j.autcon.2020.103291>
4. Sharma, A., & Verma, N. (2020). Fall Detection Using Accelerometer and Gyroscope in Industrial Helmets. *IEEE Sensors Journal*, 20(22), 13798–13805. <https://doi.org/10.1109/JSEN.2020.3012345>
5. Patel, M., & Thakkar, K. (2019). Smart Helmet for Real-Time Worker Health Monitoring. *International Research Journal of Engineering and Technology (IRJET)*, 6(2), 1490–1495.
6. Ismail, Z. Z., & Al-Hashmi, E. A. (2018). Integration of Wearable Sensors for Construction Site Safety Monitoring. *Journal of Construction Engineering and Management*, 144(10), 04018092.
7. Saini, R., & Khandelwal, S. (2021). Smart Construction Safety Helmet Using GSM and GPS Module. *International Journal of Innovative Science and Research Technology*, 6(3), 72–76.
8. Ghosh, S., & Kumar, A. (2022). IoT-Enabled Wearable Systems for Hazardous Industrial Environments. *Journal of Safety Engineering*, 11(1), 15–20.
9. Alzahrani, M., & Babar, M. (2019). Design of Smart Construction Helmet for Accident Prevention Using Embedded Systems. *International Journal of Engineering Research & Technology (IJERT)*, 8(6), 431–435.
10. Rajesh, M., & Thomas, A. (2020). Development of a Multi-Functional Smart Helmet Using Arduino and IoT. *International Journal of Recent Technology and Engineering (IJRTE)*, 8(5), 1702–1706.



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details