



(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 14, Issue 6, June 2025

⊕ www.ijirset.com 🖂 ijirset@gmail.com 🖄 +91-9940572462 🕓 +91 63819 07438





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 6, June 2025

|DOI: 10.15680/IJIRSET.2025.1406039|

Sleep Secure Smart Cradle for Infant Comfort and Health Tracking

Prof. Borhade R.B¹, Nishigandha Pingat², Divya Bhagat², Akshit Yendhe²

Professor, Department of Computer Engineering, Samarth College of Engineering and Management, Belhe,

Pune, India¹

Students, Department of Computer Engineering, Samarth College of Engineering and Management, Belhe, Pune, India²

ABSTRACT: The Smart Cradle System is an IoT-enabled solution that enhances traditional infant care by integrating smart technology into baby cradles. Utilizing a Raspberry Pi microcontroller along with a network of sensors, the system monitors key environmental parameters such as sound, temperature, humidity, and motion around the cradle. When the baby cries or environmental conditions become unfavorable, the system can automatically respond by rocking the cradle to soothe the infant or by sending real-time alerts to caregivers.

This system aims to alleviate caregiver stress and fatigue through remote monitoring and automated responses, allowing parents or guardians to supervise the baby's well-being from a distance via a web-based dashboard and SMS or email notifications. By combining infant care with smart home automation, the Smart Cradle System represents a significant step toward modern, sensor-based parenting, offering a more convenient, responsive, and less stressful caregiving experience.

KEYWORDS: Smart Cradle System, Internet of Things (IoT), Raspberry Pi, Infant Care Technology, Remote Monitoring, Sensor-Based Cradle, Automated Infant Care, Baby Cradle Automation, Smart Home Caregiving, Environmental Monitoring

I. INTRODUCTION

Infant care demands continuous attention and effort, often resulting in physical and emotional fatigue for caregivers, especially during early developmental stages. Traditional baby cradles, while helpful, lack the ability to adapt to a baby's needs or respond to changing environmental conditions. With the advent of Internet of Things (IoT) and smart technologies, there is an opportunity to transform conventional infant care methods into automated, intelligent, and remote-controlled systems that reduce caregiver workload while ensuring the safety and comfort of the baby.

The Smart Cradle System is designed to integrate these modern technologies with a conventional cradle to offer an intelligent infant care solution. At the heart of the system is a Raspberry Pi microcontroller, which coordinates with various sensors to monitor temperature, humidity, sound, and motion in real time. If the system detects a baby crying or senses discomfort due to environmental changes, it initiates appropriate actions such as automatic cradle rocking and alert generation to notify caregivers through SMS or email notifications.

Furthermore, the system includes a web-based interface that allows caregivers to remotely monitor the cradle's status and environmental conditions. This not only provides peace of mind but also helps caregivers manage their time more efficiently by reducing the need for constant physical presence.

The primary objective of the Smart Cradle System is to provide a safe, responsive, and user-friendly environment for infants, while reducing the physical and emotional stress on caregivers. It also aligns with the growing trend of smart home systems, illustrating how IoT applications can be extended into the domain of infant and healthcare.





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 6, June 2025

|DOI: 10.15680/IJIRSET.2025.1406039|

II. LITERATURE SURVEY

Sr. No.	Name of Paper	Publisher	Authors	Year	Description	Algorithm Used
01	Smart Baby Cradle Monitoring System Using IoT	IJAREEIE	A. K. Sharma, S. R. Patel	2021	IoT-based cradle with basic sensors for motion and temperature monitoring.	Rule-Based Triggering
02	Infant Monitoring Using Sensors	IJERT	P. R. Nair, M. Thomas	2020	Microcontroller- based infant monitoring using PIR sensors and GSM module	Threshold-based Logic
03	Automatic Cradle Movement and Infant Monitoring	IEEE	R. D. Sinha	2019	Used sound detection to activate cradle movement; no mobile integration.	Sound Recognition Logic
04	IoT-Based Child Care System	IJSER	S. Gupta, A. Verma	2022	Used temperature and humidity sensors with mobile app alerts.	Sensor Monitoring Protocol
05	Sensor-Based Baby Cradle System	IJRASET	M. R. Joshi, A. Bansal	2020	Used ultrasonic sensor and vibration motor; no environmental or hygiene monitoring.	Basic Sensor- Driven Logic





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 6, June 2025

|DOI: 10.15680/IJIRSET.2025.1406039|

III. PROPOSED SYSTEM

The proposed Smart Cradle System is a technology-driven solution that integrates embedded systems, Internet of Things (IoT), and sensor-based automation to improve the quality of infant care. The aim of this system is to reduce the physical workload on caregivers while ensuring real-time monitoring of the infant's activity, hygiene, and environmental comfort. This system is designed to be compact, cost-effective, and suitable for both domestic and hospital use.

Hardware Components

Arduino Uno



Arduino UNO

The core of the hardware design revolves around the Arduino Uno microcontroller. This microcontroller serves as the processing unit of the system, collecting data from multiple sensors and controlling outputs such as the motor and notification system.

sound sensor



A Sound Sensor is an electronic device that detects sound waves and converts them into electrical signals. In the context of a Smart Cradle System, the sound sensor is used to detect when a baby is crying or making unusual noises, allowing the system to respond automatically—either by rocking the cradle, sending notifications to the caregiver, or logging the event for monitoring purposes.





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 6, June 2025 |DOI: 10.15680/IJIRSET.2025.1406039|

Moisture sensor



Environmental conditions within the cradle are monitored using a DHT11 sensor, which measures both temperature and humidity. These parameters are crucial for the comfort and safety of the infant. If the temperature or humidity levels go beyond the predefined range, the system can trigger a notification or even activate auxiliary systems like a fan or heater in advanced setups.



To automate the cradle's movement, a geared DC motor is used. This motor creates a gentle side-to-side rocking motion that soothes the baby, similar to traditional manual rocking. The motor is activated when the PIR sensor detects movement or when the system determines that the baby is unsettled. A relay module is used to control the motor's operation, ensuring safe switching of power.





T

IJIRSET©2025

15303





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 6, June 2025

|DOI: 10.15680/IJIRSET.2025.1406039|

The system is powered using a regulated power supply, typically delivering 5V or 12V depending on component requirements. Optional components such as a buzzer can be added to provide immediate audible alerts within the room when abnormal conditions are detected.

Software Technologies Used

The software design of the system is built using the Arduino Integrated Development Environment (IDE). This environment is used to write, compile, and upload the embedded C code onto the Arduino Uno microcontroller. The code contains the logic for sensor readings, decision-making processes, and motor control.

The programming is done in Embedded C, which is widely used for low-level hardware interaction and provides precise control over the sensors and actuators. The code continuously monitors inputs from the PIR, moisture, and DHT11 sensors, and activates outputs based on defined conditions.

For remote monitoring and alerting, a mobile application is developed using platforms such as Blynk, or it can be custom-built using Android Studio or similar frameworks. This application connects to the hardware via the internet using the ESP8266 module and displays real-time sensor data. Caregivers receive push notifications when the baby wakes up, wets the bed, or when there are significant changes in temperature or humidity.

To handle data exchange and storage, cloud platforms like Firebase or ThingSpeak can be integrated. These platforms facilitate the collection and visualization of real-time data, and can also store historical data for analysis.

For testing and simulation, optional software tools such as Proteus or Multisim may be used to design and simulate the circuit before actual implementation. These tools help in identifying possible circuit faults and ensure optimal hardware design.

In summary, the proposed Smart Cradle System integrates robust hardware and intelligent software to provide an automated, safe, and reliable solution for infant monitoring and care. The system leverages sensor technology, real-time data processing, and IoT communication to enhance the caregiving experience while ensuring the comfort and safety of the newborn.

IV. SYSTEM ARCHITECTURE







www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 6, June 2025

|DOI: 10.15680/IJIRSET.2025.1406039|

V. MODULES

The Smart Cradle System is designed with a modular architecture where each unit performs a specific function to automate baby care and ensure a safe and monitored environment. These modules interact seamlessly using the Raspberry Pi microcontroller as the core processing unit. Below is a detailed explanation of the functional modules, software technologies used, and the hardware components involved in the project.

1. Cry Detection (Sound Detection Module)

This module is responsible for detecting when the baby cries or makes loud sounds. It uses a KY-038 microphonebased sound sensor to continuously monitor the cradle's environment. When the baby cries or an unusual sound is detected, the sound sensor triggers the Raspberry Pi to take action. The sound level is compared against a predefined threshold. Upon detection, it activates the cradle's rocking mechanism and simultaneously sends an alert notification to the caregiver using email or SMS.

2. Cradle Rocking Mechanism

The cradle rocking module is designed to calm the baby through gentle motion. A geared DC motor or servo motor connected to the cradle is used for this purpose. When the cry detection module sends a signal indicating that the baby is awake or uncomfortable, the Raspberry Pi controls the motor via GPIO pins to initiate a side-to-side rocking motion. This rocking can be timed and stopped automatically once silence is restored or manually stopped via a user interface.

3. Environmental Monitoring Module

To ensure the baby's comfort, the system includes a temperature and humidity monitoring module using the DHT11 or DHT22 sensor. The Raspberry Pi reads real-time environmental data through the Adafruit_DHT library. If the detected temperature or humidity exceeds safe levels for an infant, the system triggers a notification, alerting the caregiver to take necessary action, such as adjusting room conditions.

4. Bed-Wet Detection Module

This module detects any bed-wetting incidents using a moisture sensor placed under the mattress or baby pad. The moisture sensor identifies any liquid presence and signals the Raspberry Pi. The system responds by sending a notification to the caregiver, allowing quick intervention to maintain hygiene and comfort for the baby.

5. Central Processing & Logic Control

The core control module of the system is the Raspberry Pi (preferably Pi 3 or Pi 4). It acts as the main controller, gathering input from all sensors, executing programmed logic, and triggering appropriate outputs. Python scripts manage all the control operations, sensor data reading, motor actuation, and alert systems in a multi-threaded fashion for real-time responsiveness.

6. Notification and Communication Interface

The communication module facilitates real-time alerts using either email (through smtplib) or optional SMS services using Twilio API. All data processing and trigger decisions are handled by the Raspberry Pi. Alerts are configured for sound detection, wet bed detection, and environmental anomalies. For remote monitoring, the system can optionally be extended with cloud support or a mobile app interface.

7. Web Interface / Dashboard (Optional)

Using the Flask web framework, a simple lightweight web interface can be developed to allow caregivers to remotely view the cradle status and manually trigger the rocking mechanism. The web app displays real-time temperature, humidity, and sound activity. It can be accessed from any browser within the local network or over the internet if port forwarding or cloud hosting is enabled.

8. Power Supply Unit

The entire system is powered using a regulated 5V/12V DC supply. A combination of power adapters and voltage regulators (like the 7805 or AMS1117) ensures stable power delivery to the Raspberry Pi, sensors, and motors. Rechargeable batteries or UPS modules may be used for uninterrupted power in case of outages.





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 6, June 2025

|DOI: 10.15680/IJIRSET.2025.1406039|

Software Technologies Used

The system's software backbone is built using Python on the Raspberry Pi platform. The major libraries and frameworks used include:

- **RPi.GPIO or gpiozero**: To interface and control GPIO pins for sensors and motor.
- Adafruit_DHT: For reading data from the temperature and humidity sensor.
- **smtplib** / **email**: For sending email alerts to caregivers in real-time.
- **Twilio (optional)**: For sending SMS alerts using the Twilio cloud messaging service.
- Flask or Django: Lightweight Python-based web frameworks for building the web server and REST APIs for remote control and monitoring.
- threading module: For running parallel tasks such as monitoring multiple sensors simultaneously.

Hardware Components Used

The following key hardware components are used in the Smart Cradle System:

- Raspberry Pi (Model 3B/4): Main processing unit that controls all functions and processes sensor inputs.
- KY-038 Sound Sensor: Detects baby's cry or loud sounds.
- DHT11 / DHT22 Sensor: Monitors temperature and humidity within the cradle.
- Moisture Sensor: Detects bed-wetting conditions to maintain baby hygiene.
- DC Geared Motor / Servo Motor: Provides cradle rocking motion.
- Motor Driver Module (e.g., L298N): Controls power supply to motor based on Raspberry Pi commands.
- Power Supply (5V or 12V Adapter + Voltage Regulator): Powers the Raspberry Pi, motor, and all sensors.
- Cables, Connectors, Breadboard, Jumper Wires: Used for circuit assembly and connectivity.

VI. SCOPE OF THE PROJECT

The Smart Cradle System has a wide-ranging scope that extends from individual households to professional childcare environments such as maternity wards and neonatal care units. By integrating real-time monitoring and automation, this system greatly enhances traditional cradle functionalities.

Scope Includes:

- 1. Home Use:
 - Assists parents in taking care of newborns, especially during the night or when multitasking.
 - Provides peace of mind through automated cradle movement and mobile alerts.
- 2. Healthcare Facilities:
 - Can be deployed in maternity hospitals, nursing homes, and infant care centers to reduce the workload of nursing staff.
 - Ensures hygienic and safe monitoring for multiple infants simultaneously.
- 3. Future Scalability:
 - Can be enhanced with AI integration for predictive infant behavior analysis.
 - Video monitoring and cloud storage integration can be added for better analytics and record-keeping.
 - Support for multiple caregivers/users via app notifications.
- 4. Safety and Hygiene Enhancement:
 - Early detection of wet bedding ensures better hygiene and comfort.
 - Monitors and alerts environmental changes to prevent illnesses caused by cold or overheating.
- 5. Cost-Effective Infant Care Solution:
 - Uses affordable and easily available components.
 - Reduces the need for constant human intervention, making it suitable for `economically constrained environments.





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|







www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 6, June 2025

|DOI: 10.15680/IJIRSET.2025.1406039|

≡	M Gn	nail	Q Sear	ch mail		Ŧ		?	()		N
0	÷	•		⊡ :			1.	of 582	<	>	3
☆		Verify	Email Inbox ×					×	₽	ß	
⊘ ⊿	*	novacop to me 👻	ops.rcpit@gmail.com			10:43 (30 minutes ago)	☆	٢	4	:	e
C * ~		Results									
+		Label	Confidence	Timestamp							
		Label Happy	Confidence 0.249303936958313	Timestamp 2025-05-21 13:30:59							+
		CRYING	0.2902716994285583	5 2025-05-21 13:31:24 6 2025-05-21 13:31:33							
		CRYING	0.3340694308280945	2025-05-21 13:31:43							
		Нарру	0.2335546910762787	2025-05-21 13:32:17							
		Нарру	0.2363948673009872	4 2025-05-21 13:32:40							
		Neutral CRYING	0.4300461411476135 0.3499957323074341	2025-05-21 13:32:55 2025-05-21 13:33:19							>

VIII. CONCLUSION

The Smart Cradle System represents a significant advancement in automating infant care by integrating IoT and embedded technologies. It offers a reliable, intelligent, and responsive solution for monitoring and soothing infants, particularly in the absence of constant human supervision. By combining modules such as cry detection, environmental monitoring, bed-wet detection, and an automatic rocking mechanism, the system ensures that babies receive timely attention and comfort.

The use of Raspberry Pi as the central processing unit provides flexibility and scalability, enabling real-time data processing and alert notifications through email or SMS. The optional integration with web dashboards or mobile applications further enhances remote accessibility for caregivers, making the system practical in both home and hospital environments.

Through this project, we have demonstrated how embedded systems and IoT can be leveraged to solve real-world problems, reduce caregiver workload, and improve infant well-being. Future enhancements may include AI-based cry pattern recognition, mobile app integration, or cloud-based data analytics to make the system even smarter and more adaptive.

REFERENCES

- 1. V. M. R. Kiran, R. R. Murthy, "Smart Cradle for Baby Monitoring using IoT," International Journal of Engineering and Advanced Technology (IJEAT), vol. 9, no. 3, pp. 1205-1209, Feb. 2020.
- 2. Chatterjee, S. Biswas, "Baby Monitoring System Using Arduino and IoT," International Research Journal of Engineering and Technology (IRJET), vol. 6, no. 4, pp. 2399-2403, Apr. 2019.
- 3. M. A. Khan, R. Kumar, "Smart Cradle Using IoT," International Journal of Scientific Research and Engineering Development (IJSRED), vol. 2, no. 5, pp. 899-904, Sept. 2019.
- 4. M. S. Bhosale, R. G. Borse, "IoT Based Baby Monitoring System," International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET), vol. 8, no. 6, pp. 5624-5630, June 2019.
- 5. DHT11 Datasheet. [Online]. Available: https://components101.com/sensors/dht11-temperature-sensor
- 6. Raspberry Pi Documentation. [Online]. Available: https://www.raspberrypi.org/documentation/
- 7. Sound Sensor KY-038 Module Technical Overview. [Online]. Available: https://lastminuteengineers.com/sound-sensor-arduino-tutorial/
- 8. Adafruit Industries, "DHT Sensor Library Documentation," [Online]. Available: https://learn.adafruit.com/dht
- 9. Twilio API Documentation. [Online]. Available: https://www.twilio.com/docs
- 10. Python Official Documentation smtplib, threading, Flask. [Online]. Available: https://docs.python.org/









INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com