



# International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

*(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)*



**Impact Factor: 8.699**

**Volume 14, Issue 3, March 2025**

# A Comprehensive Survey of Retrieval-Augmented Generation (RAG): Evolution, Current Landscape and Future Directions

Shailja Gupta<sup>\*1</sup>, Rajesh Ranjan<sup>\*2</sup>, Surya Narayan Singh<sup>\*3</sup>

Carnegie Mellon University, USA <sup>1,2</sup>

BIT Sindri, India<sup>3</sup>

\* Core Contributor

**ABSTRACT:** This paper presents a comprehensive study of Retrieval-Augmented Generation (RAG), tracing its evolution from foundational concepts to the current state of the art. RAG combines retrieval mechanisms with generative language models to enhance the accuracy of outputs, addressing key limitations of LLMs. The study explores the basic architecture of RAG, focusing on how retrieval and generation are integrated to handle knowledge-intensive tasks. A detailed review of the significant technological advancements in RAG is provided, including key innovations in retrieval-augmented language models and applications across various domains such as question-answering, summarization, and knowledge-based tasks. Recent research breakthroughs are discussed, highlighting novel methods for improving retrieval efficiency. Furthermore, the paper examines ongoing challenges such as scalability, bias, and ethical concerns in deployment. Future research directions are proposed, focusing on improving the robustness of RAG models, expanding the scope of application of RAG models, and addressing societal implications. This survey aims to serve as a foundational resource for researchers and practitioners in understanding the potential of RAG and its trajectory in natural language processing.

**KEYWORDS:** Retrieval-Augmented Generation (RAG), Information Retrieval, Natural Language Processing (NLP), Artificial Intelligence (AI), Machine Learning (ML), Large Language Model

## I. INTRODUCTION

Natural Language Processing (NLP) is a key foundation for applications ranging from simple text classification to more complex tasks such as summarization, machine translation, and question-answering. Natural Language Generation (NLG) focuses on generating coherent, relevant, and context-aware text, improving interactions between humans and machines (Gatt et al. 2018). Traditional NLG models, especially sequence-to-sequence architectures (Sutskever et al. 2014), have exhibited significant advancements in generating fluent and coherent text. These models struggle to generate factually accurate or contextually rich content for queries that require knowledge beyond their training set. As a result, models like GPT (Radford et al. 2019) or BERT-based (Devlin et al. 2019) are prone to hallucinations, where they produce plausible but incorrect or nonexistent information (Ji et al. 2022). Retrieval-augmented generation (RAG) addresses these challenges by retrieving contextually relevant information from large, external datasets and grounding its responses in real-world knowledge, significantly reducing hallucinations and increasing factual accuracy. There has been a rise in research contributions focused on improving retrieval mechanisms and integrating them seamlessly with advanced generative models. These innovations have led to breakthroughs in several applications such as open-domain question answering, document summarization, conversational AI, and domain-specific tasks in fields like healthcare, legal advisory, and education. (Izacard et al., 2021). Models like Dense Passage Retrieval (DPR) (Karpukhin et al., 2020) and Fusion-in-Decoder (Izacard et al., 2021) have shown significant improvements over traditional generative or retrieval-only models. In conversational AI, RAG models have enhanced the capabilities of dialogue systems through coherent and factual information (Roller et al., 2020). New methods across the RAG components, such as retrieval optimization, hybrid retrieval, and multimodal integration, are emerging, but there is a lack of sufficient resources to synthesize the progress of the field. This paper fills these gaps by providing a systematic and thorough review of the evolution of RAG systems, their architectural advancements, applications, and ongoing challenges and serves as a foundational resource for researchers and practitioners. It synthesizes existing knowledge and identifies critical areas

for future research, such as scalability, multimodal retrieval, ethical considerations, and cross-lingual capabilities. This paper aims to provide a comprehensive survey of RAG models by summarizing key trends in RAG systems, including the shift toward multimodal integration and hybrid retrieval techniques, highlighting challenges that persist in scalability, efficiency, and bias mitigation, and proposing future research directions, emphasizing cross-modal capabilities, ethical considerations, and personalization.

## II. METHODOLOGY

This paper employs a structured survey methodology to capture the evolution, advancements, and challenges in RAG systems. The following steps were performed:

- **Data Sources:** Academic databases, including Google Scholar, IEEE Xplore, and ArXiv, were searched for relevant publications.
- **Search Terms:** Keywords such as “retrieval-augmented generation,” “RAG systems,” “dense retrieval,” “hybrid NLP models,” and “large language models with retrieval” were used to identify relevant research.
- **Categorization:** Selected papers were categorized into key themes, such as retriever mechanisms, generator advancements, multimodal RAG, and domain-specific applications.

The findings from the literature review were synthesized to summarize key trends in RAG systems, highlight challenges, and propose future research directions.

## III. RELATED WORK

### 3.1 Overview of RAG Models

Retrieval-augmented generation (RAG) is a hybrid architecture that integrates two key components: a retrieval mechanism, which retrieves relevant documents or information from an external knowledge source, and a generation module, which processes this information to generate human-like text (Lewis et al. 2020). This combination allows RAG models to not only generate fluent text but also ground their outputs in real-world, up-to-date data. The retrieval module in RAG typically leverages dense vector representations to identify relevant documents from large datasets. After retrieval, these documents are passed to the generative module, often built using transformer-based architectures, to generate responses grounded in the retrieved knowledge. This methodology helps mitigate the hallucination problem and ensures that the generated text is more factual and contextually appropriate (Thakur et al., 2021). Over the period, RAG models have seen applications in various domains, including open-domain question answering (Karpukhin et al., 2020), conversational agents (Liu et al., 2021), and personalized recommendations.




Figure 1: A basic flow of the RAG system along with its component



Before the introduction of RAG, NLP models primarily relied on either retrieval or generation approaches, each with its own set of advantages and limitations. Retrieval-based systems, such as traditional information retrieval engines (Salton et al., 1975), efficiently provided relevant documents or snippets in response to a query but could not synthesize new information or present the results in a coherent narrative. On the other hand, purely generative models, which became popular with the rise of transformer architectures (Vaswani et al. 2017), offered fluency and creativity but often lacked factual accuracy.

This hybrid system combining retrieval and generation began to gain momentum as researchers recognized the complementary strengths of both approaches. Early efforts in hybrid modeling go back to works like DrQA (Chen et al. 2017), which employed retrieval techniques to fetch relevant documents for question-answering tasks. However, the generative component in such systems was minimal, often limited to selecting text directly from the retrieved documents. Similarly, in models like Information Retrieval (Dai et al. 2019), retrieval was treated as distinct, independent components. The real innovation came with the realization that retrieval and generation could be tightly integrated. Models like REALM (Gua et al., 2020) represented a key milestone, as they trained the retrieval and generative components jointly, enabling better alignment between the retrieved information and the generated output. RAG (Lewis et al. 2020) further extended this paradigm by using dense passage retrieval (Karpukhin et al., 2020) to fetch relevant documents and transformers such as BART (Lewis et al., 2020) for a generation. This architecture provided a more seamless integration of retriever, which retrieves the most relevant documents from a corpus using techniques such as dense passage retrieval (DPR) (Karpukhin et. al. 2020) or traditional BM25 algorithms and **generators**, which synthesize the retrieved documents into coherent, contextually relevant responses. RAG's strength lies in its ability to leverage external knowledge dynamically, allowing it to outperform generative models like GPT-3 and knowledge-grounded systems like BERT, which rely on static datasets. In open-domain question answering, RAG has been demonstrated to be highly effective, consistently retrieving relevant information and improving the factual accuracy of the generated responses (Gua, K., et al. 2020). In addition to knowledge retrieval, RAG models excel at updating knowledge bases. Since the model fetches external documents for each query, it requires no retraining to incorporate the latest information. This flexibility makes RAG models particularly suitable for domains where information is constantly evolving, such as medical research, financial news, and legal proceedings. Furthermore, studies have shown that RAG models achieve superior results in a variety of knowledge-intensive tasks, including document summarization and knowledge-grounded dialogues

### 3.2 Retriever Mechanisms in RAG Systems

Several retrieval mechanisms are commonly used, ranging from traditional methods like BM25 to more sophisticated techniques like Dense Passage Retrieval (DPR) and top k retrieved items are used for the next stage of RAG.

$$\text{Retrieval Scoring} = \text{Score}(q, d_i) = \text{Sim}(\phi(q), \psi(d_i))$$

q: Query representation)

d<sub>i</sub>: Document representation

φ, ψ: Encoding functions (e.g., dense or sparse)

Sim: Similarity function (e.g., dot product, cosine similarity, or BM25 scoring)

#### Top-k Retrieval:

$$z = \text{Top} - k_{d_i \in D}(\text{Score}(q, d_i))$$

Where z is the set of retrieved documents.

BM25 is a well-established information retrieval algorithm that uses the term frequency-inverse document frequency (TF-IDF) to rank documents according to relevance. Despite being a classical method, BM25 remains a strong baseline for many modern retrieval systems, including those used in RAG models. BM25 calculates the relevance score of a document based on how frequently a query term appears in the document while adjusting for the document's length and the frequency of the term across the corpus (Robertson et. al. 2009). While BM25 is effective for keyword matching, it has limitations in understanding semantic meaning, which means BM25 cannot capture the relationships between words and tends to perform poorly on more complex, natural language queries that require an understanding of context. Despite this limitation, BM25 is still widely used because of its simplicity and efficiency. BM25 is effective for tasks

involving simpler, keyword-based queries, although more modern retrieval models like DPR tend to outperform it in semantically complex tasks. Dense Passage Retrieval (DPR), introduced by Karpukhin et al. (2020), represents a more modern approach to information retrieval. It uses a dense vector space in which both the query and the documents are encoded into high-dimensional vectors. DPR employs a bi-encoder architecture, where the query and documents are encoded separately, allowing for efficient nearest-neighbor search (Xiong et al. 2020). DPR excels at capturing semantic similarity between the query and documents, making it highly effective for open-domain question-answering tasks. The strength of DPR lies in its ability to retrieve relevant information based on semantic meaning rather than keyword matching. By training the retriever on a large corpus of question-answer pairs, DPR can find documents that are contextually related to the query, even when the query and the document do not share exact terms. Recent research has further improved DPR by integrating it with pre-trained language models, and an example is LLM adapted for the dense Retrieval approach (Li et al., 2023). A significant advancement, REALM (Gua et al. (2020) integrate retrieval into the language model's pre-training process, ensuring that the retriever is optimized alongside the generator for downstream tasks. REALM learns to retrieve documents that improve the model's performance on specific tasks, such as question answering or document summarization. During training, REALM updates both the retriever and the generator, ensuring that the retrieval process is optimized for the generation task, significantly improving the quality of generated responses. Several current methods rely on similarity-based retrieval (Mallen et al. 2022) however, Self-RAG (Asai et al. 2023b), and REPLUG (Shi et al., 2023) have advanced by leveraging LLMs to enhance retrieval capabilities, achieving more adaptive retrieval. After initial retrieval, cross-encoder models are used to re-rank the retrieved results by jointly encoding the query and each retrieved document to compute relevance scores. These models provide more context-aware retrieval at the cost of higher computational overhead. Pointwise and Pairwise Ranking, often based on Learning-to-Rank (LTR) algorithms, are used to assign relevance scores to retrieved documents, either independently (pointwise) or by comparing document pairs (pairwise). RAG systems utilize self-attention within the LLM to manage context and relevance across different parts of the input and retrieved text. Cross-attention mechanisms are used when integrating retrieved information into the generative model, ensuring that the most relevant pieces of information are emphasized during generation.

### 3.3 Generator Mechanisms in RAG Systems

After the retrieval component pulls relevant knowledge from external sources, the generator synthesizes this information into coherent, contextually appropriate responses. The Large Language Model (LLM) serves as the backbone of the generator, which ensures the generated text is fluent, accurate, and aligned with the original query.

**Conditional Text Generation:**  $P(y | q, z) = \prod_{t=1}^T P(y_t | y_{<t}, q, z; \theta)$

Where:

$y_t$ : Token at step  $t$ .

$y_{<t}$ : Tokens generated up to step  $t$ .

$\theta$ : Model parameters.

T5 (Text-to-Text Transfer Transformer) (Raffel et al. 2020) is a commonly used model for generation tasks in RAG systems as it is versatile in its approach, framing every NLP task as a text-to-text task. T5's ability to handle complex multi-task learning makes it a popular choice for RAG systems that need to tackle a diverse range of knowledge-intensive tasks. BART (Bidirectional and Auto-Regressive Transformer), introduced by Lewis et al. (2020), is a prominent generative model used in RAG systems and is well-suited for tasks involving text generation from noisy inputs, such as summarization and open-domain question answering. BART can reconstruct corrupted text sequences, making it robust for tasks that require the generation of coherent, factual outputs from incomplete or noisy data.

## IV. RAG ACROSS MODALITIES

**Text-based RAG models** leverage textual data for both retrieval and generation tasks, enabling applications such as question-answering, summarization, and conversational agents. Transformer architectures, such as BERT (Devlin et al., 2019) and T5 (Raffel et al., 2020), are foundational in text-based RAG models. These models utilize self-attention mechanisms to capture contextual relationships within text, which enhances both retrieval accuracy and generation

fluency. Dense retrieval models, such as those using dense embeddings from BERT, offer superior performance compared to traditional sparse methods like TF-IDF. Dense retrievers (Karpukhin et al. 2020) leverage dense representations to retrieve relevant documents more effectively. **Audio-based RAG Models** extend the principles of retrieval-augmented generation to the audio modality, enabling applications such as speech recognition, audio summarization, and conversational agents in voice interfaces. Audio data is often represented using embeddings derived from pre-trained models like Wav2Vec 2.0 (Baevski et al., 2020). These embeddings serve as input to retrieval and generation components, enabling the model to handle audio data effectively. **Video-Based RAG Models** incorporate both visual and audio information to enhance performance in tasks such as video understanding, captioning, and retrieval. Video data is represented using embeddings from models like I3D (Xie et. al. 2017) or TimeSformer (Bertasius et al. 2021). These embeddings capture temporal and spatial features essential for effective retrieval and generation. **Multimodal RAG models** integrate data from multiple modalities—text, audio, video, and images—to provide a more holistic approach to retrieval and generation tasks. Models like Flamingo (Alayrac et al., 2022) integrate multiple modalities into a unified framework, enabling simultaneous processing of text, images, and videos. Techniques for cross-modal retrieval involve retrieving relevant information across different modalities (Li. et. al., 2023). Multimodal capabilities enhance the versatility and efficiency of RAG across various applications. "Retrieval as generation" (Wang et. al. 2024) extends the Retrieval-Augmented Generation (RAG) framework to multimodal applications by incorporating text-to-image and image-to-text retrieval. Utilizing a large dataset of paired images and text descriptions, the system accelerates image generation when user queries align with stored text descriptions.




Figure 2: Timeline of the evolution of the RAG system and its components

## V. RECENT ADVANCEMENT IN THE FIELD

A novel agentic Retrieval-Augmented Generation (RAG) framework (Ravuru et. al. 2024) employs a hierarchical, multi-agent architecture where specialized sub-agents, using smaller pre-trained language models (SLMs), are fine-tuned for specific time series tasks. The master agent delegates tasks to these sub-agents, who retrieve relevant prompts from a shared knowledge repository. In this modular, multi-agent approach, the authors achieve state-of-the-art performance, improving flexibility and effectiveness over task-specific methods in time series analysis. RULE (Xia et. al. 2024), a multimodal Retrieval-Augmented Generation (RAG) framework designed to improve the factuality of medical Vision-Language Models (Med-LVLM), addresses challenges in medical RAG by introducing a calibrated selection strategy to control factuality risk and, by developing a preference optimization strategy to balance the model's



intrinsic knowledge with retrieved contexts, proving its effectiveness in enhancing factual accuracy in Med-LVLM systems. METRAG (Gan et. al. 2024), a multi-layered, thoughts-enhanced retrieval-augmented generation framework, integrates LLM supervision to generate utility-oriented thoughts and combines document similarity with utility for improved performance. It also incorporates a task-adaptive summarizer to produce compact thoughts. Using the multi-layered thoughts from these stages, an LLM generates knowledge-augmented content, demonstrating superior performance on knowledge-intensive tasks compared to traditional approaches. Distractor document is one of the key traits of Retrieval Augmented Fine-Tuning (RAFT) (Zhang et. al. 2024) where the model is trained to disregard irrelevant, distractor documents and instead cite directly from relevant sources. This process, combined with a chain-of-thought reasoning style, enhances the model's reasoning capabilities. RAFT demonstrates consistent performance improvements in domain-specific RAG tasks, including PubMed, HotpotQA, and Gorilla datasets, and serves as a post-training enhancement for LLMs. FILCO (Wang et. al. 2023), a method designed to enhance the quality of context provided to generative models in tasks like open-domain question answering and fact verification, addresses issues of over- or under-reliance on retrieved passages, which can lead to problems such as hallucinations in the generated outputs. The method improves context quality by identifying useful context through lexical and information-theoretic approaches and training context filtering models to refine retrieved contexts during test time. Reflection token is a key attribute of self-reflective retrieval augmented generation (Self-RAG) (Asai et. al. 2023), a novel framework designed to improve the factual accuracy of large language models (LLMs) by combining retrieval with self-reflection. Unlike traditional methods that retrieve and incorporate a fixed number of passages, Self-RAG adaptively retrieves relevant passages and uses reflection tokens to evaluate and refine its responses, allowing the model to adjust its behavior according to task-specific needs. A novel data-centric RAG workflow advances beyond the traditional retrieve-then-read mode and employs a prepare-then-rewrite-then-retrieve-then-read framework, enhancing LLMs by integrating contextually relevant, time-critical, or domain-specific information. Key innovations include generating metadata, synthetic Questions and Answers (QA), and introducing the Meta Knowledge Summary (MK Summary) for clusters of documents (Mombaerts et. al., 2024). CommunityKG-RAG (Chang et. al. 2024) introduces a zero-shot framework that integrates community structures within Knowledge Graphs (KGs) into Retrieval-Augmented Generation (RAG) systems, enhancing the accuracy and contextual relevance of fact-checking by utilizing multi-hop connections within KGs, outperforming traditional methods without requiring additional domain-specific training. The RAPTOR model (Sarathi et. al. 2024) introduces a hierarchical approach to retrieval-augmented language models, addressing limitations in traditional methods that retrieve only short, contiguous text chunks. RAPTOR forms a summary tree to retrieve information at varying abstraction levels by recursively embedding, clustering, and summarizing text. When paired with GPT-4, RAPTOR improves accuracy on the Quality benchmark by 20%. A recent study (Li et. al. 2024) compared the efficiency of RAG and long-context (LC) Large Language Models (LLMs), such as Gemini-1.5 and GPT-4. While LC models outperform RAG when adequately resourced, RAG's cost-efficiency remains advantageous. To balance performance and cost, the paper introduces Self-Route which dynamically directs queries to either RAG or LC based on model self-reflection, optimizing both computation cost and performance. (Nguyen et. al., 2024) introduce SFR-RAG, designed to enhance the integration of external contextual information into LLMs while minimizing hallucinations. LA-RAG (Li et. al., 2024), a novel RAG paradigm designed to enhance Automatic Speech Recognition (ASR) in large language models (LLMs). One of the key benefits of LA-RAG is its ability to leverage fine-grained token-level speech data stores alongside a speech-to-speech retrieval mechanism, improving ASR accuracy by incorporating LLM in-context learning (ICL). The study focuses on datasets of Mandarin and various Chinese dialects, demonstrating significant accuracy improvements, particularly in managing accent variations, which have historically been challenging for existing speech encoders. The findings highlight LA-RAG's potential to advance ASR technology, offering a more robust solution for diverse acoustic conditions. HyPA-RAG (Kalra et. al., 2024), a Hybrid Parameter-Adaptive Retrieval-Augmented Generation system, improves accuracy by using adaptive parameter tuning and hybrid retrieval strategies. Tested on NYC Local Law 144 (LL144), HyPA-RAG demonstrates enhanced correctness and contextual precision, addressing the complexities of legal texts. MemoRAG (Qian et. al., 2024) introduces a novel RAG paradigm designed to overcome the limitations of traditional RAG systems in handling ambiguous or unstructured knowledge. MemoRAG's dual-system architecture utilizes a lightweight long-range LLM to generate draft answers and guide retrieval tools, while a more powerful LLM refines the final output. This framework, optimized for better cluing and memory capacity, significantly outperforms conventional RAG models across both complex and straightforward tasks. NLLB-E5 (Acharya et. al., 2024) introduces a scalable multilingual retrieval model aimed at addressing the challenges faced in supporting multiple languages, particularly low-resource languages like Indic languages. By leveraging the NLLB encoder and a distillation approach from the E5 multilingual retriever, NLLB-E5 enables zero-shot retrieval across languages without the need for multilingual training data. Evaluations on

benchmarks such as Hindi-BEIR showcase its robust performance, highlighting task-specific challenges and advancing multilingual information access for global inclusivity.

1. **Multi-Agent and Modular RAG Architectures**
  - ✓ A novel agentic RAG framework (Ravuru et al., 2024)
  - ✓ METRAG (Gan et al., 2024)
  - ✓ MemoRAG (Qian et al., 2024)
2. **Enhancing Factuality and Context Filtering in RAG**
  - ✓ RULE (Xia et al., 2024)
  - ✓ RAFT (Zhang et al., 2024)
  - ✓ FILCO (Wang et al., 2023)
  - ✓ Self-RAG (Asai et al., 2023)
3. **RAG for Specialized Domains (Medical, Legal, Speech, and Multilingual Applications)**
  - ✓ LA-RAG (Li et al., 2024)
  - ✓ HyPA-RAG (Kalra et al., 2024)
  - ✓ NLLB-E5 (Acharya et al., 2024)
4. **Retrieval Optimization and Adaptive Query Routing**
  - ✓ RAPTOR (Sarathi et al., 2024)
  - ✓ Self-Route (Li et al., 2024)
  - ✓ SFR-RAG (Nguyen et al., 2024)
5. **Knowledge Graph and Metadata-Enhanced RAG**
  - ✓ Community-RAG (Chang et al., 2024)
  - ✓ Data-centric RAG workflow (Mombaerts et al., 2024)

Figure 3: Evolving Trends in RAG captured from research papers

## **VI. CURRENT CHALLENGES AND LIMITATIONS IN RETRIEVAL AUGMENTED GENERATION (RAG)**

Despite the promise of RAG, several challenges need attention. The retrieval mechanism, while powerful, can still struggle with retrieving the most relevant documents, particularly when dealing with ambiguous queries or niche knowledge domains. The reliance on dense vector representations, such as those used in DPR, can sometimes lead to irrelevant or off-topic documents being retrieved. Efforts to refine retrieval techniques, including the incorporation of more sophisticated query expansion and contextual disambiguation, are needed to improve performance in these areas. The integration between retrieval and generation, while seamless in theory, can sometimes fail in practice. For instance, the generative module may not always effectively incorporate the retrieved information into its responses, leading to inconsistencies or incoherence between the retrieved facts and the generated text. Research into better alignment mechanisms, such as improved attention models or hierarchical fusion techniques, may help alleviate these issues (Izacard et al. 2021). Additionally, the computational overhead of RAG models is a concern, as they require both a retrieval and a generation step for each query. This dual process can be resource-intensive, particularly for large-scale applications (Borgeaud et al. 2021). Techniques such as model pruning (Han et al. 2015) or knowledge distillation (Sanh et al., 2019) may offer ways to reduce the computational burden without sacrificing performance. Finally, there



are ethical concerns associated with the deployment of RAG models, particularly in terms of bias and transparency. Biases in AI and LLM have been a well-researched and evolving field with researchers identifying different types of biases not limited to gender, socio-economic class, or even educational background (Gupta et. al. 2024; Ranjan et. al., 2024). While RAG has the potential to reduce biases by retrieving more balanced information, there is still the risk of amplifying biases present in the retrieved sources (Binns, 2018). Furthermore, ensuring transparency in how retrieval results are selected and used in generation is crucial for maintaining trust in these systems. Other key challenges are described below:

**Scalability and Efficiency:** One of the primary challenges for RAG models is scalability. As retrieval components rely on external databases, handling vast and dynamically growing datasets requires efficient retrieval algorithms. High computational costs and memory requirements also make it difficult to deploy RAG models in real-time or resource-constrained environments (Shi et al., 2023); (Asai et al., 2023b).

**Retrieval Quality and Relevance:** Ensuring the quality and relevance of retrieved documents remains a significant concern. Retrieval models can sometimes return irrelevant or outdated information, which negatively affects the accuracy of the generated output. Improving retrieval precision, especially for long-form content generation, remains an active area of research (Mallen et al., 2022); (Shi et al., 2023).

**Bias and Fairness:** Similar to other machine learning models, RAG systems can exhibit bias due to biases present in the retrieved datasets. Retrieval-based models may amplify harmful biases in retrieved knowledge, leading to biased outputs in a generation. Developing bias mitigation techniques for retrieval and generation in tandem is an ongoing challenge.

**Coherence:** RAG models often struggle with integrating the retrieved knowledge into coherent, contextually relevant text. The alignment between retrieved passages and the generation model's output is not always seamless, leading to inconsistencies or factual hallucinations in the final response (Ji et al., 2022).

**Interpretability and Transparency:** Like many AI systems, RAG models are often treated as black boxes, with limited transparency in how retrieval influences generation. Improving the interpretability of these models is crucial to fostering trust, especially in critical applications (Roller et al. 2020).

## VII. FUTURE RESEARCH DIRECTIONS FOR RAG

RAG represents a significant advancement in natural language processing and related fields by combining retrieval and generative mechanisms. This section explores key areas for future research, highlighting the potential for innovation and improvement in RAG systems.

**Enhancing Multimodal Integration:** The integration of text, image, audio, and video data in RAG models remains an evolving challenge. Future research should focus on improving multimodal fusion techniques to enable seamless interaction between different data types. This includes developing advanced methods for aligning and synthesizing information across modalities. Recent works (Chen et. al., 2022), (Yasunaga et. al., 2022), (Zhu et. al., 2024) have explored multimodal learning, but further innovations are needed to enhance the coherence and contextuality of multimodal outputs. Research into cross-modal retrieval aims to improve the ability of RAG systems to retrieve relevant information across different modalities. For example, combining text-based queries with image or video content retrieval could enhance applications such as visual question answering and multimedia search.

**Scaling and Efficiency:** As RAG models are deployed in increasingly large-scale applications, scalability becomes a critical concern. Research should focus on developing methods to efficiently scale retrieval and generation processes without compromising performance. Techniques such as distributed computing and efficient indexing methods are essential for handling large datasets. Improving the efficiency of RAG models involves optimizing both retrieval and generation components to reduce computational resources and latency.

**Personalization and Adaptation:** Future RAG models should focus on personalizing retrieval processes to cater to individual user preferences and contexts. This involves developing techniques to adapt retrieval strategies based on user history, behavior, and preferences. Enhancing the contextual adaptation of RAG models by a deeper understanding of the context and sentiments of the query (Gupta et. al. 2024) and the repository of documents is crucial for improving

the relevance of generated responses. Research should explore methods for dynamic adjustment of retrieval and generation processes based on the evolving context of interactions. This includes incorporating user feedback and contextual cues into the RAG pipeline.

**Ethical and Privacy Considerations:** Addressing biases (Shrestha et. al., 2024; Gupta et. al., 2024) in general and specific to RAG models is a critical area for future research. As RAG systems are deployed in diverse applications, ensuring fairness and mitigating biases in retrieved and generated content is essential. Future RAG research should focus on privacy-preserving techniques to protect sensitive information during retrieval and generation. This includes developing methods for secure data handling and privacy-aware retrieval strategies. Interpretability of the model is also a critical area to focus upon as a part of ongoing research in improving RAG.

**Cross-Lingual and Low-Resource Languages:** Expanding RAG technology to support multiple languages (Chirkova et. al. 2024), especially low-resource languages, is a promising direction. Future research should aim to improve cross-lingual retrieval and generation capabilities to provide accurate and relevant results across different languages. Enhancing RAG models to effectively support low-resource languages involves developing methods to retrieve and generate content with limited training data. Research should focus on techniques for transfer learning and data augmentation to improve performance in underrepresented languages.

**Advanced Retrieval Mechanisms:** Future RAG research should explore dynamic retrieval mechanisms that adapt to changing query patterns and content requirements. This includes developing models that can dynamically update their retrieval strategies based on new information and evolving user needs. Investigating hybrid retrieval approaches that combine various retrieval strategies, such as dense and sparse retrieval, could enhance the effectiveness of RAG systems. Research should explore how to integrate different retrieval methods to achieve optimal performance for diverse tasks.

**Integration with Emerging Technologies:** Integrating RAG models with brain-computer interfaces (BCIs) could lead to novel applications in human-computer interaction and assistive technologies. Research should explore how RAG systems can leverage BCI data to enhance user experience and generate context-aware responses. The integration of RAG with AR and VR technologies presents opportunities for creating immersive and interactive experiences. Future research should investigate how RAG models can be used to enhance AR and VR applications by providing contextually relevant information and interactions.

## **VIII. CONCLUSION**

Retrieval Augmented Generation (RAG) has undergone significant evolution, with extensive research dedicated to improving retrieval effectiveness and enhancing coherent generation to minimize hallucinations. From its early iterations to recent advancements, RAG has been instrumental in integrating external knowledge into Large Language Models (LLMs), thereby boosting accuracy and reliability. In particular, recent domain-specific work has showcased RAG's potential in specialized areas such as legal, medical, and low-resource language applications, highlighting its adaptability and scope. However, despite these advances, this paper identifies clear gaps that remain unresolved. Challenges such as the integration of ambiguous or unstructured information, effective handling of domain-specific contexts, and the high computational overhead of complex retrieval tasks persist. These limitations constrain the broader applicability of RAG systems, particularly in diverse and dynamic real-world environments. The future research directions outlined in this paper—ranging from improving retrieval mechanisms to enhancing context management and ensuring scalability—will serve as a critical guide for the next phase of innovation in this space. By addressing these gaps, the next generation of RAG models has the potential to drive more reliable, efficient, and domain-adaptable LLM systems, further pushing the boundaries of what is possible in retrieval-augmented AI applications.

## **REFERENCES**

1. Acharya, A., Murthy, R., Kumar, V., & Sen, J. (2024). NLLB-E5: A Scalable Multilingual Retrieval Model. ArXiv. <https://arxiv.org/abs/2409.05401>
2. Alayrac, J., Donahue, J., Luc, P., Miech, A., Barr, I., Hasson, Y., Lenc, K., Mensch, A., Millican, K., Reynolds, M., Ring, R., Rutherford, E., Cabi, S., Han, T., Gong, Z., Samangooei, S., Monteiro, M., Menick, J., Borgeaud, S.,

- . . . Simonyan, K. (2022). Flamingo: A Visual Language Model for Few-Shot Learning. ArXiv. <https://arxiv.org/abs/2204.14198>
3. Asai, A., Wu, Z., Wang, Y., Sil, A., & Hajishirzi, H. (2023). Self-RAG: Learning to Retrieve, Generate, and Critique through Self-Reflection. ArXiv. <https://arxiv.org/abs/2310.11511>
4. Baevski, A., Zhou, H., Mohamed, A., & Auli, M. (2020). Wav2vec 2.0: A Framework for Self-Supervised Learning of Speech Representations. ArXiv. <https://arxiv.org/abs/2006.11477>
5. Bertasius, G., Wang, H., & Torresani, L. (2021). Is Space-Time Attention All You Need for Video Understanding? ArXiv. <https://arxiv.org/abs/2102.05095>
6. Binns, R. (2018). Fairness in machine learning: Lessons from political philosophy. Proceedings of the 2018 Conference on Fairness, Accountability, and Transparency (pp. 149-159).
7. Borgeaud, S., Mensch, A., Hoffmann, J., Cai, T., Rutherford, E., Millican, K., Driessche, G. V., Lespiau, J., Damoc, B., Clark, A., Casas, D. D., Guy, A., Menick, J., Ring, R., Hennigan, T., Huang, S., Maggiore, L., Jones, C., Cassirer, A., . . . Sifre, L. (2021). Improving language models by retrieving from trillions of tokens. ArXiv. [/abs/2112.04426](https://arxiv.org/abs/2112.04426)
8. Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., Agarwal, S., Krueger, G., Henighan, T., Child, R., Ramesh, A., Ziegler, D. M., Wu, J., Winter, C., Hesse, C., . . . Amodei, D. (2020). Language Models are Few-Shot Learners. ArXiv. <https://arxiv.org/abs/2005.14165>
9. Chang, R., & Zhang, J. (2024). CommunityKG-RAG: Leveraging Community Structures in Knowledge Graphs for Advanced Retrieval-Augmented Generation in Fact-Checking. ArXiv. <https://arxiv.org/abs/2408.08535>
10. Chen, D., Fisch, A., Weston, J., & Bordes, A. (2017). Reading Wikipedia to answer open-domain questions. In Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (pp. 1870-1879).
11. Chen, W., Hu, H., Chen, X., Verga, P., & Cohen, W. W. (2022). MuRAG: Multimodal Retrieval-Augmented Generator for Open Question Answering over Images and Text. ArXiv. <https://arxiv.org/abs/2210.02928>
12. Chirkova, N., Rau, D., Déjean, H., Formal, T., Clinchant, S., & Nikoulina, V. (2024). Retrieval-augmented generation in multilingual settings. ArXiv. <https://arxiv.org/abs/2407.01463>
13. Dai, Z., & Callan, J. (2019). Context-Aware Sentence/Passage Term Importance Estimation For First Stage Retrieval. ArXiv. <https://arxiv.org/abs/1910.10687>
14. Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2019). BERT: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (pp. 4171-4186).
15. Devlin, J., Chang, M., Lee, K., & Toutanova, K. (2018). BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. ArXiv. <https://arxiv.org/abs/1810.04805>
16. Gan, C., Yang, D., Hu, B., Zhang, H., Li, S., Liu, Z., Shen, Y., Ju, L., Zhang, Z., Gu, J., Liang, L., & Zhou, J. (2024). Similarity is Not All You Need: Endowing Retrieval Augmented Generation with Multi Layered Thoughts. ArXiv. <https://arxiv.org/abs/2405.19893>
17. Gatt, A., & Krahmer, E. (2018). Survey of the state of the art in natural language generation: Core tasks, applications, and evaluation. Journal of Artificial Intelligence Research, 61, 65-170.
18. Gupta, S., & Ranjan, R. (2024). Evaluation of LLMs Biases Towards Elite Universities: A Persona-Based Exploration. ArXiv. <https://arxiv.org/abs/2407.12801>
19. Gupta, S., Ranjan, R., & Singh, S. N. (2024). Comprehensive Study on Sentiment Analysis: From Rule-based to modern LLM based system. ArXiv. <https://arxiv.org/abs/2409.09989>
20. Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., Küttler, H., Lewis, M., Yih, W., Rocktäschel, T., Riedel, S., & Kiela, D. (2020). Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. ArXiv. <https://arxiv.org/abs/2005.11401>
21. Guu, K., Lee, K., Tung, Z., Pasupat, P., & Chang, M. (2020). REALM: Retrieval-augmented language model pre-training. In Proceedings of the 37th International Conference on Machine Learning (pp. 3929-3938).
22. Han, S., Pool, J., Tran, J., & Dally, W. J. (2015). Learning both weights and connections for efficient neural network. In Advances in Neural Information Processing Systems (pp. 1135-1143).
23. Izacard, G., & Grave, E. (2021). Leveraging passage retrieval with generative models for open domain question answering. In Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume (pp. 874-880).



24. Ji, Z., Lee, N., Frieske, R., Yu, T., Su, D., Xu, Y., Ishii, E., Bang, Y., Chen, D., Dai, W., Chan, H. S., Madotto, A., & Fung, P. (2022). Survey of Hallucination in Natural Language Generation. ArXiv. <https://doi.org/10.1145/3571730>
25. Kalra, R., Wu, Z., Gulley, A., Hilliard, A., Guan, X., Koshiyama, A., & Treleaven, P. (2024). HyPA-RAG: A Hybrid Parameter Adaptive Retrieval-Augmented Generation System for AI Legal and Policy Applications. ArXiv. <https://doi.org/10.18653/v1/2024.customnlp4u-1.18>
26. Karpukhin, V., Oguz, B., Min, S., & Yih, W. (2020). Dense passage retrieval for open-domain question answering. arXiv preprint. <https://arxiv.org/abs/2004.04906>
27. Karpukhin, V., Oguz, B., Min, S., Lewis, P., Wu, L., Edunov, S., Chen, D. & Yih, W. T. (2020). Dense passage retrieval for open-domain question answering. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP) (pp. 6769-6781).
28. Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., ... & Riedel, S. (2020). Retrieval-augmented generation for knowledge-intensive NLP tasks. In Proceedings of the 34th International Conference on Neural Information Processing System ( pp. 9459-9474).
29. Li, C., Liu, Z., Xiao, S., & Shao, Y. (2023). Making Large Language Models A Better Foundation For Dense Retrieval. ArXiv. <https://arxiv.org/abs/2312.15503>
30. Wang, T., Li, F., Zhu, L., Li, J., Zhang, Z., & Shen, H. T. (2023). Cross-Modal Retrieval: A Systematic Review of Methods and Future Directions. ArXiv. <https://arxiv.org/abs/2308.14263>
31. Li, S., Shang, H., Wei, D., Guo, J., Li, Z., He, X., Zhang, M., & Yang, H. (2024). LA-RAG:Enhancing LLM-based ASR Accuracy with Retrieval-Augmented Generation. ArXiv. <https://arxiv.org/abs/2409.08597>
32. Li, S., Park, S., Lee, I., & Bastani, O. (2023). TRAQ: Trustworthy Retrieval Augmented Question Answering via Conformal Prediction. ArXiv. <https://arxiv.org/abs/2307.04642>
33. Li, Z., Li, C., Zhang, M., Mei, Q., & Bendersky, M. (2024). Retrieval Augmented Generation or Long-Context LLMs? A Comprehensive Study and Hybrid Approach. ArXiv. <https://arxiv.org/abs/2407.16833>
34. Liu, Z., Wang, H., Niu, Z., Wu, H., Che, W., & Liu, T. (2020). Towards Conversational Recommendation over Multi-Type Dialogs. ArXiv. <https://arxiv.org/abs/2005.03954>
35. Mallen, A., Asai, A., Zhong, V., Das, R., Khashabi, D., & Hajishirzi, H. (2022). When Not to Trust Language Models: Investigating Effectiveness of Parametric and Non-Parametric Memories. ArXiv. <https://arxiv.org/abs/2212.10511>
36. Mombaerts, L., Ding, T., Banerjee, A., Felice, F., Taws, J., & Borogovac, T. (2024). Meta Knowledge for Retrieval Augmented Large Language Models. ArXiv. <https://arxiv.org/abs/2408.09017>
37. Nguyen, X., Pandit, S., Purushwalkam, S., Xu, A., Chen, H., Ming, Y., Ke, Z., Savarese, S., Xong, C., & Joty, S. (2024). SFR-RAG: Towards Contextually Faithful LLMs. ArXiv. <https://arxiv.org/abs/2409.09916>
38. Niu, C., Wu, Y., Zhu, J., Xu, S., Shum, K., Zhong, R., Song, J., & Zhang, T. (2023). RAGTruth: A Hallucination Corpus for Developing Trustworthy Retrieval-Augmented Language Models. ArXiv. <https://arxiv.org/abs/2401.00396>
39. Qian, H., Zhang, P., Liu, Z., Mao, K., & Dou, Z. (2024). MemoRAG: Moving towards Next-Gen RAG Via Memory-Inspired Knowledge Discovery. ArXiv. <https://arxiv.org/abs/2409.05591>
40. Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., & Sutskever, I. (2019). Language models are unsupervised multitask learners. OpenAI Blog, 1(8), 9.
41. Raffel, C., Shazeer, N., Roberts, A., Lee, K., Narang, S., Matena, M., Zhou, Y., Li, W., & Liu, P. J. (2019). Exploring the Limits of Transfer Learning with a Unified Text-to-Text Transformer. ArXiv. <https://arxiv.org/abs/1910.10683>
42. Ranade, P., & Joshi, A. (2023). FABULA: Intelligence Report Generation Using Retrieval-Augmented Narrative Construction. ArXiv. <https://doi.org/10.1145/3625007.3627505>
43. Ranjan, R., Gupta, S., & Singh, S. N. (2024). A Comprehensive Survey of Bias in LLMs: Current Landscape and Future Directions. ArXiv. <https://arxiv.org/abs/2409.16430>
44. Ravuru, C., Sakhinana, S. S., & Runkana, V. (2024). Agentic Retrieval-Augmented Generation for Time Series Analysis. ArXiv. <https://arxiv.org/abs/2408.14484>
45. Robertson, S.G., & Zaragoza, H. (2009). The Probabilistic Relevance Framework: BM25 and Beyond, Foundations and Trends in Information Retrieval, 3(4), pp. 333-389.
46. Roller, S., Dinan, E., Goyal, N., Ju, D., Williamson, M., Liu, Y., Xu, J., Ott, M., Shuster, K., Smith, E. M., Boureau, Y., & Weston, J. (2020). Recipes for building an open-domain chatbot. ArXiv. <https://arxiv.org/abs/2004.13637>

47. Salton, G., Wong, A., & Yang, C. S. (1975). A vector space model for automatic indexing. *Communications of the ACM*, 18(11), 613-620.
48. Sanh, V., Debut, L., Chaumond, J., & Wolf, T. (2019). DistilBERT, a distilled version of BERT: Smaller, faster, cheaper and lighter. *ArXiv*. <https://arxiv.org/abs/1910.01108>
49. Sarthi, P., Abdullah, S., Tuli, A., Khanna, S., Goldie, A., & Manning, C. D. (2024). RAPTOR: Recursive Abstractive Processing for Tree-Organized Retrieval. *ArXiv*. <https://arxiv.org/abs/2401.18059>
50. Shi, W., Min, S., Yasunaga, M., Seo, M., James, R., Lewis, M., Zettlemoyer, L., & Yih, W. (2023). REPLUG: Retrieval-Augmented Black-Box Language Models. *ArXiv*. <https://arxiv.org/abs/2301.12652>
51. Shrestha, R., Zou, Y., Chen, Q., Li, Z., Xie, Y., & Deng, S. (2024). FairRAG: Fair Human Generation via Fair Retrieval Augmentation. *ArXiv*. <https://arxiv.org/abs/2403.19964>
52. Sutskever, I., Vinyals, O., & Le, Q. V. (2014). Sequence to sequence learning with neural networks. In *Advances in Neural Information Processing Systems* (pp. 3104-3112).
53. Thakur, N., Bonifacio, L., Zhang, X., Ogundepo, O., Kamalloo, E., Li, X., Liu, Q., Chen, B., Rezagholizadeh, M., & Lin, J. (2023). NoMIRACL: Knowing When You Don't Know for Robust Multilingual Retrieval-Augmented Generation. *ArXiv*. <https://arxiv.org/abs/2312.11361>
54. Thakur, N., Reimers, N., Ruckl'e, A., Srivastava, A., & Gurevych, I. (2021). BEIR: A Heterogenous Benchmark for Zero-shot Evaluation of Information Retrieval Models. *ArXiv*, abs/2104.08663.
55. Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., & Polosukhin, I. (2017). Attention is all you need. In *Advances in Neural Information Processing Systems* (pp. 5998-6008).
56. Wang, X., Wang, Z., Gao, X., Zhang, F., Wu, Y., Xu, Z., Shi, T., Wang, Z., Li, S., Qian, Q., Yin, R., Lv, C., Zheng, X., & Huang, X. (2024). Searching for Best Practices in Retrieval-Augmented Generation. *ArXiv*. <https://arxiv.org/abs/2407.01219>
57. Wang, Z., Araki, J., Jiang, Z., Parvez, M. R., & Neubig, G. (2023). Learning to Filter Context for Retrieval-Augmented Generation. *ArXiv*. <https://arxiv.org/abs/2311.08377>
58. Xia, P., Zhu, K., Li, H., Zhu, H., Li, Y., Li, G., Zhang, L., & Yao, H. (2024). RULE: Reliable Multimodal RAG for Factuality in Medical Vision Language Models. *ArXiv*. <https://arxiv.org/abs/2407.05131>
59. Xie, S., Sun, C., Huang, J., Tu, Z., & Murphy, K. (2017). Rethinking Spatiotemporal Feature Learning: Speed-Accuracy Trade-offs in Video Classification. *ArXiv*. <https://arxiv.org/abs/1712.04851>
60. Xiong, L., Xiong, C., Li, Y., Tang, K., Liu, J., Bennett, P., Ahmed, J., & Overwijk, A. (2020). Approximate Nearest Neighbor Negative Contrastive Learning for Dense Text Retrieval. *ArXiv*. <https://arxiv.org/abs/2007.00808>
61. Yasunaga, M., Aghajanyan, A., Shi, W., James, R., Leskovec, J., Liang, P., Lewis, M., Zettlemoyer, L., & Yih, W. (2022). Retrieval-Augmented Multimodal Language Modeling. *ArXiv*. <https://arxiv.org/abs/2211.12561>
62. Zhang, T., Patil, S. G., Jain, N., Shen, S., Zaharia, M., Stoica, I., & Gonzalez, J. E. (2024). RAFT: Adapting Language Model to Domain Specific RAG. *ArXiv*. <https://arxiv.org/abs/2403.10131>
63. Zhu, Y., Ren, C., Xie, S., Liu, S., Ji, H., Wang, Z., Sun, T., He, L., Li, Z., Zhu, X., & Pan, C. (2024). REALM: RAG-Driven Enhancement of Multimodal Electronic Health Records Analysis via Large Language Models. *ArXiv*. <https://arxiv.org/abs/2402.07016>



INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  [ijirset@gmail.com](mailto:ijirset@gmail.com)



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details