



(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



### Impact Factor: 8.699

### Volume 14, Issue 5, May 2025

⊕ www.ijirset.com 🖂 ijirset@gmail.com 🖄 +91-9940572462 🕓 +91 63819 07438





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

#### Volume 14, Issue 5, May 2025

|DOI: 10.15680/IJIRSET.2025.1405136|

# **Comparison of Steel Structure with Rigid and Semi Rigid Joints using Software Analysis Tool**

Pushpendra Sinha, Shiva Verma, Akhand Pratap Singh, Parmeshwar Sahu

M.Tech Scholar, Department of Civil Engineering, Shri Rawatpura Sarkar University, Raipur, India Assistant Professor, Department of Civil Engineering, Shri Rawatpura Sarkar University, Raipur, India Assistant Professor, Department of Civil Engineering, Shri Rawatpura Sarkar University, Raipur, India Assistant Professor, Department of Civil Engineering, Shri Rawatpura Sarkar University, Raipur, India

**ABSTRACT:** In steel constructions, the connection between the beam and column is generally designed as an instantaneous and solid connection. However, in the actual conditions, the structure operated between these two conditions, leading to a semi-rigid condition between the rigid and stacked joints between the stiffness level and the stacked level. This study achieves the effect of semi-rigid connections on multi-storey multibay frames. In this study, we introduce the effects of static and dynamic stress on G+12 history steel structures with Laurel voltage lengths of 4 m, 6 m, 8 m and 8 m. The structure is analyzed under two different conditions of partial release of semi-rigid connections. In this study, it comes from 0.5 and 0.75. Analysis is available in stores. History and history drifts are preserved from nonlinear analysis. The overall performance of the structure from the analysis shows more story shifts and story drifts compared to the semi rigid joints. To overcome the outcome, shutoff systems are introduced elsewhere around the structure. This gorge frame structure consists of exclusion and oblique conclusions. Again, comparative analyses of facilities should be performed via these 3-bay span width lengths. The semi-rigid frame structure has been found to work very well compared to the flexible structure.

KEYWORDS: Multi-Storey Multibay Frames, Semirigid Joints, Rigid, Stacked, Comparative Analyses.

#### **I. INTRODUCTION**

Steel jet connections may also be required for strange connections, section columns, and associations with segment networks. These are classified as extraordinary connections and are handled individually. There are different types of steel jet connections. SteelonCall is currently giving a considerable number of steel jet connections sorts in the next section.

#### **1.1 Breaked Framework Connections**

Connections from the pile are planned regularly towards the edge of the beam. While the connection is established, you need to be convinced of the quality of the bar, the type, and the quality of the basic materials. In any case, the minimum length of the connection angle must be half the clear web depth. This measurement is specified to ensure proper strength and solidity. Screwed frame connections come in a variety of standard sizes for the skills given in the cord

#### 1.2 Screw-in sit-in connections

- There are two types of threaded seat connections:
- Stiffened connections and Unstiffened connections

If the reaction is huge for the staff finishing, it is stipulated at this point. However, if there is no connection type without stapes, there will be a break against the force. The seat connection should be practical and provide faster during an erection. Apart from that, they do not need some major steel details. These connections are environmentally friendly as the structure of this connection can be disassembled and used in a variety of activities.

#### **1.3 Welding Frame Connections**

The goal with a welded structure is to ensure that the principle column section compounds are established in the working situation and that the connection is full of quality. To achieve this, a short stub of the soft steel rod segment is sent to the section, but the piece is still fully appreciated for the mode of transport. Connections to the remaining beams





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

#### Volume 14, Issue 5, May 2025

#### |DOI: 10.15680/IJIRSET.2025.1405136|

of the parlor are regularly established with screwed cover plate splices. Note that screwed splices must use pre-installed background analysis.

#### **1.4 Welding Sheet Connection**

This is like a connection to a fixing screw, but is used to fix it more than bolts. Piles of steel bars affect welding abnormally and generate pressure. In this sense, such loads, such as welding connections, should be turned on. Types of welded sheet connections include slippery sheets and cured sheets. The previous one is used for unused loads, but the last one is suitable for huge loads.

#### **1.5 Final Plate Connections**

Adaptable end panel connections include plates mounted on either side of the metal column structure mesh by filling the weld seams. The connection must send vertical shots and enable rod pivot without raising a huge minute. They convey a small, secure connection between the rays and columns on the sides of the edge, or a small contrast to the connection with the elongated rays. Normal adaptable end plates Compounds are incomplete depth or complete occupation and are welded in the structure of a born metal rod. The column at this point will move to the support wave or nearby segment. This type of connection is generally estimated, but there is the inconvenience of a small open house to change location. Although typical wavelengths require steel within narrow boundary points, the pack is used to build elasticity and erectile resistance. Finally, the end panel connections are not suitable for high steel constructions.

#### **1.6 Special Connections**

Simple, Rigid and Semi-rigid Connections This type of connection is used in situations where the impact course of the basic components is not available to use standard connections. For example, the defects at intersections can vary to some extent, and are varied when the columns are focused from the focus of the section. Special connection instances include twisted covered plates, individual web panels, uneven, incoming, editing boards, and Z-type connections.

A simple connection requires that scissors be transferred from columns to segments only without creating surprising minutes. Silent connections are compounds that are not completely wrong in the application. This means there is a rotation limit of 90% or . At the end of the day, you will get full continuity during the connection. Semi-rigid connections have some rotational limit and must be performed at certain minutes along these lines. This means that there are no fine moments transmitted through the joints, nor are they perfect progression as a rigid connection. Steel beam structures consist of connect people of different people, such as segments, beams, and rays. Connections are structural elements used to connect people of different steel structures. Analysis and design of steel structures with ideally rigid and defined radiation conditions under earthquake resistance stress. Analysis and design of steel structures with semi rigid radios is in a state under seismic stress. Compare the responses of rigid bodies, stacks, and semi-rigid framework structures exposed to seismic loads. To investigate parameters such as basic shear, compare the lateral shifts along with the parameters from seismic analysis. Comparison of analysis results for rigid, employee, and semi-layers Conditions related to parameters such as shear force, element axial force, upper Story shift, frame weight, and basic scissors.

#### **II. LITERATURE SURVEY**

**M. Ghassemieh and A.R. Bahadori (2015)** objectives to research the seismic overall performance of metal moments taking into consideration the effects of their connection flexibility. The conduct of the frame with cowl plate torque connections and the flexibility of the compounds are as compared with nonlinear static push bars and incremental dynamic analysis. In all models, the p-delta impact was included inside the evaluation alongside material and geometric nonlinearity. The consequences of the pushover evaluation showed that the preliminary stiffness and final numbers of cover plate frames with absolutely rigid connections exceed the counterpart framework that takes into consideration connection flexibility. Moreover, the flexibility of connections inside the operation of the structural framework has expanded the flexibility of the structure. Moreover, thinking about the power of connections, the maximum inter-historical glide within the frame reports a higher cost than a body with a completely rigid connection. And subsequently, the implementation of incremental dynamic analysis can purpose great variations among the two seven-storey frames in phrases of performance stage, and overlooking the ability of the beam can lead to erroneous conclusions.





[www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

#### Volume 14, Issue 5, May 2025

#### |DOI: 10.15680/IJIRSET.2025.1405136|

**Harsh Rana et al. (2020)** research paper delivered the consequences of static and dynamic stresses on steel structures of 4 m, 6 m, and 8 m long. The shape is analyzed underneath specific situations of semi rigid connection partial emission, derived through constant coefficients of 0.5 and zero. Seventy five (via AISC) in this look at. analysis become to be had at stores software program-Staad.pro. tale displacement and postponement had been preserved from nonlinear evaluation. Standard overall performance of the structure from the analysis, half of-tension connections display greater tales compared to greater story shifts and tale drifts. to triumph over the outcome, the distribution gadget become delivered at one of a kind locations around the structure. This bracket body shape includes x exclusion and diagonal distribution. Comparative analyses have been done on STAAD. seasoned thru those 3-bake clamp lengths. Quite, the semi-rigid frame shape proved to work thoroughly as compared to insufficient body systems. The results show that lateral shifts of semi-rigid connections require extra than the period of the inflexible connection and bay. Multiplied flexibility of connections thru the fixed coefficient "zero.75" than in comparison to the fixed coefficient 0.5 consequences lower. As the range increases the discovered lateral shift to triumph over this impact, a anxiety system is used to improve lateral structural stability. The effects of the X-hearth frame analysis display higher lateral stability than the diagonal body. In high-rise structures, corners, and complete scope General seismic evaluation of frames allows for slight lateral shifts and drifts compared to the middle grip framework.

Yang Rongqian and Zhou Xuejun (2020) research paper, semi-integer-rated metal frames had been designed and examined and examined for faults underneath inverse annular hundreds. The hysteric curve, storage capability, electricity dissipation ability, ductility performance, and stiffness degradation have been examined in detail. next, we as compared performance with an analysis of the blessings and drawbacks of the 2 frames. Exams display that plastic deformation and harm are specifically focused in parentheses, with the connection among the column and semi-stress displaying little plastic deformation. The specimen exceeded the elastic degree, elastic plastic degree, and fault degrees under take a look at. Results showed that rehearsals the usage of Chevron clamps had better seismic performance. The shape shows the overall characteristics of duktile's failure. The metallic frame and pattern braces are cooperative collectively, as there are seismic fixation lines within the shape. creation with chevron clips has notable storage capacity, high lateral stiffness, reliable lateral resistance overall performance, and robust electricity loss ability. In this example, the shape of the X Shaped clip due to early fractures of move-connections results in a dramatic reduction in storage capacity, resulting in a less efficient fabric use.

**Bishal Koirala and Dr. Rajan Suwal (2020)** aimed to decide the impact of semi-dizzy conduct of beam column connections at some stage in the reaction of framework systems. Immediately relationships act as a degree of a half-degree degree of connection. The non-folding link factors of SAP2000 have been used to model the instant rotation relationships of numerous connections in metallic systems. Based on this second rotational relationship, the resistance body became modeled to account for strict connections and semi-wall connections. Rigid and various styles of semi-inflexible connections also evaluate the response parameters, including lateral shifts and bending moments. The effect of the presence of half the relationship at the seismic performance of the frame turned into investigated. We signed the horizontal shift in connection stiffness for semi-inflexible connections. Redistribution of moments to EPC, reinforcement marketers, approximately the identical intermediate span and span moments with kind of the identical intermediate span and end span moments have been 30% greater than the inflexible compounds, and consequently resisted the body. The ductility of the shape will increase with the lower in connection stiffness, for that reason growing the seismic performance of the shape.

#### **III. METHODOLOGY**

Step 1- The first step in general is to review research papers from different authors or to identify the problem statement and the remedies adopted from different researchers. The review of the papers were summarized in section two.

Step 2- The grid system are defined from the predefined template or even provides the option to customize it as per the stature of the desired structure. The model is designed as per model initialization to define the unit and IS codes.

Step 3- the grip matrix for the structure is designed as per the quick template available in analytical application ETABS. The grid is defined in X and Y direction whereas the storey height is defined in Z direction.





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

#### Volume 14, Issue 5, May 2025

#### |DOI: 10.15680/IJIRSET.2025.1405136|

Step 4- This step involves the properties of material as here in this case, a steel structure is considered and the properties of steel is defined.

Step 5- Defining section properties for the steel frame and steel slab where the sections are defined for steel beams and columns.

Step 6 Defining properties for Rigid Joints and Semi RIgid Joints for the steel structure.

Step 7 Defining loading conditions and load patterns assigned to the frame of the structure.

Step 8- Analysing the model on parameters of displacement, shear force, bending moment and Joint Analysis.

Step 9- This last step is to present the comparative analysis of steel structure with two different joints namely rigid and semi rigid joints. The results will be tabulated and presented.

#### Structural type Commercial Total stories 12(G+11)Total height of building 42 m Size of column ISWB600@145.1kg/m Size of beam ISWB300 @48.1kg/m, ISMB400 @61.6kg/m and ISMB600 @ 122.6 kg/m Thickness of slab 150 mm Floor height 3.5 m Grade of slab concrete M25 Live load 4 kN/m2 Dead load 1.5 kN/m2 Seismic zone V Medium Soil Type Importance factor 1 Response reduction factor 5 Damping ratio 5%

#### Table3.1 Parameters of developed steel frame models

#### **IV. RESULTS & DISCUSSION**

#### 4.1 Maximum Displacement

Maximum Lateral Displacement			
Storey Number	Rigid Joints	Semi Rigid Joints	
Storey0	0.09549	0.1509	
Storey1	0.09567	0.292	
Storey2	0.09581	0.4046	
Storey3	0.09591	0.472	





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

#### Volume 14, Issue 5, May 2025

#### |DOI: 10.15680/IJIRSET.2025.1405136|

Storey4	0.09597	0.5154
Storey5	0.096	0.542
Storey6	0.09649	0.5873
Storey7	0.09689	0.612
Storey8	0.09701	0.632
Storey9	0.0976	0.689
Storey10	0.0992	0.717



#### Fig.1. Maximum Displacement

#### 4.2 Shear Force:-

Shear Force in kN			
Storey Number	<b>Rigid Joints</b>	Semi Rigid Joints	
Storey0	11.98	11.02	
Storey1	12.34	11.41	
Storey2	12.96	11.77	
Storey3	13.55	12.31	
Storey4	11.03	11.33	
Storey5	10.13	10.24	
Storey6	8.49	8.79	
Storey7	7.99	8.05	
Storey8	6.67	6.75	
Storey9	5.98	6.02	
Storey 10	5.21	5.28	
Storey 11	4.76	4.81	





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

#### Volume 14, Issue 5, May 2025

#### |DOI: 10.15680/IJIRSET.2025.1405136|



#### Fig. 2. Shear Force

#### V. CONCLUSION

We tried to evaluate the behavior of the rigid and semi-rigid connection. The duration of the layer, storey drift, and g+11 structural structures were evaluated in terms of rigid and semi-rigid connection. Based on the results of the analysis, the following conclusions can be drawn: text region.

- Semi-Rigid connections show significantly larger basic scissors that contribute to improved step-number performance, 16% shift. Semi rigid connections are better replacement for hinged and fixed connections which are down by 2% and 16% respectively.
- It shows the collapse points of different models, indicating that the collapse points of the half star structure are 2% higher than the swirling structure at end more than 20% higher than the solid structue.
- From the hinge connection position, it is considered higher than the fixed and Semi Rigid connection positions, but since the load is in the direction of the collapse point, halfthin connections exhibit a more basic displacement rate than lowered drainage and fixed connections
- It shows important readings related to basic scissors and shifts. The basic scissors for the solid frame are the best, followed by half the intense model frame and saved frame.
- The next observation means that from modal analysis the period of half stiffness increases by 36%. Good models reduce by 34%, while fixed models are very small.

#### REFERENCES

- 1. M. Ghassemieh and A.R. Bahadori, [Seismic Evaluation of a Steel Moment Frame with Cover Plate Connection Considering Flexibility by Component Method], Advances in Structure Engineering and Mechanics, August 2015.
- Dr B. A. Shah, [Seismic Performance Evaluation of RC Frames with Semirigid Joints using Storey Drift as a Criterion], International Journal of Engineering Research & Technology (IJERT), ISSN: 2278-0181, Vol. 5 Issue 05, May-2016.
- 3. Iman Faridmehr, Mahmood Md. Tahir, Tom Lahmer, and Mohd Hanim Osman, [Seismic Performance of Steel Frames with Semirigid Connections], Hindawi Journal of Engineering Volume 2017, Article ID 5284247, 10 pages.
- 4. Moghadam, H.E. Estekanchi, and M. Yekrangnia, [Evaluation of PR steel frame connection with torsional plate and its optimal placement], Scientia Iranica A (2018) 25(3), 1025{1038.
- Hardik M Paghadal, Dr. Darshana R. Bhatt and Dr. Snehal V. Mevada, [Ductility evaluation of steel frames using semi-rigid connections, Journal of Emerging Technologies and Innovative Research (JETIR), November 2018, Volume 5, Issue 11.





www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

#### Volume 14, Issue 5, May 2025

#### |DOI: 10.15680/IJIRSET.2025.1405136|

- Neema B.R., Shreyas S.C. and Dr. Chidananda G, [Effect Of Connection Rigidity On Seismic Performance Of Multi Storey Steel Frames], International Research Journal of Engineering and Technology (IRJET), Volume: 05 Issue: 07 | July 2018.
- Harsh Rana, Dr. Darshana R. Bhatt and Dr. Snehal V. Mevada, [High Rise Long Span Steel Structure with Semi-Rigid Connection using Bracing System], International Journal of Engineering Research & Technology (IJERT), ISSN: 2278-0181, Vol. 9 Issue 03, March-2020. UdayModha, Preeti Dave, "Image Inpainting-Automatic Detection and Removal of Text From Images", International Journal of Engineering Research and Applications (IJERA), ISSN: 2248-9622 Vol. 2, Issue 2, 2012
- 8. D.Shama and A.kush,'GPS Enabled E Energy Efficient Routing for Manet', International Journal of Computer Networks (IJCN), Vol.3, Issue 3, pp. 159-166, 2011.
- 9. Shilpajain and Sourabhjain,'Energy Efficient Maximum Lifetime Ad-Hoc Routing (EEMLAR)', international Journal of Computer Networks and Wireless Communications, Vol.2, Issue 4, pp. 450-455, 2012.
- 10. Vadivel, R and V. MuraliBhaskaran,'Energy Efficient with Secured Reliable Routing Protocol (EESRRP) for Mobile Ad-Hoc Networks', Procedia Technology 4,pp. 703- 707, 2012.
- Nobuo Ezaki, Marius Bulacu Lambert, Schomaker, "Text Detection from Natural Scene Images: Towards a System for Visually Impaired Persons", Proc. of 17th Int. Conf. on Pattern Recognition (ICPR), IEEE Computer Society, pp. 683-686, vol. II, 2004
- Mr. Rajesh H. Davda1, Mr. Noor Mohammed, "Text Detection, Removal and Region Filling Using Image Inpainting", International Journal of Futuristic Science Engineering and Technology, vol. 1 Issue 2, ISSN 2320 – 4486, 2013
- 13. Uday Modha, Preeti Dave, "Image Inpainting-Automatic Detection and Removal of Text From Images", International Journal of Engineering Research and Applications (IJERA), ISSN: 2248-9622 Vol. 2, Issue 2, 2012.
- 14. Muthukumar S, Dr.Krishnan .N, Pasupathi.P, Deepa. S, "Analysis of Image Inpainting Techniques with Exemplar, Poisson, Successive Elimination and 8 Pixel Neighborhood Methods", International Journal of Computer Applications (0975 8887), Volume 9, No.11, 2010









# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com