



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 14, Issue 5, May 2025

Software Analysis of Low Carbon Emission Building using ETABS

Dipti Kurre, Shiva Verma, Akhand Pratap Singh, Parmeshwar Sahu

M.Tech Scholar, Department of Civil Engineering, Shri Rawatpura Sarkar University, Raipur, India

Assistant Professor, Department of Civil Engineering, Shri Rawatpura Sarkar University, Raipur, India

Assistant Professor, Department of Civil Engineering, Shri Rawatpura Sarkar University, Raipur, India

Assistant Professor, Department of Civil Engineering, Shri Rawatpura Sarkar University, Raipur, India

ABSTRACT: The current world applies to supportable practices from a wide range of backgrounds, and the development industry is not unique. The idea of sustainability in the development industry has made incredible advances, but requires new turns of events and creation. One of the most important aspects of sustainable construction is the concept of green buildings. It is a type of building that is environmentally friendly and resource efficient. There are several systems for evaluating and evaluating green buildings. India has three main valuation systems, all of which make up very large or small commercial buildings. This Exploration Centre attempts to stimulate private structures that are not present in the structure of the rated frame Svagriha (a basic flexible green rating for biological space assessment) to convert normal structures into green structures in the middle. The structural state was examined and a green structural idea was proposed. Additional work and basic commitment exams of framework conditions have also been completed to demonstrate the efficient part of the conversion to green structures. Green structure on regulatory levels - many suggestions for improving the evaluation framework. Minimizing the energy consumption of buildings has become an important goal in architecture and urban planning in recent years. For all climate zones, rules have been created that aim to reduce the expanding solar openness to cool environment structures and the solar-based openness of warm environment structures. This approach typically meets seasonal arrangements in the most extreme climates. If you don't remember that urban temperatures in the 25° range of winter drop under warm, arid boundaries and the temperatures in local urban communities at 48° exceed the limits of warm summer comfort. This study presented a comparative analysis of the conventional and sustainable structures of 17 uplifts taking into account similar load conditions developed at the facility. Comparative analyses were performed on the Storey Moment, Storey Displacement, Storey Drift, and Storey Shear parameters. In this study, spare parts of the material were planned. Member. Establishment tools are considered in this research work for modelling and dynamic analysis.

KEYWORDS: Green Buildings, Sustainability, Energy Consumption, Evaluation Framework, Structural Analysis.

I. INTRODUCTION

India is an exponentially expanding nation. The construction of green buildings is a result of rapid industrialization, population growth, infrastructure development, and the destruction of natural resources. The eco-friendly structure is a well-thought-out and efficient design that considers the environment throughout its entire life cycle. The green structure is also recognized for its meticulous upkeep and exceptional execution. Warm comfort emphasizes the traditional private structure of India. It is well-known for employing regular and uninvolved techniques to create a pleasant inner atmosphere. The most suitable response is the most effective solution to ensure a strong energy and stable internal climate. This is crucial for the jungle's structure, which relies on mechanical framework conditions with high energy consumption to maintain a comfortable interior temperature. People are compelled to depend on these framework conditions, as most of the structure is designed without specific methods to regulate the internal climate. In most cases, the inability to provide the expected warm conditions resulted in distress, chronic illness, and decreased efficiency. In the future, we must evaluate the warm conditions of the internal conditions to gain more knowledge and continue our exploration of the separated plans. Water is a vital and limited resource. Covering over 70% of the earth's surface, water is vital for sustaining life and plays a crucial role in preserving food, human health, and the natural environment. Access to clean drinking water is diminishing in many of the world's most densely populated areas. This responsibility will assist in minimizing waste, promoting reuse, or increasing the appeal of reuse. In general, we need to be more

efficient in our water usage. The act of washing has a significant impact on the environment and can result in challenging issues. Some garbage is eventually descending, but not all. Methane gas can emit a distinct odor and contribute to the creation of hazardous substances, thereby intensifying the potential risks associated with kindergartens. When words are not being produced as expected, especially liquids and strong waste from families and communities, they can become a serious threat to wells and lead to the spread of infectious diseases. The waste left unattended around it shows flies, rodents, and various animals that can spread diseases. Puddles typically liquefy and emit an unpleasant odor. This led to unsanitary conditions and subsequently an increase in the illness. Plastic waste is another reason for its fragility. To reduce the excessive and potent waste generated, it is necessary to eliminate a specific preventive measure.

1.1 Concept of Green Building:- The construction industry has both detrimental and beneficial impacts on the environment, business, and society. According to estimates, buildings account for more than 30% of their energy consumption, which in turn utilizes 40% of their resources, while simultaneously producing 40% of their waste and 35% of their harmful greenhouse gases (mane 2017). Green structures are the utilization of a process that can naturally transition from location to planning, development, activity, maintenance, redesign, and demolition throughout the entire lifecycle. This training enhances and complements conventional structural obstacles in economy, profits, strength, and comfort. The green structure is also known as a manageable or elite execution building (choudhary, 2018). There are numerous features that can contribute to the creation of an environmentally friendly structure. These include the efficient utilization of energy, water, and various resources, as well as the adoption of sustainable electricity, such as solar energy and waste management, and the implementation of enhanced reuse. Tenants expressed their personal satisfaction with the plans, development, and activities that enable them to adapt to the changing climate.

1. 3 Green Building Rating System:- Rating systems are a form of building certification that evaluates or rewards the degree of compliance or performance with specific environmental objectives and criteria. Green structure rating and certificate frameworks require an incorporated plan interaction to make projects that are ecologically mindful and asset effective all through a structure's life-cycle: from siting to plan, development, activity, upkeep, redesign, and demolition. (vierra, 2019). There are several rating systems in existence, with the primary four being LEED, Green Globes, Green Star, and Breeam idea of eco-friendly construction in India.

The development of green structure in india started in the year 2001, with the foundation of igbc (indian green structure chamber) by confederation of indian enterprises (cii) in participation with usgbc and green structure gathering of the world (mane, 2017). As per igbc as on third November 2021 a bigger number of than 7,002 green structures projects concocting an impression of over 7. 97 billion sq. Ft are enrolled with the indian green structure chamber (igbc), out of which 2,344 green structure projects are guaranteed and completely utilitarian in india. In india there are 3 principal green structure rating frameworks. They are leed (authority in energy and ecological plan), igbc green rating and griha (green rating for coordinated natural surroundings evaluation). The problem with this extensive collection of frameworks is that none of them accurately represent the existing private structures. There is no current agreement in these frameworks to evaluate evaluations to change current private structures below 2500m² to green structures.

1. 4 seismic analysis

Earthquakes are a natural occurrence caused by the shifting of tectonic plates. Due to the unpredictable nature of seismic tremor, it is crucial to thoroughly evaluate the load of the stem to determine the appropriate construction route. Quake embraces the powerful parts of the testing and planning design. Seismic inspections are part of the underlying test and include estimation of tremor (or non-construction) structures. A survey is an interaction to determine the behavior of the structure under a specified loading mixture. Equivalent static lateral force method - The main assumption of this method is that the lateral output of the actual stress corresponds. In this method, the fundamental shear, the overall horizontal force on a structure, is calculated based on the structure mass and its fundamental vibration period. The overall design of the lateral power or design of the seismic-based shear (VB) along the main direction must be determined with the help of the following equation:-

$$VB = A_h W$$

Where,

A_h = Design horizontal acceleration spectrum using fundamental natural period T_a ,

W = seismic weight of all the Building The Design horizontal Seismic Coefficient A_h for a Structure will be

evaluated by expression:

$$A_h = (ZIS_a)/(2Rg)$$

Z = Zone Factor,

I = Importance Factor

S_a/g = Average response Spectrum Coefficient using soil type and fundamental time period

R = Response reduction factor

The Value of W, Z, I, S_a/g , and R are dependent on the IS 1893 (Part 1): 2016

Connect to structures to reduce dynamic responses of structures. Works based on the principle that the damper frequency is adjusted to a specific structural frequency. Energy is derived. This is the inertia of the damper that affects the structure.

II. LITERATURE SURVEY

Wacale Yogesh Namdev et.al (2022) When planning structure, maximum shear power, rotational portion, most extreme story deposit, implementation of seismic forces, solidity of the story, story float, all forces with various reactions, the results stated that the highest distance level expands from the first story to the last story. The edges pushed that structures in the stack, such as dead stress, living stress, wind loads, earthquake stress, and more are protected. The partial sides (shafts, sections, chunks, balances) are modified by detailing the heap, and the details of the CSI used for it are Min. Beams, pieces, width and balance of the same segment.

Xiao-guang Zhao and Chun-Ping Gao (2022) research work explained the importance of energy-saving plan for the envelope curve, and lighting energy-saving plan. Interactions between investigating energy capabilities from an attribute and BIM perspective were appropriately proposed. Finally, energy conservation results were given to green structures from the perspective of BIM, and the model showed that the energy planning strategy for green structures proposed in the research work has excellent validity and feasibility from the perspective of BIM. The green structure energy saving plan for BIM innovation proposed in this paper not only allows references from the lower inspection of BIM innovation to the top, but also provides special help to a wide range of applications in the field of green structures.

The research paper on **lakshmi r (2021)** research paper attempts to mandate small private structures on the structure of one of the evaluation frames Svagriha (flexible and appropriate green assessments for flexible and suitable habitat assessment). The structural state was examined and a green structural idea was proposed. Additional work and basic cost inspections of framework conditions were also completed to demonstrate the efficient portion of the green structure change. The study showed that limited range of changes to green structures were certainly wise and conceivable. In any case, there is no accurate evaluation framework that can mandate such conversions. Concentrates can also be achieved in other such structures, despite the fact that it is a specific case. It will be further improved if further inspection of the topic is needed and rules require the creation of evaluation frames.

Johnson and Aswathy Soman (2021) exploration paper tracked the G+9 RCC structure and G+4 wood structure as seismic similarities in structures. The G+ 4 wood models, RCC wood model and steel wood model take into account unique stacking analysis. The structure has been demonstrated in establishment programming using a variety of material properties. Results expressed that due to the high mass of the RCC outline design, the time range of the RCC outline structure is greater as the analysed wood structure. The basic shear seen in the RCC circulation structure was in contrast to the reduced structure of steel. The basic scissors in the base values of RCC and wood outline structures were 1361.28 kN and 349.9 kN. Due to the more prominent thicker cross-segment of the underlying part, seismic strains in the RCC cutting structure are more than edge structures of steel. Therefore, the RCC and timber integration factors were assumed to plan a protected decision in the seismic zone for a stronger implementation of construction.

III. METHODOLOGY

3.1 General

For study purposes, a plan with a 17-storey frame was considered. For linear elastic studies, RC level frames and green buildings were analysed and designed for gravity loading according to lateral loads (seismic loads) according to IS 456:2000 and IS 1893 (part 1):2002 (part 1).

3.2 Steps of Demonstrating and Examination

1. the inquire about papers from distinctive creators were summarized to get it the conduct of associated towers and the inquire about done till date.

- To begin modelling the case study, ETABS supports building regulations in various countries, so the model must first initialize the model based on the definition of display units in metric SI in India region. The steel cord was created according to IS 800:2007 and the concrete structure code was created according to IS 456:2000
- ETABS offers the possibility to model structures with simple options in quick templates that allow you to define grids in X, Y, and Z. In this case, five bays examined in both the X and Y directions at a constant distance of 5 m make the model symmetric. The G+16 story structure is displayed at a typical floor height of 3 m.
- The next step is to define the material properties of concrete and steel. This case study considers the M30 concrete and iron muscle-HySD 500, and its predefined properties are available at the facility. Step 5: Define the section properties of the beam, column. A ray size of 500 x 350 mm, a column size of 500 x 500 mm, and a plate size of 150 mm will be considered in the study.
- Characterizing segment properties for Beam, Column. Bar measure of 500x350mm, Column measure of 500x500mm and Chunk estimate of 150 mm is considered within the think about.
- Doling out Settled Bolster at foot of the structure in X, Y and Z heading in both the considered cases.
- Define loads for dead loads, living loads, and load cases for seismic analysis in x and y directions.
- Defining Seismic Loading as per IS 1893: 2016 Part I.
- Running model tests for both cases of ETABS
- Analysis of structures on dead stress, voltage analysis, and shifts.




Fig 3.1 Seismic Loading




Fig3.2Load Case Data




Fig 3.3 Seismic Loading




Fig 3.4 Load Case Data

IV. PROBLEM STATEMENT

4.1 General

Research examined that the behavior of the naked framework is commonly referred to as traditional structures, and that green sustainable high-pile structures were examined under seismic stress. An analysis of the 17-storey building was conducted. The buildings in Earthquake Zone III were assumed to take into account soft soil. Building analysis was carried out using the facility using seismic coefficient approach. Seismic responses in various buildings were compared with strong drift and average shifts.

4.2 Building Geometry

Modelling is done with ETABS 2018 software. Reaction reduction coefficients are considered 5 in a specific RC moment resistance frame, as shown in 1893 (Part 1): 2002, and analysis of the response spectra is performed with a decay of 5%. Basic journals, beams, columns, and panels are provided as references. Support conditions have been determined and the important factor specified is 1.

Table 4.1 Building Description

Building Description	
Plan dimension	25m x 25m
Number of storey	17
Typical Storey height	3m
Bottom Storey Height	3m
Building Height	63m
Number of Grid in X Direction	5
Number of Grid in Y Direction	5
Spacing of Grids in X direction	5m
Spacing of Grids in Y direction	5m
Beam Size	500x350mm
Column Size	500x500mm
Slab Thickness	125mm
Panel Wall Thickness	100mm
Soil Profile Type	Soft

Table 4.2 Properties of Concrete

Properties of Concrete	
Grade of Concrete	G+30
Directional Symmetry Type	Isotropic
Weight per Unit Volume	24.9926 kN/m ³
Mass per Unit Volume	2548.538 kg/m ³
Modulus of Elasticity, E	27386.13 MPa
Poisson's Ratio, U	0.2
Coefficient of Thermal Expansion, A	0.000013 1/C
Shear Modulus, G	11410.89 MPa

Table 4.3 Properties of Rebar

Table 4.4 Properties of Foam Concrete

Properties of R		Rebar		Properties of Foam		Concrete	
Material Name		HYSD 415		Grade of Concrete		Foam Concrete	
Directional Symmetry Type		Uniaxial		Directional Symmetry Type		Isotropic	
Weight per Unit Volume		76.9729 kN/m ³		Weight per Unit Volume		24.9926 kN/m ³	
Mass per Unit Volume		7849.047 kg/m ³		Mass per Unit Volume		2548.538 kg/m ³	
Modulus of Elasticity, E		200000 MPa		Modulus of Elasticity, E		27386.13 MPa	
Coefficient of Thermal Expansion, A		0.0000117 1/C		Poisson's Ratio, U		0.2	
Yield strength of distribution bar (fysec)		Fe415		Coefficient of Thermal Expansion, A		0.000013 1/C	
Yield strength of main bar (fymain)		Fe415		Shear Modulus, G		11410.89 MPa	


V. EXPERIMENTAL RESULTS

5.1 Storey Moment in kN-m

Table 5.1 Storey Moment in kN-m

Storey Moment in kN-m		
Storey	Bare Frame	Green Sustainable Frame
Storey 17	663.38	554.19
Storey 16	601.83	511.1
Storey 15	555.23	476.21
Storey 14	489.12	436.72
Storey 13	426.04	399.09
Storey 12	388.02	364.54
Storey 11	326.58	319.09
Storey 10	318.38	311.46
Storey 09	310.18	303.88
Storey 08	302.97	296.21
Storey 07	294.77	288.63
Storey 06	286.57	280.06
Storey 05	278.37	272.48
Storey 04	270.71	265.08
Storey 03	262.96	265.23
Storey 02	254.76	249.65

Fig 5.1 Storey Moment in kN-m




Storey 01	246.56	241.08
Base	0	0

5.4 Storey Displacement in mm

Table 5.3 Storey Displacement in mm

Storey Displacement in mm		
Storey	Bare Frame	Green Sustainable Frame
Storey 17	54.92	44.44
Storey 16	51.19	42.24
Storey 15	49.3	38.43
Storey 14	45.89	35.67
Storey 13	41.21	33.52
Storey 12	37.85	30.95
Storey 11	34.635	28.32
Storey 10	31.42	25.69
Storey 09	28.205	23.06
Storey 08	24.99	20.43
Storey 07	21.775	17.8
Storey 06	18.56	15.17
Storey 05	15.345	12.54
Storey 04	12.13	9.91
Storey 03	8.79	7.28
Storey 02	5.95	4.65
Storey 01	2.63	2.2
Base	0	0

Fig 5.3 Storey Displacement in mm



VI. CONCLUSION

This study presented a comparative analysis of traditional and sustainable structures on the 17th floor, taking into account similar stress conditions designed using the facility. Comparative analyses were performed on the Storey Moment, Storey Displacement, Storey Drift, and Storey Shear parameters. In this study, spare parts of the material were planned. Establishment tools are considered in this research work for modeling and dynamic analysis.

Results are observed in this research work

Storey Moment:-

The common equation to assess storey moment is Storey moment = Storey shear x storey height/3. Storey moment was found to be very comparable to story 11 with negligible distinction though hole of 2.9% was more unmistakable with increment in story tallness. Green structure was found to be lightweight and was able to stand up to forced loads considering seismic zone III.

Storey Shear:-

Storey shear factor is the ratio of the story shear force when story collapse occurs to the story shear force when total collapse occurs. Many dynamic analyses provide simple equations to calculate the required shear safety coefficients of stories that history can prevent. Shear forces showed minimal differences compared to cases, with a constant increase

as the amount of structure increased. Intuitively, moving the structure upwards would mean a higher overall shift value. Graphics showing history and The height of the structure looks exactly like the distracting shape. The shifts in the sticks increased on each floor, with the largest naked frame structure compared to the green building.

Storey Displacement:-

Story Uprooting Story relocation is the avoidance of a single story relative to the base or ground level of the structure. Naturally, able to anticipate higher add up to uprooting values as we move up the structure. So, a chart appearing the story displacement vs. the tallness of the structure looks precisely just like the avoided shape. Story relocation was found to rise with each story stature and was most extreme in case of uncovered outline structure when compared to green building.

REFERENCES

- [1] Shejwal Neha, Danish Ali and Bhutekar S.B., [Comparative Study of Estimate Between Conventional Building and Green Building], International Journal of Advance Research in Science and Engineering, Volume no.6, Issue no. 9, September 2017.
- [2] AlSadi A, Cabrera N, Faggini M, He Y, Patel M, Trevino F, Boyajian D and Zirkian T, [Comparative Study on the Cost Analysis of a Green Versus Conventional Building], Advancements in Civil Engineering & Technology, 2019.
- [3] Noel Johnson and Aswathy Soman, [Effect of Timber Members on Structures under Seismic Loading], International Journal of Engineering Research & Technology (IJERT) ISSN: 2278-0181, 2021.
- [4] Ashish Kumar Karn, Ashish Kumar Mishra and Kanhaiya kumar, [A CASE STUDY AND COMPARATIVE STUDY OF TWO GREEN BUILDING], IIIrd International Conference on New Horizons in Science, Engineering and Management and Humanities, 19th April 2019, ISBN: 978-93-87793-82-8.
- [5] Vishnu Vijayan, Geethu Elsa Thomas, Athira Madhu A, Devipriya P and Teena Thomas, [A COMPARATIVE STUDY ON SUSTAINABLE BUILDING CONSTRUCTION WITH CONVENTIONAL RESIDENTIAL BUILDING], INTERNATIONAL JOURNAL OF CURRENT ENGINEERING AND SCIENTIFIC RESEARCH (IJCESR), VOLUME-5, ISSUE-4, 2018.
- [6] Xiao-guang Zhao and Chun-Ping Gao, [Research on Energy-Saving Design Method of Green Building Based on BIM Technology], Hindawi Scientific Programming Volume 2022, Article ID 2108781, 10 pages.
- [7] Sneha S. Nagrale and Syed Sabihuddin, [Cost Comparison Between Normal Building and Green Building Considering Its Construction and Maintenance Phase], International Journal of Scientific Research and Engineering Development— Volume 3 Issue 4, July –Aug 2020.
- [8] Sidheshwar Murkute, Madan S. H and Dr. V. A. Patil, [Comparative Study of Green Concrete and Conventional Concrete on Strength and Durability Properties], International Research Journal of Advanced Engineering and Science, Volume 3, Issue 4, pp. 229-232, 2018.
- [9] Srikant Misra, G.R.K.D. Satya Prasad, Navnit Kumar and Satish Kumar Sah, [Comparison analysis of Green building materials and conventional materials in energy efficiency performance], International Research Journal of Engineering and Technology (IRJET), Volume: 03 Issue: 05 | May-2016.
- [10] Keerthana B Chandran and Dr. Susan Abraham, [Economic Evaluation and Comparison of Green Building with Conventional Building using Carbon Footprint and Embodied Energy Calculator developed using MATLAB], International Research Journal of Engineering and Technology (IRJET), Volume: 07 Issue: 07 | July 2020. 2010



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details