



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 14, Issue 5, May 2025

⊕ www.ijirset.com ⊠ ijirset@gmail.com 🖄 +91-9940572462 🕓 +91 63819 07438



International Journal of Innovative Research of Science, Engineering and Technology (IJIRSET)



www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 5, May 2025

DOI: 10.15680/IJIRSET.2025.1405430

Efficient use of Exhaust Gas Recirculation

A. Madeshwaran^a, R.Vimalanand^a, S.Vignesh^a, U. Santhosh^a, A. Raja^b

B.E Student, Department of Mechanical Engineering, Annamalai University, Annamalainagar, Tamil Nadu, India^a

Associate Professor, Department of Mechanical Engineering, Annamalai University, Annamalainagar,

Tamil Nadu, India^b

ABSTRACT: Exhaust Gas Recirculation (EGR) is a critical emission control technology that mitigates nitrogen oxides (nox) by reintroducing inert exhaust gases into the combustion chamber, thereby reducing peak flame temperatures. While effective in nox suppression, improper EGR management can adversely affect engine performance, fuel economy, and particulate emissions. This study examines the mechanisms of EGR operation, its influence on combustion dynamics, and the trade-offs between emission reduction and engine efficiency. Recent advancements, including cooled EGR systems, high-pressure and low-pressure EGR configurations, and intelligent control algorithms, are analyzed to highlight their role in optimizing EGR performance. Furthermore, the challenges of soot accumulation, combustion instability, and the interplay between EGR and aftertreatment systems are addressed. The findings emphasize the need for adaptive EGR strategies, particularly in modern downsized, turbocharged engines, to comply with stringent environmental regulations without compromising power output or durability. Future directions, such as hybridization with alternative nox reduction techniques and AI-driven EGR optimization, are also explored.

KEYWORD: Nitrogen oxide, EGR configuration, control algorithum , combustion instability , Aftertreatment, Turbocharged

I. INTRODUCTION

The increasing stringency of global emission regulations has driven the automotive industry to adopt advanced technologies for reducing harmful pollutants from internal combustion engines (ices) [1]. Among these, nitrogen oxides (nox) are a major concern due to their contribution to smog, acid rain, and respiratory diseases. Exhaust Gas Recirculation (EGR) has emerged as one of the most effective in-cylinder techniques to suppress nox emissions by reintroducing a portion of exhaust gases into the combustion chamber.[1]

The fundamental principle of EGR is based on diluting the fresh air-fuel mixture with inert exhaust gases, primarily carbon dioxide (CO_2) and water vapor (H_2O)[2]. This dilution reduces the oxygen concentration and increases the specific heat capacity of the charge, leading to lower peak combustion temperatures. Since nox formation is highly temperature- dependent, EGR effectively mitigates emissions without requiring additional aftertreatment in some cases. Despite its benefits, the application of EGR presents several challenges. Excessive EGR rates can lead to incomplete combustion, increased particulate matter (PM) emissions, and reduced engine efficiency. Additionally, the recirculated exhaust gas contains soot and unburned hydrocarbons, which can accumulate in the intake system and affect long-term engine reliability. Modern engines, particularly those with turbocharging and direct injection, require precise EGR control to avoid combustion instability and knocking.[2]

To address these challenges, advancements in EGR technology have led to the development of cooled EGR systems, which lower the temperature of recirculated gases for improved efficiency, and high-pressure/low-pressure EGR configurations, which optimize flow dynamics in turbocharged engines[2]. Furthermore, electronic control systems with real-time feedback from sensors enable dynamic EGR adjustment based on engine load, speed, and operating conditions[2]. This paper examines the role of EGR in modern emission control strategies, its impact on engine performance, and the latest technological advancements. It also discusses the integration of EGR with other aftertreatment systems, such as diesel particulate filters (DPF) and selective catalytic reduction (SCR), to meet future emission standards. Finally, emerging trends, including artificial intelligence (AI)-driven EGR optimization and hybrid EGR-SCR systems, are explored to highlight the future direction of clean combustion technologies.



International Journal of Innovative Research of Science, Engineering and Technology (IJIRSET)



www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 5, May 2025

|DOI: 10.15680/IJIRSET.2025.1405430|

II. EXPERIMENTAL SETUP

Exhaust Gas Recirculation (EGR) is an emission control technique that reduces nitrogen oxide (nox) emissions by recirculating a portion of an engine's exhaust gas back into the combustion chamber[3]. The primary mechanism behind EGR's effectiveness lies in its ability to lower peak combustion temperatures, which are a major factor in nox formation[3]. When exhaust gases—primarily composed of carbon dioxide (CO₂), nitrogen (N₂), and water vapor (H₂O)—are reintroduced into the cylinder, they act as a diluent, reducing the oxygen concentration and increasing the heat capacity of the intake charge. This results in slower combustion and lower flame temperatures, thereby suppressing thermal nox production[3].

The efficiency of EGR depends on several factors, including the EGR rate (the percentage of exhaust gas recirculated), the temperature of the recirculated gas, and the engine's operating conditions. Higher EGR rates generally lead to greater nox reduction but may also cause incomplete combustion, increased particulate matter (PM) emissions, and reduced thermal efficiency[3]as shown in Fig[1]. To mitigate these drawbacks, modern engines often employ cooled EGR, where the recirculated exhaust gas passes through a heat exchanger before re-entering the intake manifold. Cooling the EGR stream improves charge density and reduces knocking tendencies in gasoline engines, while also enhancing nox reduction in diesel engines.

Another critical aspect is the distinction between high-pressure EGR (HP-EGR) and low-pressure EGR (LP-EGR) systems. HP-EGR routes exhaust gas from upstream of the turbocharger turbine back to the intake manifold, making it suitable for high-load conditions[3]. LP-EGR, on the other hand, extracts exhaust gas downstream of the turbocharger and aftertreatment systems, providing better mixing and lower soot intake but requiring additional filtration to prevent compressor fouling. The choice between these systems depends on engine design, operating range, and emission targets[3].




Fig 1: Working Diagram of EGR




Fig. 2: Schematic Diagram of the EGR Attached to Engine



International Journal of Innovative Research of Science, Engineering and Technology (IJIRSET)



www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 5, May 2025

|DOI: 10.15680/IJIRSET.2025.1405430|

III. DESIGN OVERVIEW

The efficient use of Exhaust Gas Recirculation (EGR) involves a carefully designed system that recirculates a portion of an engine's exhaust gas back into the combustion chamber to reduce nitrogen oxide (nox) emissions by lowering peak combustion temperatures[4,5]. The key components of an EGR system include the EGR valve, which regulates the flow of exhaust gas; the EGR cooler, which reduces the temperature of the recirculated gas to improve charge density and combustion efficiency; and the engine control unit (ECU), which dynamically adjusts EGR flow based on engine load, speed, and operating conditions[5]as shown in fig[2]. There are two primary types of EGR systems—high-pressure (HP-EGR), which draws gas before the turbocharger turbine, and low-pressure (LP-EGR), which extracts gas after the turbocharger and particulate filter, each offering distinct advantages in diesel and gasoline engines[6].

To maximize efficiency, the system must ensure precise control over EGR rates to avoid combustion instability, soot formation, or excessive carbon deposits. Cooling the recirculated exhaust gas is critical, as it enhances volumetric efficiency and reduces knocking in gasoline engines[6]. However, challenges such as carbon buildup, corrosion, and potential power loss must be mitigated through robust materials, periodic maintenance, and optimized ECU calibration. Advanced EGR designs incorporate variable geometry valves, hybrid HP/LP-EGR configurations, and integration with aftertreatment systems like selective catalytic reduction (SCR) to further reduce emissions without compromising performance. By balancing nox reduction with engine efficiency, modern EGR systems play a vital role in meeting stringent emission standards while maintaining fuel economy and drivability[7].

IV. METHODOLOGY

The methodology for the efficient use of Exhaust Gas Recirculation (EGR) involves a systematic approach to optimize nox reduction while maintaining engine performance and fuel efficiency[7]. The process begins with engine mapping and calibration, where the optimal EGR rates are determined under various operating conditions, such as load, speed, and temperature, using computational models and experimental testing[8]. Next, EGR system design incorporates high-precision components, including a controlled EGR valve, an efficient cooler to lower exhaust gas temperatures, and durable piping to minimize pressure losses and carbon buildup[9]. Advanced control strategies are implemented through the Engine Control Unit (ECU), which dynamically adjusts EGR flow based on real-time sensor feedback to ensure stable combustion and prevent misfires or excessive particulate formation[10]as shown in fig [3,4]. Additionally, cooled EGR systems are preferred to enhance charge density and reduce knocking, particularly in gasoline engines. Integration with other emission control technologies, such as selective catalytic reduction (SCR) or particulate filters, further improves efficiency by addressing multiple pollutants simultaneously[10]. Finally, validation through bench and on-road testing ensures the system meets emission standards without compromising durability or drivability. Continuous monitoring and adaptive algorithms further refine EGR operation over the engine's lifespan, ensuring long-term efficiency and compliance with environmental regulations[11,12].




Fig 3 : Circuit Diagram Representation




Fig 4: Exhaust Gas flow diagram to Engine



International Journal of Innovative Research of Science, Engineering and Technology (IJIRSET)



www.ijirset.com |A Monthly, Peer Reviewed & Refereed Journal| e-ISSN: 2319-8753| p-ISSN: 2347-6710|

Volume 14, Issue 5, May 2025

[DOI: 10.15680/IJIRSET.2025.1405430]

V. CONCLUSION

Exhaust Gas Recirculation (EGR) is a highly effective technology for reducing nox emissions in internal combustion engines by lowering peak combustion temperatures through the controlled reintroduction of exhaust gases. When optimized through precise calibration, advanced cooling, and intelligent control strategies, EGR systems can achieve significant emission reductions without compromising engine performance or fuel efficiency. The integration of EGR with complementary technologies like turbocharging and after treatment systems further enhances its effectiveness, ensuring compliance with stringent environmental regulations. However, challenges such as carbon deposition, corrosion, and combustion instability must be carefully managed through robust design and maintenance practices. As automotive and industrial engines continue to evolve, EGR remains a critical component in the pursuit of cleaner and more sustainable combustion technologies, balancing ecological benefits with operational reliability. Future advancements in materials, control algorithms, and hybrid EGR configurations will further refine its efficiency, solidifying its role in next-generation emission control systems.

REFERENCES

[1]Heywood, J.B. (2018) – Internal Combustion Engine Fundamentals (2nd Ed.), mcgraw-Hill. (Covers EGR principles and nox reduction mechanisms)

[2]Ladommatos, N. Et al. (1996) – "The Effect of Exhaust Gas Recirculation on Diesel Engine Emissions", SAE Technical Paper 961165.

[3]Maiboom, A. Et al. (2008) – "EGR Effects on Combustion and Emissions in Diesel Engines", International Journal of Engine Research, Vol. 9, No. 1.

[4]EPA (Environmental Protection Agency) – "Emission Standards for Heavy-Duty Diesel Engines" (CFR Title 40, Part 86).

[5]Euro 6/VI Emission Standards – European Union regulations on nox limits for vehicles.

[6]SAE International – Multiple technical papers on EGR optimization in modern engines.

[7]Bosch (2020) – "Advanced EGR Systems for Clean Diesel Technology", Bosch Technical Reports.

[8]Cummins (2019) – "Optimized EGR Strategies for Low-nox Heavy-Duty Engines", Whitepaper.

[9]Toyota (2017) – "Cooled EGR in Gasoline Direct Injection (GDI) Engines", SAE Paper 2017-01-0683.

[10]Zhang, Y. Et al. (2021) – "AI-Based EGR Control for Hybrid Electric Vehicles", Applied Energy, Vol. 282.

[11]Guan, W. Et al. (2022) – "LP-EGR and Electrification for Ultra-Low Emissions", Journal of Automotive Engineering.

[12]Books & Comprehensive Guides Stone, R. (2012) – Introduction to Internal Combustion Engines (4th Ed.), Palgrave Macmil









INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com