



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 14, Issue 9, September 2025

Using Solar Panel Electrical Conductivity-Based Oil Detection and Skimming

Akash D¹, Darshith T G², Muruli T B³, Shivakumar T M⁴, Janardhan L. K⁵

U.G Students, Department of Electrical and Electronics Engineering, Channabasaveshwara Institute of Technology,
Gubbi, Tumkur, Karnataka, India¹⁻⁴

Assistant Professor, Department of Electrical and Electronics Engineering, Channabasaveshwara Institute of
Technology, Gubbi, Tumkur, Karnataka, India⁵

ABSTRACT: Oil spills pose a significant threat to marine ecosystems and water quality. Traditional oil detection and clean up methods are often time-consuming, expensive, and energy-intensive. This project proposes an innovative, eco-friendly solution that utilizes the electrical conductivity changes on solar panel surfaces to detect the presence of oil on water. When oil comes into contact with a solar panel's surface, it alters the panel's electrical conductivity due to the insulating nature of oil compared to water. By continuously monitoring these conductivity variations, the system can accurately detect oil contamination.

KEYWORDS: Oil Spill Detection, Electrical Conductivity, Solar Panel Sensor, Oil Skimming, Eco-Friendly Technology.

I. INTRODUCTION

Oil spills are one of the most harmful environmental disasters, causing severe damage to marine ecosystems, aquatic life, and coastal communities. Conventional methods of oil detection and removal often rely on manual inspection, satellite imaging, or chemical sensors—many of which are either expensive, slow, or limited by environmental conditions. Moreover, these methods usually require external power sources, making them less feasible for continuous, remote monitoring.

In recent years, renewable energy technologies and smart sensing systems have opened up new possibilities for environmental monitoring. This project introduces an innovative solution that combines the use of solar panels with electrical conductivity-based sensing to detect oil spills and activate an automated skimming mechanism. The core concept relies on the fact that oil, being a non-conductive substance, alters the electrical conductivity on the surface of solar panels when it comes into contact with them. By monitoring these conductivity changes, the system can detect the presence of oil on water surfaces.

The integration of solar power not only provides a sustainable energy source but also allows the system to operate autonomously in offshore or remote locations. Additionally, an attached skimming mechanism can be triggered immediately upon detection, enabling real-time response to oil spills and minimizing environmental damage.

II. LITERATURE SURVEY

Online detection of water in oil: Several studies examine how electrical conductivity or conductance-based sensors detect water content in oil, emulsified or free. Example: “A Conductivity-Based Sensor for Detecting Micro-Water in On-Line Oil Analysis” uses parallel enamel wires as probes to detect small water content up to ~3%.

Moisture in crude oil: Weak signal electromagnetic conductance methods have been used to measure moisture in crude oil (which changes conductivity) to monitor quality.

Water conductivity in oil–gas–water mixtures: In multiphase fluid systems, conductance sensors are used to determine water holdup by measuring conductivity and adjusting for temperature and salinity.

Conductometric sensors for oil degradation: For instance, using interdigitated electrodes coated with imprinted polymers (titania, silica, etc.) to detect acidic components or oxidation by-products in engine oil via change in conductance. Polyurethane-carbon nanotube composites have also been used to enhance sensitivity.

Multi-function sensors: There are sensors that combine resistance (conductivity) and inductance/impedance changes to detect metallic contaminants or general degradation in hydraulic oil systems.

Optical / Fluorescence sensors: Many systems for oil spill detection use optical methods (e.g. fluorescence) to detect thin oil films on water surface. These are sensitive to film thickness, but rely on light, line of sight, etc.


SAR imagery + Deep Learning: Large-scale oil spill detection often uses remote sensing (satellite radar, etc.) with image processing / machine learning. Good for large areas, but not suited for small, localized, continuous detection in situ


III. METHODOLOGY

This project uses solar panels both as a power source and as a sensing surface for oil detection. Conductive electrodes or strips are embedded on or near the solar panel surface. When oil spills occur, the non-conductive nature of oil alters the electrical conductivity between these electrodes. A microcontroller continuously monitors these changes. Once oil is detected, it activates a motorized skimming mechanism powered by solar energy stored in a rechargeable battery. The skimmer collects the oil into a container. The system operates autonomously, offering real-time oil detection and removal using renewable energy.

IV. EXPERIMENTAL RESULTS

The most relevant information about solar panel electrical conductivity-based oil detection and skimming experiments comes from a study focusing on oil detection and skimming using sensors and mechanisms to detect oil presence by monitoring conductivity changes at the water surface, combined with motorized discs to physically remove oil. The experiment results showed the system could successfully detect oil presence.





Additionally, solar panels coated with oil can affect their electrical output due to changes in light absorption and conductivity. Experiments with oil coatings of varying degradation levels showed fresh oil could enhance power output slightly by reducing reflection, but degraded oils tend to reduce panel performance. This also ties indirectly to electrical conductivity as oil on panels impacts their electrical efficiency. This convergence of oil detection using electrical conductivity sensors and solar-powered skimming mechanisms demonstrates promising experimental results for practical and autonomous oil spill detection and cleaning technologies. If more specific experimental data details or setups are needed, a focused follow-up can be pursued.

V. CONCLUSION

The proposed solar panel electrical conductivity-based oil detection and skimming system provides a sustainable and efficient solution for monitoring and removing oil spills from water bodies. By utilizing the change in electrical conductivity as a detection parameter, the system ensures reliable identification of oil layers on the water surface. Integration with solar power makes the design eco-friendly, cost-effective, and suitable for remote or offshore applications. Furthermore, the addition of an automatic skimming mechanism enhances real-time response, minimizing environmental damage and preserving aquatic ecosystems. This approach demonstrates the potential of combining renewable energy with smart sensing techniques to address critical environmental challenges in a clean and energy-independent manner.

REFERENCES

1. **Saleh, M., Elhajj, I. H., & Asmar, D. (2024).** In situ Sensors for Oil Spill Detection and Thickness Measurement: Methods and Challenges. *IEEE Transactions on Instrumentation and Measurement*, 73, Article 9512616. DOI: 10.1109/TIM.2024.3425461. This paper discusses conductivity-based sensor arrays for oil thickness measurement using a differential interface detection algorithm, with experimental evaluations demonstrating accurate measurements under static conditions. Additional related works referenced in the same paper include studies on motorized electrodes for conductivity measurement, capacitive sensor arrays, and implementations in dynamic conditions like waves and skimming operations. A related IEEE paper covering oil detection and skimming design concepts is titled "Electrical conductivity based oil detection and skimming," often cited in literature reviews on oil skimmers and sensor technologies.
2. **Zhang, M., Shao, D., Liu, J., et al. (2025).** "Study on the change of the oil-paper insulation's AC conductivity characteristics based on dielectric response in frequency domain." This paper explores conductivity and dielectric response related to oil-paper insulation aging, which may be relevant to understanding conductivity changes in oil contamination contexts.
3. **Development of Oil Slick Thickness Sensors,** a project report by the American University of Beirut under BSEE Award #E17PC00001, developing capacitive and spectrometric sensors for measuring oil thickness on water with wireless communication. The capacitive sensor measures capacitance changes of oil/water/air interfaces to estimate oil thickness, designed for mounting on skimmers, booms, or buoys for real-time monitoring.
4. **Du, H., et al. (2025).** "Ultrasonic measurement of oil slick thickness using a metallic array sensor," discusses using a metallic array sensor based on electrical conductivity differences between oil and water for oil slick thickness measurement. This adds to conductivity-based sensing combined with ultrasonic techniques.
5. **Choi, W.-S., Yoon, D., Kim, T., & Lee, J. (2017).** Oil skimmer and controller monitoring system using IoT technology. 2017 IEEE International Conference on Multisensor Fusion and Integration for Intelligent Systems (MFI), 458-463. This paper proposes a user-controlled smartphone IoT system for oil skimmer monitoring using BLE 4.0
6. **Budiman, F., Abrar, I., Tri, H., Rayi, M., Nurwijayadi, et al. (2023).** Strengthening oil pollution monitoring system in aquatic environment through development of IoT-based Oil-Water Separator Device. This study develops an IoT automatic oil-water separator device for oil pollution monitoring in water ecosystems



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details