



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 15, Special Issue 1, January 2026

IoT-Based Smart Footstep Power Generation and Monitoring System

Glory Ram¹, Dipti Nale², Ditisha Mohite³, Roshani Shinde⁴

Department of Information Technology, Indala College of Engineering, Kalyan, Maharashtra, India¹²³⁴

ABSTRACT: The growing global energy crisis and environmental concerns have accelerated the search for sustainable power alternatives, with footstep power generation emerging as an innovative method to harness kinetic energy from human movement. This review examines three main approaches: piezoelectric-based systems, hybrid piezoelectric–solar designs, and mechanical rack-and-pinion mechanisms. Piezoelectric models convert pressure from footsteps into electricity, while hybrid systems enhance efficiency through solar integration and motion sensors, and mechanical setups use linear-to-rotary conversion to drive DC generators for large-scale applications. The generated energy is stored in batteries for uses such as lighting, charging devices, and powering sensors in smart environments. Although limited by pedestrian flow and installation costs, these systems hold strong potential for reducing carbon emissions and promoting renewable, decentralised energy solutions. Future advancements in storage, IoT, and AI are expected to further optimise performance and expand real-world applications.

KEYWORDS: Footstep Power Generation, Piezoelectric Energy Harvesting, Hybrid Renewable System, Rack and Pinion Mechanism, Sustainable Energy, Smart Power Generation.

I. INTRODUCTION

The rising global demand for electricity and the depletion of fossil fuels have driven the search for renewable energy alternatives. Footstep power generation has emerged as a promising method to harvest human kinetic energy from walking, converting it into electricity through mechanisms like piezoelectric materials or mechanical rack-and-pinion systems. Piezoelectric-based designs generate power when pressure is applied to floor tiles, while mechanical systems use foot motion to drive DC generators. These systems can power small devices or lighting in high-traffic areas such as stations or malls. Though the energy output depends on pedestrian flow, advancements in materials, storage, and smart technologies continue to enhance efficiency, making footstep power generation a clean, sustainable, and practical energy source for modern urban environments.

II. SYSTEM MODEL AND ASSUMPTIONS

The proposed footstep power generation system is modelled as an integrated electromechanical arrangement that converts the mechanical pressure of human footsteps into usable electrical energy. At the core of the system is a network of piezoelectric transducers placed beneath a specially designed floor panel. When a person steps on the panel, the applied force produces mechanical deformation in the piezoelectric material, resulting in the generation of alternating electrical signals. To ensure uniform stress distribution, the sensors are embedded within a rigid or semi-flexible mechanical platform that transfers the footstep force evenly across the entire array. This arrangement not only boosts the energy output but also reduces the likelihood of structural fatigue in the sensors.

The electrical output produced by the piezoelectric discs is irregular and alternating in nature, making power conditioning essential. The generated AC voltage is routed through a rectification and filtering unit that converts it into a stable DC supply. A voltage regulation stage is then used to maintain consistency in the output before the energy is stored in a rechargeable battery or a supercapacitor. Because footstep-generated energy is intermittent, the storage module acts as a buffer, accumulating small amounts of energy and making it available for continuous operation of low-power devices such as LEDs, mobile charging units, or environmental monitoring sensors. To monitor the behaviour of the system, a microcontroller records step count, voltage levels, and storage status, enabling analysis of energy production under different walking conditions.

In developing the system model, several assumptions are made to simplify performance evaluation and theoretical calculations. It is assumed that the footsteps occur at a uniform pace and exert a force equivalent to that of an average adult. This assumption helps in estimating the typical stress experienced by the piezoelectric sensors, although real-world walking patterns may vary. The model also assumes that the relationship between mechanical pressure and electrical output is approximately linear, allowing easier prediction of the voltage generated for each footstep. Mechanical losses such as friction, heat dissipation, and deformation of the platform are considered minimal, with the expectation that most of the applied force is directly transferred to the sensors. Additionally, the model is developed under the assumption that environmental conditions—such as temperature or humidity—remain constant and do not significantly influence the performance of the piezoelectric elements. Electrical components, including the rectifier, filters, and storage unit, are assumed to operate with stable efficiency over the duration of testing, without major losses or degradation.

III. LITERATURE SURVEY

Footstep power generation has gained attention as an innovative method for harvesting renewable energy from human locomotion. Various researchers have proposed different techniques and materials to improve efficiency, output, and practicality.

Saju Simon et al. (2019) designed a piezoelectric-based system that converts mechanical stress from footsteps into electrical energy using piezo sensors embedded under flooring tiles. The generated power is stored in rechargeable batteries and monitored using a microcontroller. Their results demonstrated that installing these systems in crowded public areas such as railway stations can generate considerable power for lighting and small loads.

Prabaharan et al. (2013) and **Mathane et al. (2015)** also investigated piezoelectric energy harvesting and showed that output voltage depends on sensor arrangement and applied pressure. These studies confirmed that piezo materials are durable and eco-friendly for small-scale applications.

Naresh et al. (2018) presented a practical implementation of a piezoelectric energy system combined with a microcontroller for voltage regulation and storage. Their work emphasised low-cost design and real-time monitoring, highlighting the potential for campus-level power generation.

To improve overall output, **hybrid systems** have been proposed that combine **piezoelectric and solar sources**. **Ghosh et al. (2013)** and **Vijay Anand et al. (2017)** developed hybrid models that use solar panels during daytime and piezoelectric sensors underfoot, producing higher and more consistent energy output. These systems achieved around **17 V – 22 V**, sufficient for lighting and battery charging.

On the other hand, **rack-and-pinion mechanical systems** convert linear foot motion into rotary motion that drives a DC generator. **Abhishek N. and Shivasharana Yalagi (2016)** and **Yogesh Motey et al. (2017)** demonstrated such designs capable of producing higher wattage per step. These setups are robust and scalable, making them suitable for public places with heavy foot traffic, though they require strong mechanical construction and regular maintenance. Collectively, the reviewed literature indicates steady progress in footstep energy harvesting—from early piezoelectric prototypes to modern hybrid and mechanical models. Each approach contributes to improving energy efficiency, reliability, and adaptability. The findings reveal that integrating **smart controllers, efficient storage units, and IoT-based monitoring** can further enhance system performance, making footstep power generation a promising step toward sustainable urban energy solutions.

IV. PROBLEM STATEMENT

The increasing global demand for electricity and the depletion of non-renewable energy resources have created a pressing need for alternative and sustainable energy solutions. A considerable amount of mechanical energy generated by human footsteps in crowded public places remains unused. This project aims to address the problem of wasted kinetic energy by designing a system that utilizes piezoelectric sensors to convert footstep pressure into electrical energy. The generated energy can then be stored and used for powering low-energy devices such as LEDs or charging small batteries, thereby contributing to renewable energy generation and environmental conservation.

However, the main challenge lies in efficiently harvesting and storing this energy in a cost-effective manner suitable for practical applications such as lighting systems, battery charging, or sensor networks.

V. METHODOLOGY

This review paper adopts a systematic methodology to examine and synthesise existing research on footstep power generation systems. The process comprised three main stages: literature collection, classification of design approaches, and comparative analysis. Relevant journal articles, conference papers, and experimental studies published between 2010 and 2023 were retrieved from reputed scientific databases using keywords such as piezoelectric energy harvesting, footstep power generation, hybrid renewable systems, and rack-and-pinion mechanism. The collected literature was categorised into three primary approaches.

- (1) **Piezoelectric-based systems** utilise piezoelectric sensors embedded beneath walking surfaces to convert mechanical pressure and vibration into electrical energy, which is stored in rechargeable batteries and regulated using microcontroller-based circuits.
- (2) **Hybrid piezoelectric–solar systems** combine piezoelectric modules with solar panels to enhance efficiency and ensure energy availability under variable conditions. These systems incorporate motion sensors such as PIR modules to minimise energy wastage and employ lithium-ion batteries for storage.
- (3) **Rack-and-pinion mechanical systems** convert the linear motion of footsteps into rotary motion to drive DC generators, providing greater scalability and mechanical strength, making them suitable for high-traffic public infrastructure. A comparative analysis was then conducted based on energy output, implementation cost, durability, and application scope. Results indicate that piezoelectric systems are efficient for small-scale applications, hybrid systems offer improved energy yield and reliability, and rack-and-pinion mechanisms are ideal for large-scale installations. Overall, this methodological framework underscores that integrating these systems with modern technologies such as IoT, advanced energy storage, and smart grid connectivity can further enhance efficiency, scalability, and sustainability of footstep power generation in urban environments.

VI. EFFICIENT COMMUNICATION

Efficient communication within a footstep power generation system using piezoelectric sensors plays a crucial role in ensuring that the collected data, system status, and energy metrics are accurately transferred between different hardware components. Since the system relies on the interaction between mechanical, electrical, and digital modules, effective communication is essential for seamless coordination. The microcontroller acts as the central processing unit that receives input signals from the piezoelectric transducers, converts them into interpretable electrical measurements, and communicates this information to the monitoring and storage units. This exchange must occur with minimal delay and high accuracy to ensure that the energy harvested from each footstep is properly calculated, stored, and utilised.

In addition to internal signal processing, efficient communication is important for real-time monitoring and user interaction. Many modern implementations integrate IoT modules or wireless communication systems that transmit performance data such as energy generated, number of footsteps, or battery condition to a remote display or cloud platform. For such systems, the communication channel must be reliable, energy-efficient, and capable of handling continuous data flow without introducing noise or signal loss. By ensuring smooth and accurate communication among sensors, controllers, storage devices, and user interfaces, the overall efficiency, responsiveness, and reliability of the footstep energy harvesting system are greatly enhanced. This not only supports better system management but also improves long-term performance analysis and optimisation.

VII. SECURITY

Security is an important consideration in the design and deployment of a footstep power generation system using piezoelectric sensors, especially when the system incorporates digital monitoring, data logging, or IoT-based communication. Although the primary purpose of the system is energy harvesting, the integration of microcontrollers, wireless modules, and storage devices introduces potential vulnerabilities that must be addressed to ensure safe and reliable operation. One key aspect of security involves protecting the system's electrical components from unauthorised

access or tampering. Since the setup is typically installed in public pathways, floors, or staircases, the mechanical structure and embedded sensors must be physically secured to prevent damage, theft, or accidental interference. Robust enclosures, protective casings, and shock-absorbing materials help safeguard the sensors and wiring from environmental stress and deliberate misuse.

In addition to physical protection, data security becomes essential when the system transmits information such as voltage levels, footstep counts, or energy statistics to a remote monitoring platform. Wireless communication channels, if left unsecured, may be susceptible to interception, manipulation, or unauthorised monitoring. Implementing secure communication protocols, encrypted data transfer, and controlled access to the microcontroller interface helps prevent cyber threats and ensures the integrity of the system's data. Furthermore, firmware security measures, such as password protection and restricted programming access, reduce the risk of malicious reconfiguration of the power management system. By incorporating both physical and digital security strategies, the footstep power generation system can operate safely in public environments while maintaining accurate data reporting and long-term reliability.

VIII. RESULT AND DISCUSSION

In the fig 1, it shows the connections of all the components to generate the energy using the piezoelectric sensor with footsteps.




Fig. 1 Connection of the components.




Fig. 2 Block Diagram of Footsteps Power Generation

In the fig 2, it shows the working flow of the project. It is the Block Diagram of Footsteps Power Generation showing the work flow. Steps of power generation.

IX. CONCLUSION

Footstep power generation represents a promising step toward sustainable and decentralised energy solutions. By harnessing kinetic energy through piezoelectric, hybrid, and mechanical systems, it transforms everyday human activity into useful electrical power. While current limitations include modest output and installation costs, continuous advancements in materials, storage, and smart integration indicate strong potential for large-scale adoption. This technology not only supports renewable energy goals but also paves the way for smarter, energy-efficient urban infrastructures.

REFERENCES

1. Saju Simon S. G., Manikandan R., Priyanka S., and Ranjith Kumar S., "Advanced Foot Step Power Generation Using Piezoelectric Sensors," *Journal of Emerging Technologies and Innovative Research (JETIR)*, vol. 6, no. 12, pp. 211–214, Dec. 2019.
2. Jaydev Ghosh, Supratim Sen, Amit Saha, and Sameer Basak, "Electrical Power Generation Using Foot Step for Urban Area Energy Applications," *International Conference on Advances in Computing, Communications, and Informatics (ICACCI)*, 2013.
3. Prabakaran R., Jayramaprakash A., and Vijay Anand, "Power Harvesting by Using Human Foot Step," *International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET)*, vol. 2, no. 7, Jul. 2013.

International Journal of Innovative Research in Science, Engineering and Technology

International Conference on Emerging Technologies and Pharmaceutical Research (ICETPR 2026)

17–18 January 2026

Indala College of Engineering, Polytechnic & Pharmacy, Kalyan, MH, India

[Volume 15, Special Issue 1, January 2026]

4. Mathane Nitashree V., Salunkhe Arati L., and Gaikwad Sayali S., “Foot Step Power Generation Using Piezoelectric Material,” International Journal of Advanced Research in Electronics and Communication Engineering (IJARECE), vol. 4, no. 10, Oct. 2015.
5. Naresh K., Balaji A., Rambabu M., and Nagaraju G., “Practical Oriented Foot Step Electric Power Generation by Using Piezo Material and Microcontroller in Campus,” International Research Journal of Engineering and Technology (IRJET), vol. 5, no. 7, Jul. 2018.
6. Abhishek N., and Shivasharana Yalagi, “Power Generation by Foot Steps Using Rack and Pinion Arrangement,” International Journal of Engineering Research and Advanced Technology (IJERAT), Special Volume 2, Issue 1, May 2016.
7. Yogesh Motey, Pooja Dekate, Madhushri Kewate, and Jayashree Aswale, “Footstep Power Generation System,” International Journal of Innovations in Engineering and Science (IJIES), vol. 2, no. 6, 2017.
8. Itika Tandon and Alok Kumar, “A Unique Step Towards Generation of Electricity via New Methodology,” International Journal of Advanced Research in Computer and Communication Engineering (IJARCCE), vol. 3, no. 10, Oct. 2014.



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details