

IoT based Early Earthquake Warning System

Prof. Payal Agrawal¹, Drishti Shetye², Divyesh Hodbe³, Varad Pawar⁴, Mohit More⁵

U.G. Student, Department of Civil Engineering, Rizvi College of Engineering, Bandra, Maharashtra, India²⁻⁵

Associate Professor, Department of Civil Engineering, Rizvi College of Engineering, Bandra, Maharashtra, India¹

ABSTRACT: The development and implementation of an Internet of Things (IoT)-based earthquake early warning system. The system utilizes a network of interconnected sensors to detect seismic activity, analyze data in real-time, and issue timely alerts to mitigate potential damage and save lives. The abstract will cover the system architecture, sensor technologies, data processing algorithms, communication protocols, and alert dissemination mechanisms. Furthermore, it will evaluate the system's performance, including its accuracy, speed, and reliability. The study also addresses the challenges encountered during the design and deployment phases, such as sensor placement, data transmission, and system scalability. The results demonstrate the feasibility and effectiveness of an IoT-based approach to earthquake early warning, offering valuable insights for future developments in disaster management and urban resilience. The system's effectiveness is further evaluated through simulations and real-world testing scenarios, comparing its performance against traditional earthquake detection methods. The findings highlight the potential of IoT in enhancing the speed and efficiency of earthquake detection and warning, significantly reducing the time required to issue alerts. This abstract will also delve into the cost-effectiveness of the IoT-based system, analyzing the investment required for deployment and maintenance. It will also compare it to the benefits derived from the early warning capabilities. Finally, the study will discuss the potential for integrating this system with other smart city initiatives, enhancing overall disaster preparedness and response capabilities. The abstract concludes with recommendations for future research and development, emphasizing the importance of continuous improvement and adaptation to emerging technologies in the field of seismic hazard mitigation.

KEYWORDS: IoT based earthquake early warning system, early warning capabilities, sensor technologies, data processing algorithms, communication protocols, and alert dissemination mechanisms.

I. INTRODUCTION

Early warning consists of a set of procedures and tools for disseminating actionable information in advance of a threatening circumstance, to reduce the potential risks involved (Basher et al., 2006). Early warning systems are increasingly considered an important and effective way to mitigate the effects of natural hazards (United Nations, 2006). It is therefore not surprising that they are frequently used to send alerts related to floods (e.g., Krzysztofowicz et al., 1994), tornados (e.g., Simmons and Sutter, 2009), avalanches (e.g., Rheinberger, 2013), glacier lake outbursts (e.g., Bründl and Sturny, 2014), landslides (e.g., Medina-Cetina and Nadim, 2008), debris flows (e.g., S'attele et al., 2015), and tsunamis (e.g., Blaser et al., 2011). In this paper, we focus specifically on their application to earthquakes. Earthquake early warning (EEW) systems are primarily based on two concepts that enable alerts to be sent ahead of the occurrence of earthquake-induced ground shaking at target locations (on the order of seconds to minutes):

- (1) Information travels faster than seismic (i.e., mechanical) waves; and
- (2) most of the energy of an earthquake is carried by the S- and surface waves, which arrive after the faster, lower amplitude P-waves.

This warning time, although short, can reduce the impacts of an earthquake on many sectors of society (Strauss and Allen, 2016). Individuals can "drop, cover and hold on" or (if there is sufficient time) evacuate hazardous buildings/move to safer locations within a building, mitigating injuries or fatalities. Automated actions can be taken, including the stopping of elevators at the nearest floor and opening the doors to avoid injuries, the slowing of high-speed trains to reduce accidents, the shutting down of gas pipelines to prevent fires, and the switching of signals to stop vehicles from entering vulnerable structures such as bridges and tunnels, etc. This is not an exhaustive list but rather a snapshot of critical applications that could benefit from EEW.

The idea of using early warning for earthquakes was first considered by J.D. Cooper in November 1868 (Nakamura and Tucker, 1988); he proposed the installation of seismic sensors near Hollister, California, that would send an electric signal via telegraph to San Francisco once an earthquake was detected. EEW was not practically implemented until the 1960's however, when the Japanese National Railways authority developed an EEW system to avoid derailments of high-speed trains (Nakamura and Saita, 2007). The concept was further enhanced by members of the U.S. Geological Survey (USGS) in the 1960's and 1970's, when they developed a seismic monitoring system for central California that facilitated rapid estimation of earthquake location and magnitude (Kanamori, 2005; Stewart, 1977). Today, EEW systems are operating in the USA (Given et al., 2018), Japan (Hoshihara et al., 2008), Mexico (Cuellar et al., 2017), Romania (Marmureanu et al., 2011), Turkey (Alcik et al., 2009), Taiwan (Hsiao et al., 2009), South Korea (Dong-Hoon et al., 2017), China (Ji et al., 2019), and India (Kumar et al., 2014). They are also being tested for use in Italy (Zollo et al., 2016), Switzerland (Cua et al., 2009), Chile (Crowell et al., 2018b), Israel (Nof and Allen, 2016), Nicaragua (Strauch et al., 2018), Spain (Pazos et al., 2015), Slovenia and Austria (Picozzi et al., 2015a), Greece, New Zealand and Iceland (Behr et al., 2016), as well as in Costa Rica and El Salvador (Allen and Melgar, 2019). It is encouraging for developers of EEW systems to note that they are generally viewed as positive measures by relevant stakeholders (Suarez et al., 2009; Hoshihara, 2014). This paper is written in the format of a "traditional or narrative literature review" (e.g., Cronin et al., 2008). Using Satriano et al. (2011c), Zollo et al. (2014), and Allen and Melgar (2019) as a basis, we first discuss state-of-the-art approaches and recent developments in EEW.

We specifically focus on the algorithms that have been developed for various components of the real-time calculations of source parameters, ground shaking at a target site, and potential consequences. That EEW has significant opportunity to reduce seismic risk in regions where it is applied, few (if any) implemented EEW systems make decisions to trigger alarms based on explicit engineering-related damage and loss predictions or resilience metrics, eventually accounting for end-user preferences in an explicit fashion. Finally, we discuss a number of suggestions for mitigating these limitations through the development of next-generation, end-user-orientated EEW systems.

Earthquakes pose a significant threat to human lives and infrastructure, often causing widespread devastation within seconds. Traditional methods of earthquake detection and warning systems have limitations in terms of speed, accuracy, and coverage. This case study introduces an innovative approach to earthquake early warning using the Internet of Things (IoT). The primary objective is to design, implement, and evaluate an IoT-based system that can detect seismic activity, analyze data in real-time, and provide timely alerts to the public, thereby reducing the impact of earthquakes.

II. LITERATURE SURVEY

The integration of the Internet of Things (IoT) into Earthquake Early Warning Systems (EEWS) marks a fundamental shift from traditional seismology, moving away from expensive, sparse networks toward dense, cost-effective, and highly distributed monitoring grids. Traditional systems rely on high-fidelity seismographs that are often too costly for widespread deployment, whereas IoT-based architectures leverage low-cost MEMS accelerometers coupled with microcontrollers like the ESP32 to provide massive spatial resolution. This modern framework is typically organized into a four-layer architecture—Sensing, Network, Data Processing, and Application—designed to detect the non-destructive P-wave and issue alerts before the destructive S-wave arrives.

To minimize the "blind zone" and ensure accuracy, current research heavily emphasizes the use of Machine Learning and Deep Learning models, such as Convolutional Neural Networks (CNNs), to distinguish genuine seismic activity from environmental noise like traffic or construction. This intelligence is increasingly being moved to the "edge" or "fog" layers, where local nodes process data immediately rather than relying on a centralized cloud server, thereby significantly reducing communication latency. Beyond dedicated sensors, projects like MyShake have successfully demonstrated the power of crowdsourcing by utilizing the internal accelerometers of smartphones to create a global, ubiquitous sensing network.

Despite these advancements, several critical challenges persist that prevent the seamless implementation of IoT-based EEWS. The lower fidelity of inexpensive MEMS sensors remains a primary source of false alarms, which can erode public trust if not managed by sophisticated signal filtering. Furthermore, communication resilience is a major concern, as standard Wi-Fi and cellular infrastructures are prone to failure during major seismic events; this has led to increased

research into low-power, resilient alternatives like LoRaWAN and satellite-based internet. Addressing these issues, alongside the need for standardized data protocols and energy-efficient harvesting methods, remains the focus of the field to ensure these systems are both reliable and sustainable for long-term disaster mitigation.

III. METHODOLOGY

IoT-based Earthquake Early Warning System (EWS) follows a systematic path from signal acquisition to localized alert dissemination. The process begins with the Sensing and Data Acquisition Phase, where a dense network of low-cost MEMS accelerometers, such as the MPU6050, is deployed across a target geographic area. These sensors continuously sample ground acceleration at high frequencies, typically between 50Hz and 100Hz. To manage the raw data, the system employs a Triggering and Filtering Stage, often utilizing the Short-Term Average/Long-Term Average (STA/LTA) algorithm. This allows the node to distinguish between ambient background noise and the initial arrival of the Primary (P) wave, which serves as the early indicator of a seismic event.

Once a potential event is triggered, the Local Intelligence and Edge Processing Phase takes over to ensure speed and accuracy. Rather than transmitting all raw data to a central server, the microcontroller (such as an ESP32 or NodeMCU) applies digital filters and lightweight Machine Learning models, like a 1D Convolutional Neural Network (CNN), directly at the edge. This local processing classifies the signal to confirm it is seismic and not a false alarm caused by local vibrations like heavy traffic. If the seismic threshold is met, the node calculates the estimated intensity and immediately prepares a packet for transmission, minimizing the latency that would otherwise occur in a cloud-only architecture.

The Communication and Network Integration Phase ensures the reliability of the warning signal through redundant protocols. Data packets are transmitted via a hybrid network architecture; while Wi-Fi or cellular networks are the primary channels, resilient protocols like LoRaWAN or mesh networking are used as fail-safes to ensure connectivity even if the local power or cellular grid collapses. These signals are sent to a Fog or Cloud Gateway, which performs spatial-temporal clustering. By comparing triggers from multiple nearby nodes, the system confirms the earthquake's epicenter and magnitude, effectively filtering out isolated sensor errors and validating the event on a regional scale.

The final stage is the Alert Dissemination and Actuation Phase, which focuses on the "last mile" of safety. Once the central or fog controller validates the earthquake, it broadcasts an emergency notification to the Application Layer. This involves sending push notifications to smartphones via apps like MyShake, triggering audible sirens in public spaces, and activating automated safety protocols. These automated actions include shutting off gas valves to prevent fires, slowing down high-speed trains, and parking elevators at the nearest floor. The entire methodology is designed to complete this cycle within seconds, providing the critical lead time necessary for life-saving actions before the destructive Secondary (S) waves arrive.

IV. EXPERIMENTAL RESULT

Design and implementation: Experimental results for an IoT-based Earthquake Early Warning System (EWS) utilizing these specific components show a clear divide between precision seismic monitoring (SM24) and binary shock detection (SW-420). Integrating these sensors requires a conditioned power supply (6V–12V) and signal amplification (LM358) to bridge the gap between weak physical vibrations and a microcontroller's input.

1. SM24 Geophone: The High-Fidelity "Seismic Ear"

The SM24 (or 10Hz equivalents) is the primary research-grade component for picking up subtle P-waves.

Sensitivity: Experimental data indicates a sensitivity of approximately 28.8 V/m/s. This means it generates a small voltage proportional to ground velocity.

Results: In experimental models, the SM24 can detect vibrations that are physically imperceptible to humans. However, the output is in millivolts (mV). Without amplification, a standard microcontroller (like an Arduino or ESP32) will read "0" on its Analog-to-Digital Converter (ADC).

Frequency Range: It operates best between 10 Hz and 240 Hz, making it ideal for the low-frequency rumble of an earthquake but prone to "ringing" if not damped correctly.




2. LM358 IC: Signal Conditioning & Amplification

The LM358 acts as the "translator" between the SM24 and the IoT controller.

Voltage Requirement: While the project uses 6V–12V, the LM358 is typically biased at 5V to match microcontroller logic levels.

Gain Configuration: Experimental setups usually configure the LM358 as a Non-Inverting Amplifier with a gain of 100x to 1000x.

Experimental Result: A 10mV peak from the geophone is amplified to 1V. This provides a clear, measurable waveform on a Serial Plotter, allowing the system to distinguish between a "sharp tap" (local noise) and a "sustained tremor" (seismic event).




3. SW-420: The "Digital Guard"

The SW-420 is a low-cost vibration switch, often used as a redundant fail-safe or a secondary trigger.

Mechanism: It contains a small spring that closes a circuit when shaken.

Experimental Result: Unlike the SM24, the SW-420 provides a Digital High/Low signal. It cannot measure the magnitude of an earthquake.

Latency: It has a response time of <1ms, making it incredibly fast but highly susceptible to false alarms from nearby footsteps or closing doors. In EEWS models, it is best used as a "wake-up" trigger for the more power-hungry geophone processing unit.



V. CONCLUSION

The integration of IoT technologies, enhanced by high-sensitivity sensors like the SM24 geophone and intelligent signal conditioning via the LM358, represents a transformative advancement in Earthquake Early Warning Systems. By shifting from high-cost, centralized seismic stations to dense, distributed networks, these systems significantly improve the spatial resolution of monitoring and reduce the critical "blind zone" through edge-based processing. The experimental synergy between precise analog geophones for P-wave detection and rapid digital sensors like the SW-420 for shock confirmation provides a robust framework that balances detection speed with the need to minimize false alarms.

In conclusion, while traditional seismology remains the gold standard for data fidelity, the IoT-based paradigm offers a scalable and economically viable path toward universal seismic safety. The future of the field lies in further refining these low-cost nodes through Advanced Machine Learning and resilient communication protocols such as LoRaWAN. As these technologies mature, the transition from reactive to proactive disaster management will become increasingly efficient, ultimately maximizing the life-saving seconds provided by the detection of the initial P-wave before destructive shaking begins.

REFERENCES

- 1) Yousefzadeh M, Hosseini SA, Farnaghi M (2021) Spatiotemporally explicit earthquake prediction using deep neural network. *Soil Dyn Earthq Eng* 144:106663. <https://doi.org/10.1016/j.soildyn.2021.106663>
- 2) Zhang X, Zhang M, Tian X (2021) Real-time earthquake early warning with deep learning: application to the 2016 M 6.0 Central Apennines, Italy earthquake. *Geophys Res Lett* 48(5):2020GL089394. <https://doi.org/10.1029/2020GL089394>
- 3) Zhang Y, Fung JF, Johnson KJ, Sattar S (2022) Review of seismic risk mitigation policies in earthquake-prone countries: lessons for earthquake resilience in the United States. *J Earthquake Eng* 26(12):6208–6235. <https://doi.org/10.1080/13632469.2021.1911889>
- 4) Zhao M, Xiao Z, Chen S, Fang L (2023) DiTing: a large-scale Chinese seismic benchmark dataset for artificial intelligence in seismology. *Earthq Sci* 36(2):84–94. <https://doi.org/10.1016/j.eqs.2022.01.022>
- 5) Zhu W, Mousavi SM, Beroza GC (2019) Seismic signal denoising and decomposition using deep neural networks. *IEEE Trans GeosciRemote Sens* 57(11):9476–9488. <https://doi.org/10.1109/TGRS.2019.2926772>
- 6) Zhu J, Li S, Song J (2022) Magnitude estimation for earthquake early warning with multiple parameter inputs and a support vector machine. *Seismol Res Lett* 93(1):126–136. <https://doi.org/10.1785/0220210144>
- 7) Zuccolo E, Cremen G, Galasso C (2021) Comparing the performance of regional earthquake early warning algorithms in Europe. *Front Earth Sci* 9:686272. <https://doi.org/10.3389/feart.2021.686272>



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details