



International Journal of Innovative Research in Science Engineering and Technology (IJIRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.699

Volume 15, Issue 3, March 2026

Semantic Analysis of News Authenticity Using BERT

Dr. P Ashok Kumar¹, Syed Amreen Begum², Vabuloju Srinidhi³, Dopati Abhilash⁴, Mamidala venu⁵

Assistant Professor, Dept. of CSE-Data Science, ACE Engineering College, Hyderabad, Telangana, India¹

IV B. Tech Students, Department of CSE (Data Science), ACE Engineering College, Hyderabad, Telangana, India^{2,3,4,5}

ABSTRACT: The widespread use of social media and online platforms has made the sharing of news faster and easier than ever before. However, this rapid information exchange has also led to a significant increase in the spread of fake news and misleading content. Such misinformation can influence public opinion, create confusion, and negatively affect social, political, and economic stability. Therefore, identifying and filtering fake news has become an important research problem. Traditional machine learning techniques for fake news detection often rely on manual feature extraction methods such as Bag of Words and TF-IDF. While these techniques can capture word frequency, they struggle to understand the deeper context and meaning of text. Recent advancements in Natural Language Processing (NLP) and deep learning have introduced transformer-based models that are capable of capturing contextual relationships between words. In this project, we propose a fake news detection system based on the BERT (Bidirectional Encoder Representations from Transformers) model. BERT is a powerful transformer-based language model that understands the contextual meaning of words within a sentence. By fine-tuning a pre-trained BERT model on a labeled dataset of news articles, the system can effectively analyze textual content and determine whether the news is genuine or misleading. The proposed approach demonstrates how advanced NLP techniques can be applied to combat misinformation and improve the reliability of digital information sources.

KEYWORDS: Fake News Detection, BERT, Natural Language Processing, Transformers, Deep Learning, Transfer Learning

I. INTRODUCTION

With the rapid expansion of the internet and social media platforms, information can now spread across the world within seconds. While this has improved communication and access to information, it has also made it easier for false or misleading news to circulate widely. Fake news can manipulate public perception, create unnecessary panic, and even influence political or economic outcomes. As a result, developing automated systems that can identify and filter unreliable information has become increasingly important.

Fake news detection is a challenging task because misleading information is often written in a style that resembles legitimate news articles [1]. Traditional text classification approaches rely on statistical features such as word frequency or keyword matching, which are often insufficient for capturing the deeper meaning of language [4][5]. These limitations highlight the need for more advanced techniques capable of understanding contextual relationships in text.

In this project, we present a fake news detection system that utilizes the BERT model, a transformer-based language representation model developed by Google [2]. BERT has shown remarkable performance across a wide range of natural language processing tasks due to its ability to process text in a bidirectional manner [14]. Unlike earlier models that read text in a single direction, BERT analyzes the context of words based on both the preceding and following text.

The proposed system processes news content through multiple stages, including data preprocessing, tokenization, model training, prediction, and evaluation. When a user provides a news statement, the system analyzes the text using the trained BERT model and predicts whether the news is real or fake. To reduce the risk of spreading misinformation, the system displays results only when the news is classified as authentic [6].

Overall, this project demonstrates how modern deep learning techniques and transformer-based architectures can be applied to address the growing problem of misinformation in digital media.

II. LITERATURE SURVEY

The detection of fake news has attracted considerable attention from researchers due to the increasing spread of misinformation on online platforms. Early research in this area relied mainly on traditional machine learning algorithms such as Logistic Regression, Naïve Bayes, Support Vector Machines, and Random Forests [9]. These methods used manually engineered features such as Bag-of-Words, TF-IDF representations, and N-grams to classify news articles. Although these approaches achieved reasonable performance, they were limited in their ability to capture deeper semantic relationships within text. Since these models primarily rely on word frequency patterns, they often struggle to interpret complex sentence structures, sarcasm, or contextual meanings. To overcome these limitations, researchers began exploring deep learning techniques such as Convolutional Neural Networks (CNNs) and Long Short-Term Memory (LSTM) networks for text classification tasks [8] [10]. These models improved fake news detection performance because they could learn patterns directly from the data and capture sequential dependencies in text.

A significant advancement occurred with the introduction of the Transformer architecture by Vaswani et al. in 2017. Transformers use attention mechanisms to understand relationships between words in a sentence, allowing them to process text more efficiently and capture long-range dependencies. Building on the transformer architecture, Google introduced BERT (Bidirectional Encoder Representations from Transformers). BERT quickly became one of the most effective models for natural language understanding tasks. Unlike earlier models that process text in a single direction, BERT reads text bidirectionally, enabling it to understand the context of a word based on both its preceding and following words. Due to its strong contextual understanding, BERT has been widely adopted in various NLP applications, including sentiment analysis, question answering, and fake news detection [11] [12]. Its ability to learn semantic relationships makes it particularly suitable for identifying subtle differences between genuine and misleading information [15].

III. PROPOSED MODEL

The proposed model aims to identify fake news by using a powerful natural language processing model called **BERT (Bidirectional Encoder Representations from Transformers)**. BERT is a transformer-based deep learning model that has shown excellent performance in many language understanding tasks [16]. Unlike traditional machine learning models that rely heavily on manually created features, BERT is capable of understanding the context and meaning of words within a sentence.

In this project, a **pre-trained BERT model** is used as the base model. Since BERT has already been trained on a large amount of textual data, it has a strong understanding of grammar, sentence structure, and word relationships. To adapt it for the fake news detection task, the model is further **fine-tuned using a labeled dataset of real and fake news articles**. This process allows the model to learn patterns that commonly appear in misleading or fabricated news content. A classification layer is added on top of the BERT architecture so that the model can categorize the news into two classes: **real news** and **fake news**. When a user provides a news statement, the system processes the text and passes it through the trained BERT model, which analyzes the contextual relationships within the sentence. Based on this analysis, the system predicts whether the news content is authentic or misleading. By utilizing BERT's ability to understand language context more effectively than traditional models, the proposed system improves the accuracy of fake news detection. This approach demonstrates how modern deep learning techniques can be applied to address the growing issue of misinformation on digital platforms.

IV. METHODOLOGY

The proposed fake news detection system follows a structured workflow consisting of several stages, including data collection, preprocessing, model training, and prediction. Initially, datasets containing both real and fake news articles are collected from publicly available sources. These datasets are combined into a single dataset where each news article is labeled as either **real** or **fake**. This labeled dataset forms the foundation for training and evaluating the model. Before training the model, the textual data undergoes preprocessing. This step involves cleaning the text by removing unnecessary characters, converting text to a consistent format, and preparing it for tokenization. Tokenization converts the text into smaller units that can be understood by the BERT model.

Only the newly added layers and the last few BERT layers are trained on the fake news dataset. This helps the model learn the characteristics of real and fake news. Fine-tuning adjusts the weights of the BERT model with a lower learning rate. This step ensures the model adapts precisely to the fake news dataset while maintaining general language understanding. Fine-tuning adjusts the weights of the BERT model with a lower learning rate. This step ensures the model adapts precisely to the fake news dataset while maintaining general language understanding.

1. Dataset : We begin by collecting fake and real news datasets from various online sources. The datasets are merged into a single corpus, and each news article is assigned a label such as true or fake. This labeled dataset will be used for training and evaluating the model.

2. Obtain the Pre-trained Model: We use a pre-trained BERT model from Hugging Face, which has already been trained on a large corpus of text. This gives the system strong language understanding even before training on fake news data.

3. Create a Base Model: We create a base architecture by adding layers on top of the pre-trained BERT model. This includes adding a classification head so that BERT can be adapted for binary classification (real vs fake).

4. Freeze Layers: The initial layers of BERT are frozen. These layers contain general language understanding and should not be changed. Only the upper layers and classification head will be trained to learn fake-news-specific patterns.

5. Train the New Layers on the Dataset: Only the newly added layers and the last few BERT layers are trained on the fake news dataset. This helps the model learn the characteristics of real and fake news.

6. Improving the Model via Fine-tuning: Fine-tuning adjusts the weights of the BERT model with a lower learning rate. This step ensures the model adapts precisely to the fake news dataset while maintaining general language understanding.

7. Predictions: Once training is completed, the fine-tuned BERT model is used to classify incoming news articles. If the news is real, the system will display "This News is Real". If the news is fake, the system will suppress the output.



Fig 1. Steps for Implementation

V. SYSTEM ARCHITECTURE

The system architecture of the proposed fake news detection model is designed to process news content through multiple stages to determine whether the information is reliable or misleading. Initially, the system receives raw news text either from a dataset or directly from user input. Since the input text may contain unnecessary characters, URLs, punctuation marks, or irrelevant information, a preprocessing step is performed to clean and normalize the text. This includes removing noise, converting text to lowercase, eliminating extra spaces, and preparing the data for further analysis.




Fig 2. System Architecture

After preprocessing, the cleaned data is converted into numerical representations through tokenization and embedding techniques so that it can be understood by the deep learning model. The dataset is then divided into training and testing sets, where approximately **80% of the data is used for training the model and 20% is used for evaluating its performance**. Before being passed into the model, the text undergoes additional preparation steps required by the BERT architecture, including token ID generation and attention mask creation.

The processed input is then fed into the **mini-BERT transformer model**, which analyzes the contextual relationships between words using attention mechanisms. This model extracts meaningful semantic features from the news text. These features are then passed to a deep learning classification layer that learns patterns associated with real and fake news. Based on these learned patterns, the model generates prediction scores that indicate the likelihood of the news being authentic or misleading. Finally, the system evaluates the prediction results and presents the outcome to the user. If the news is classified as real, the system displays it as **reliable news**. If the model predicts the news to be fake, the output is suppressed to prevent the spread of misinformation. This architecture enables the system to efficiently analyze news content and provide reliable classification results.

VI. EXPERIMENTAL RESULT

The developed system was tested using multiple input scenarios to evaluate its performance and reliability. The user interface allows users to enter a single news statement or upload multiple news entries for batch processing.




Fig 3. User Interface

This figure represents the implementation architecture of the fake news detection system. The system is developed using Python along with machine learning and natural language processing libraries such as PyTorch, Hugging Face Transformers, and Scikit-learn.

The implementation includes modules for data preprocessing, model loading, training, prediction, and result visualization. The pre-trained BERT model is fine-tuned using labeled news data to adapt it for the specific task of fake news classification. During training, the model learns important linguistic patterns and contextual relationships that help distinguish between genuine and fake news articles.

The architecture ensures efficient processing of textual data and enables the system to perform predictions in real time.




Fig 4. Single news Detection

The system also supports batch processing, where multiple news articles can be analyzed simultaneously. This feature is particularly useful for large datasets or automated fact-checking systems.




Fig 5 . Batch news detection interface




Fig 6. Batch News detection

VII. CONCLUSION

The project titled “**Semantic Analysis of News Authenticity using BERT**” demonstrates how transformer-based deep learning models can be effectively used to identify misleading or fabricated news content. By leveraging BERT’s ability to understand the contextual meaning of words, the system analyzes news articles more accurately than traditional machine learning methods that rely mainly on simple keyword or frequency-based features. The proposed system follows a structured process that includes text preprocessing, tokenization, contextual feature extraction, and classification to determine whether the given news is real or fake. In addition, the system stores prediction results, user

inputs, and logs in a database, which helps in monitoring performance and maintaining records for future analysis. To reduce the risk of spreading misinformation, the system is designed to display results only when the news is identified as authentic. Although the model shows promising performance, its accuracy largely depends on the quality and diversity of the training dataset. In the future, the system can be improved by supporting multiple languages, integrating real-time news data through APIs, and deploying the application on cloud platforms for large-scale use. Overall, this work demonstrates the potential of modern natural language processing techniques in addressing the growing challenge of fake news and contributes to building more reliable digital information systems.

REFERENCES

- [1] Aljawarneh, Shadi A., and Safa Ahmad Swedat. "Fake news detection using enhanced BERT." *IEEE Transactions on Computational Social Systems* 11.4 (2022): 4843-4850.
- [2] Shishah, Wesam. "Fake news detection using BERT model with joint learning." *Arabian Journal for Science and Engineering* 46.9 (2021): 9115-9127.
- [3] KUMAR, P. ASHOK, GSatish KUMAR, and SETTI NARESH KUMAR. "Improve the Capacity of Uniform Embedding for Efficient JPEG Steganography Based on DCT." (2015).
- [4] Kumarr, P. Ashok, et al. "In-vestigating Context-Aware Sentiment Classification Using Machine Learning Algorithms." *Accelerating Discoveries in Data Science and Artificial In-telligence 1. ICDSAI 2023. Springer Proceedings in Mathematics & Statistics*. Vol. 421. 2024.
- [5] Sunkavalli, Jayaprakash, B. Madhav Rao, M. Trinath Basu, Harish Dutt Sharma, P. Ashok Kumar, and Ketan Anand. "Experimentation Analysis of VQC and QSVM on Sentence Classification in Quantum Paradigm." In *2024 International Conference on Computing, Sciences and Communications (ICCSC)*, pp. 1-5. IEEE, 2024.
- [6] Kumar, P. Ashok. "Event Based Time Series Sentiment Trend Analysis.", ResearchGate
- [7] PANDI, CHIRANJEEVI, THATIKONDA SUPRAJA, P. ASHOK KUMAR, and RALLA SURESH. "A SURVEY: RECOMMENDER SYSTEM FOR TRUSTWORTHY."
- [8] Kumar, P. Ashok, B. Vishnu Vardhan, and Pandi Chiranjeevi. "Correction to: Investigating Context-Aware Sentiment Classification Using Machine Learning Algorithms." In *XVIII International Conference on Data Science and Intelligent Analysis of Information*, pp. C1-C1. Cham: Springer Nature Switzerland, 2023.
- [9] Supraja, Thatikonda, et al. "Lstm-based cloud workload prediction using pso-ga hybrid algorithm." *Security Issues in Communication Devices, Networks and Computing Models*. CRC Press, 2025. 44-52.
- [10] Sunkavalli, Jayaprakash, et al. "Experimentation Analysis of VQC and QSVM on Sentence Classification in Quantum Paradigm." *2024 International Conference on Computing, Sciences and Communications (ICCSC)*. IEEE, 2024.
- [11] Supraja, Thatikonda, et al. "Exploring IoT and 5G in Smart Healthcare: Applications, Challenges and Future Directions." *CVR Journal of Science and Technology* 28.1 (2025): 12-21.
- [13] Supraja, T., Chiranjeevi, P., Kumar, P.A. and Swapna, Y., 2025. Exploring IoT and 5G in Smart Healthcare: Applications, Challenges and Future Directions. *CVR Journal of Science and Technology*, 28(1), pp.12-21.
- [14] Ashok Kumar P, Dr. B. Vishnu Vardhan, "Event Based Sentiment Trend Analysis using Deep Learning Techniques". *Journal of Electrical Systems (JES)*, April 2024, ISSN: 1112-5209, Vol. 20 No. 3, Pg.no: 3077-3086. <https://journal.esrgroups.org/jes/article/view/4728>
- [15] Ashok Kumar P, Dr. B. Vishnu Vardhan, "Event Based Time Series Sentiment Trend Analysis". *Journal of Civil and Environmental Engineering (IJCEE)*, August 2024, ISSN:2096-6717, Vol.12, Issue.3, Page. no: 126-134. doi: 10.1018/IJCEE.2024.12.8.517
- [16] Ashok Kumar P, Dr. B. Vishnu Vardhan (2024) "Event-Driven Context-Aware Sentiment Analysis using BERT - Bi-LSTM for Emotion Insights". *International Journal of Intelligent Systems and Applications in Engineering (IJISAE)*, March 2024, 12(3), 1030–1036. <https://ijisae.org/index.php/IJISAE/article/view/5382>



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details