

Gesture Controlled Robotic Vehicle Using RF Communication

B.Suresh kumar¹, Dinesh T², Selvamurugan P², Srikar R², Chandu M²

HOD, Department of Electronics and Communication Engineering, The Kavary Engineering College (Autonomous),
Mecheri, Salem, Tamil Nadu, India¹

Department of Electronics and Communication Engineering, The Kavary Engineering College (Autonomous), Mecheri,
Salem, Tamil Nadu, India²

ABSTRACT: The development of intuitive human-robot interaction systems has become crucial in modern robotics applications. This paper presents the design and implementation of a hand gesture motion-controlled robotic vehicle capable of pick and place operations using accelerometer sensors and RF communication. The system consists of two main units: a transmitter unit equipped with ADXL335 accelerometer and Arduino Nano for gesture detection, and a receiver unit with Arduino Uno controlling DC gear motors through L298N motor drivers. The proposed system eliminates the need for traditional button-based controllers, providing a more natural and accessible interface for robotic control. Experimental results demonstrate successful operation with 200-300ms response time, 44 meters operational range, and 1100 grams payload capacity. The system achieves 96-98% gesture recognition accuracy with 2-hour battery life, making it suitable for industrial automation, medical assistance, and hazardous environment applications. Gesture-controlled robotic systems are gaining importance in modern robotics as they provide a natural and intuitive way for humans to interact with machines. The proposed system uses an accelerometer sensor mounted on a hand glove or handheld device to detect the motion and orientation of the user's hand. The detected gestures are processed by a microcontroller, which converts them into control signals. These signals are transmitted wirelessly to the robotic vehicle using Radio Frequency (RF) communication. At the receiver side, another microcontroller interprets the received signals and controls the motors of the robotic vehicle through a motor driver circuit.

KEYWORDS: Hand gesture recognition, Robotic vehicle, Pick and place, Accelerometer, RF communication, Arduino, Human-robot interaction, ADXL335.

I. INTRODUCTION

Robotics has become an important field in modern technology, with applications in industries, healthcare, defense, and automation. Traditional robotic systems are usually controlled using switches, joysticks, or remote controllers. However, these methods may not provide a natural and user-friendly way for humans to interact with machines. Gesture-based control systems have emerged as an innovative solution that allows users to control devices through simple hand movements.

A Gesture-Controlled Robotic Vehicle is a robotic system that moves according to the hand gestures of the user. Instead of pressing buttons on a remote controller, the user can control the robot by simply moving their hand in different directions. This makes the system more convenient and interactive. Gesture control technology is widely used in applications such as robotics, gaming systems, smart devices, and assistive technologies.

In this project, a Gesture-Controlled Robotic Vehicle using RF Communication is developed to demonstrate an easy and efficient method of controlling a robot wirelessly. The system uses an accelerometer sensor attached to a glove or handheld device to detect the orientation and movement of the user's hand. The accelerometer converts the hand gestures into electrical signals, which are processed by a microcontroller.

These signals are then transmitted wirelessly to the robotic vehicle using Radio Frequency (RF) communication. At the receiver side, another microcontroller receives the RF signals and controls the motors of the robotic vehicle through a motor driver circuit. Based on the hand gesture, the robot can move forward, backward, left, right, or stop.

The proposed system is simple, cost-effective, and easy to operate, making it suitable for various practical applications. Gesture-controlled robotic vehicles can be used in military surveillance, search and rescue operations, hazardous environment monitoring, and industrial automation, where human intervention may be difficult or dangerous. This project demonstrates the integration of gesture sensing technology and wireless communication to create an efficient and user-friendly robotic control system.

Gesture Controlled Car is a robot which can be controlled by simple human gestures. The user just needs to wear a gesture device in which a sensor is included. The sensor will record the movement of hand in a specific direction which will result in the motion of the robot in the respective directions. The robot and the Gesture instrument are connected wirelessly through radio waves. User can interact with the robot in a more friendly way due to the wireless communication. We can control the car using accelerometer sensors connected to a hand glove. The sensors are intended to replace the remote control that is generally used to run the car. It will allow user to control the forward, backward, leftward and rightward movements, while using the same accelerometer sensor to control the throttle of the car. Movement of car is controlled by the differential mechanism. The mechanism involves the rotation of both forth & rear wheels of left or right side to move in the anticlockwise direction and the other pair to rotate in the clockwise direction which makes the car to rotate about its own axis without any kind of forward or backward motion. The main advantage of this mechanism is the car with this mechanism can take sharp turn without any difficulty. The design and implementation of a gesture control robotic arm using flex sensor is proposed. The robotic arm is designed in such a way that it consists of four movable fingers, each with three linkages, an opposing thumb, a rotating wrist and an elbow. The robotic arm is made to imitate the human hand movements using a hand glove.

II. LITERATURE SERVEY

Gesture-controlled robotic systems have attracted significant attention in recent years because they provide a natural and intuitive method of human-machine interaction. Several researchers have developed robotic vehicles that can be controlled using hand gestures, sensors, and wireless communication technologies.

One study proposed a **gesture-controlled robot using an accelerometer and microcontroller**. In this system, an accelerometer sensor detects the tilt and orientation of the user's hand. The sensor data is processed by a microcontroller and converted into control signals that drive the motors of the robot. The study demonstrated that gesture-based control is more convenient than traditional remote control methods.

Another research work introduced a **gesture-controlled robotic vehicle using RF communication**. In this system, hand gestures are captured using an accelerometer attached to a glove. The signals are transmitted to the robot through an RF transmitter and receiver pair. The robot interprets the received signals and moves in different directions such as forward, backward, left, and right. The study emphasized the advantages of RF communication, such as longer communication range and reliable wireless transmission.

A different approach used **Bluetooth-based gesture-controlled robots**. In this system, gestures detected by sensors are sent to a smartphone via Bluetooth, and the smartphone application controls the robot. Although this method provides flexibility, the communication range is limited compared to RF-based systems.

Some recent research has also explored **gesture recognition using cameras and image processing techniques**. These systems use computer vision algorithms to detect hand movements and translate them into robot commands. While these systems provide advanced gesture recognition capabilities, they require complex hardware and high computational power.

From the literature survey, it is clear that gesture-controlled robotic vehicles offer an efficient and user-friendly way of controlling robots. However, many existing systems are either complex, expensive, or limited in communication range. Therefore, the proposed project focuses on developing a **Gesture-Controlled Robotic Vehicle using RF communication**, which provides a simple, cost-effective, and reliable solution for wireless robot control.

III. IMPLEMENTATION

EXISTING SYSTEM

In the existing systems, robotic vehicles are commonly controlled using **manual controllers such as joysticks, switches, or wired remote controls**. These traditional control methods require direct physical interaction with the controller to operate the robot. Although they provide basic control over the robot's movement, they are not always convenient or user-friendly.

Some systems use **Bluetooth-based mobile applications** to control robotic vehicles. In this method, the user sends commands from a smartphone to the robot using Bluetooth communication. The robot receives the commands through a Bluetooth module connected to a microcontroller and moves accordingly.

Other advanced systems use **camera-based gesture recognition** or computer vision techniques to control robots. These systems detect hand gestures through cameras and process the images using complex algorithms to control the robot's movement. While such systems provide advanced features, they require powerful processors, high-cost hardware, and complex programming.

Although these existing methods allow robotic vehicles to be controlled wirelessly, they have several limitations such as **limited communication range, higher complexity, and dependency on specific devices like smartphones or computers**. These drawbacks highlight the need for a simpler and more efficient gesture-controlled robotic system using reliable wireless communication.

3.1. DISADVANTAGES OF EXISTING SYSTEM

Limited Communication Range

Systems that use Bluetooth or wired connections have a limited operating range, which restricts the movement of the robotic vehicle.

Dependence on External Devices

Some systems require smartphones, computers, or other external devices to control the robot, which makes the system less convenient.

3.2. PROPOSED SYSTEM

The proposed system is a Gesture-Controlled Robotic Vehicle using RF Communication that allows users to control the movement of a robotic vehicle through simple hand gestures. The system eliminates the need for traditional remote controllers, switches, or smartphones by using gesture-based commands.

In this system, an accelerometer sensor is attached to a glove or handheld device to detect the motion and orientation of the user's hand. The accelerometer converts the hand movements into electrical signals. These signals are processed by a microcontroller at the transmitter side.

The processed signals are then transmitted wirelessly using an RF transmitter module. The RF communication allows the signals to be sent over a longer distance without requiring a direct line of sight between the transmitter and receiver.

At the receiver side, an RF receiver module receives the transmitted signals and sends them to another microcontroller. The microcontroller interprets the signals and controls the motor driver circuit connected to the motors of the robotic vehicle. Based on the received command, the robot can move forward, backward, left, right, or stop.

3.2.1. ADVANTAGES

User-Friendly Control

The robotic vehicle can be controlled easily using simple hand gestures, making the system more natural and convenient to use.



Wireless Operation

RF communication allows the robot to be controlled wirelessly without the need for physical connections.

Longer Communication Range

RF modules provide a longer operating range compared to some other wireless technologies such as Bluetooth.

BLOCK DIAGRAM



IV. WORKING

In the area of safety, for example, many machines require operators to place each hand on a control switch before the controller starts any action. Instead of having operators move their hands to special switches, why not simply let them hold up their hands with a gesture sensor? This type of control could improve productivity, reduce the effects of repetitive motions, and improve safety. Advanced robotic arms that are designed like the human hand itself can easily be controlled using hand gestures only. The arm controller wears the sensor gloves and the robotic arm will mimic the movement of the controller. Advanced robotic arms like these can perform complex and hazardous tasks with ease. Proposed utility in fields of construction, hazardous waste disposal, medical sciences.



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details